

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

|   |          |              |     |          | TEST GRO   |                     | RMAT                                       | ION                                |  |                                      |                  |  |  |
|---|----------|--------------|-----|----------|------------|---------------------|--|------------------------------------|--|--------------------------------------|------------------|--|--|
| MODE  | TI       | EST GROUP    |     | VEHIC    | LE CLASS(E | S)                  |  | FUEL CATEGORY                      |  |                                      | FUEL TYPE        |  |  |
| 2020  | D LV     | GAV05.2NDE   |     |          | PC         |                     | DED  | DEDICATED SINGLE FUEL<br>VEHICLE   |  |                                      | GASOLINE         |  |  |
| USEFUL LIFE (miles) VEHICLE EMISSION  |          |              |     |          |            |                     | CATEGORY INTERIM / INTERMEDIATE IN-USE STD |                                    |  |                                      |                  |  |  |
| EX  | H/ORVR   | EVAP         |     | 101000   | FTP        |                     | SFTP                                       |                                    | FTP  |                                      | SFTP             |  |  |
| 1   | 50000    | 150000       |     | LEV3     | LEV160     | LEV 3               | COMPO                                      | SITE                               | 1  | PM                                   |                  |  |  |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL<br>SYSTEMS                                  |          |              |     |          |            |                     |  | ENGINE DISPLACEMENT<br>(L)         |  |                                      |                  |  |  |
| 1   | 211      | C, 2WR-HO2S, | 2HC | 2S, DFI+ | SFI, AIR   |                     | FUL  | 4                                  | *  | 1.000                                |                  |  |  |
| *   |          |              | *   |          |            |                     | PART                                       | PARTIAL ALL MODELS 5.2             |  |                                      |                  |  |  |
| * * PARTIAL WITH *  |          |              |     |          |            |                     |  | *                                  |  |                                      |                  |  |  |
|   |          | EV           | APO | RATIVE & | REFUELING  | EVAP/               | ORVR)                                      | FAMIL                              | INFORMATIO   | N                                    |                  |  |  |
| EVA   | AP / ORV | R FAMILY     | EVA | PORATIVE | STD CATE   | GORY                |  | EVAP EMISSION STD<br>VEHICLE CLASS |  |                                      | SPECIAL FEATURES |  |  |
|   | LVGAR01  | 55NAL        |     | L        | EV 2       |                     |  | E                                  | PC   | *                                    |                  |  |  |
|   |          |              |     | E        | EMISSION C | REDIT IN            | IFORM                                      | ATION                              |  |                                      |                  |  |  |
| NMOG+NOX FLEET AVE.<br>CREDIT FOR EXTENDED<br>WARRANTY NMOG CREDIT FOR NON<br>ZERO-EVAP |          |              |     |          |            | NMOG CREDIT FOR DOR |  |                                    | R  | OPTIONAL EXH. STD<br>FOR WORK TRUCKS |                  |  |  |
|   |          | N            |     |          | N          |                     |  |                                    | N  | N                                    |                  |  |  |
| NMOG AND FLEET AVERAGE INFORMATION  |          |              |     |          |            |                     |  |                                    |  |                                      |                  |  |  |
| NMOG<br>RAF   |          |              |     |          | 0-3750 L   |                     |  |                                    | NMOG+NOX FLEET STD<br>MDV (10,001-14,000<br>GVWR) (g/mi) |                                      |                  |  |  |
| *   | *        | 1.10         |     | 0.03     | 0          | .065                |  |                                    | 0.074  |                                      | *                |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC.

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>1374</u> day of May 2019.

Allen Lyons, Chief Emissions Compliance, Automotive Regulations and Science Division

CALIFORNIA AIR RESOURCES BOARD

FUEL TYPE

VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0142 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g. gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

|             |     |                          | NMOG+NOx<br>(g/mi) |         | CO<br>(g/mi) |     | NOx<br>(g/mi) |                 | HCHO<br>(mg/mi) |     | PM<br>(g/mi) |          |  |  |  |
|-------------|-----|--------------------------|--------------------|---------|--------------|-----|---------------|-----------------|-----------------|-----|--------------|----------|--|--|--|
|             |     |                          | CERT               | STD     | CERT         | STD | CERT          | STD             | CERT            | STD | CERT         | STD      |  |  |  |
| FTP@50K     |     | *                        | *                  | *       | *            | *   | *             | *               | *               | *   | *            | *        |  |  |  |
| FTP@UL      | TIE | OLINE-<br>R3 E10<br>PREM | 0.0525             | 0.160   | 0.42         | 4.2 | *             | *               | *               | 4   | 0.0010       | 0.003    |  |  |  |
| 50°F @4K    | TIE | OLINE-<br>R3 E10<br>PREM | 0.0698             | 0.320   | 0.43         | 4.2 | *             | *               | 1.4             | 30  |              |          |  |  |  |
| 1000        |     |                          |                    |         |              |     | N             | NMOG+NOx (g/mi) |                 |     | CO (g/mi)    |          |  |  |  |
| FUEL TYPE   |     |                          |                    |         | CE           | RT  | STD           | CER             | T               | STD |              |          |  |  |  |
| HWFET @ 50K |     |                          | *                  |         |              |     |               | <del>.</del>    | *               |     |              | 間間間になった。 |  |  |  |
| HWFET @ UL  |     |                          | GASOLIN            | E-TIER3 | E10 PREN     | 4   | 0.0           | 235             | 0.160           |     |              |          |  |  |  |
| 20°F @ 50K  |     |                          | GASOLIN            | E-TIER3 | E10 PREN     | 4   |               |                 |                 | 1.9 | 7            | 10.0     |  |  |  |

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

|              |                              | 3                       | FIF EXHAUSI        | EMISSION       | STAND          | ANDS AND           | GERTIFIC          | ATION L      |          | <b>.</b>        |              |               |  |
|--------------|------------------------------|-------------------------|--------------------|----------------|----------------|--------------------|-------------------|--------------|----------|-----------------|--------------|---------------|--|
|              |                              |                         |                    | US06           |                | SC03               | SC03              |              |          | COMPOSITE       |              |               |  |
|              | FUEL TYP                     | E                       | NMOG+NOx<br>(g/mi) | c CO<br>(g/mi) |                |                    | OG+NOx<br>(g/mi)  | CO<br>(g/mi) |          | DG+NOx<br>g/mi) | CO<br>(g/mi) | PM<br>(mg/mi) |  |
| @ 4K         | *                            | CERT                    | *                  | *              | *              |                    | *                 | *            |          |                 |              |               |  |
| •            |                              | STD                     | *                  | *              |                |                    | *                 | *            |          |                 |              |               |  |
|              |                              | CERT                    | *                  | * *            |                | . 0                | *                 | *            | 0        | .0323           | 0.31         | *             |  |
| @ UL         | GASOLINE<br>TIER3 E1<br>PREM |                         | · · · · •          | *              |                | 6                  | *                 | *            | 0.083    |                 | 4.2          | *             |  |
|              |                              | BIN                     |                    |                | and the second |                    | the design of the |              | 0        | .160            |              |               |  |
|              |                              | WHOLE V                 | EHICLE EVAP        | ORATIVE E      | MISSION        | STANDA             | RDS AND C         | ERTIFIC      | ATIO     | N LEVELS        | 6            |               |  |
|              |                              |                         |                    | WHOLE V        | /EHICLE        | EVAPORA            | TIVE TEST         | ING          |          |                 |              |               |  |
|              |                              |                         |                    | IS (g/test) (  | D UL           | 2DHS (g/test) @ UL |                   |              |          | RL (g/mi) (     |              | ĝ UL          |  |
|              |                              |                         | CERT               | STD            | FEL            | CERT               | STD               | FE           | FEL CERT |                 |              | STD           |  |
| LVGAR0155NAL |                              | GASOLI<br>TIER3<br>PREM | E10 0.491          | 0.50           | *              | 0.354              | 0.65              | . *          | *        |                 |              | 0.05          |  |

| A  | VOLKSWAGEN GROUP<br>OF AMERICA, INC.                   |          |         | P         | Executive Order: A-413-0142<br>New Passenger Cars, Light-Duty Trucks and<br>Medium-Duty Vehicles<br>Page 4 of 4 |                                 |         |  |          |                      |                      |  |  |  |
|--|--|----------|---------|-----------|---|---------------------------------|---------|--|----------|----------------------|----------------------|--|--|--|
| ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS  |  |          |         |           |   |                                 |         |  |          |                      |                      |  |  |  |
|  |  |          |         |           | en en   | FUEL ONLY EVAP & CANISTER BLEED |         |  |          |                      |                      |  |  |  |
| EVAPORATIVE<br>FAMILY  | ORVR (g/gallon) @ UL                                   |          |         | FUEL TYPE |   | 3DHS RIG TEST<br>(g/test) @ UL  |         | the second s |          | BLEED C<br>TEST (g/t | ANISTER<br>est) @ 4K |  |  |  |
|  | FUEL TYPE  | E CERT   | STD     |           |   | CERT                            | STD     | CERT   | STD      | CERT                 | STD                  |  |  |  |
| LVGAR0155NAL   | GASOLINE-<br>GASOLINE-<br>TIER3 E10 0.011 0.20<br>PREM |          |         | *         | * * *   |                                 |         |  | *        | *                    | *                    |  |  |  |
| E  | EFFECTIVE  | E LEAK D | IAMET   | ER STA    | NDAR  | D AND CI                        | RTIFICA | TION LEV   | EL (INCH | IES)                 |                      |  |  |  |
| EVAPORATIVE  | FAMILY   | LEAI     | K FAMIL | Y         |   | CE                              | RT      | r STD  |          |                      |                      |  |  |  |
| *  |  |          | *       | * *       |   |                                 |         |  |          | *                    |                      |  |  |  |
| LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-<br>3500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium-<br>duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family<br>emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle;<br>JLEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst;<br>ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or<br>SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH30C: ammonia oxidation catalyst; CTOX/PTOX:<br>continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S:<br>neated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor;<br>RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR; exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE:<br>secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI:<br>direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/S: full/partial/partial with<br>fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2)<br>suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel;<br>E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; AX: semi-automatic transmission; AMS:<br>automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in<br>hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warr |  |          |         |           |   |                                 |         |  |          |                      |                      |  |  |  |
|  | 2020 N   | NODEL    | YEA     | R: VE     | HICI  | LE MO                           | DELS    | INFORI   | MATIO    | N                    |                      |  |  |  |
|  |  |          |         |           |   |                                 |         | DE EV.   | APORATIV | E EXH                |                      |  |  |  |

| MAKE        | MODEL          | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE<br>FAMILY | EXH<br>ECS | OBD |
|-------------|----------------|-----------|------------|------------|-----------------------|------------|-----|
| LAMBORGHINI | HURACAN        | PC        | 5.2        | AMS7       | LVGAR0155NAL          | 1          | P   |
| LAMBORGHINI | HURACAN 2WD    | PC        | 5.2        | AMS7       | LVGAR0155NAL          | 1          | P   |
| LAMBORGHINI | HURACAN SPYDER | PC        | 5.2        | AMS7       | LVGAR0155NAL          | 1          | P   |
| LAMBORGHINI | HURACAN SPYDER | PC        | 5.2        | AMS7       | LVGAR0155NAL          | 1          | P   |

.