\sim	CALIFORNIA
A	CALIFORNIA
KAN	CALL ONNIA
NIC IN M	AIR RESOURCES BOARD

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FOR	ATION				
MODE	TEST COOLID I			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2020	LV	GAV05.2NBE	PC tas second in 1				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
191	USEFUL	LIFE (miles)	a de la	VEH	ICLE EMIS	SION C	ATEG	ORY	INTERIM / INT	ER	MEDIATE IN-USE STD	
EXH/ORVR EVAP			FTP. book 9 as 7 b			SF	(P. C. C.	FTP		SFTP		
15	150000 150000			LEV3	3 LEV160 LEV 3 (MPOSITE	PM		PM	
SPE	CIAL FE	ATURES & EX				DL	100	OBD S	TATUS	E	NGINE DISPLACEMENT (L)	
1 21	WU-TWC	, 2TWC, 2WR-	но2	S, 2HO2S,	DFI+SFI,	AIR	\$ 7	FULL	*	1000	Phate Barris and Phate	
*			;	*			P	PARTIAL ALL MODELS		STANS IN	5.2	
*		2	,	*			- <u></u>	TIAL WITH	*	-		
		E	VAP	ORATIVE &	REFUELING	G (EVAI	PIOR	VR) FAMILY	INFORMATION			
EVA	P / ORV	RFAMILY	EV	APORATIVE	STD CATE	GORY	DRY EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
I	LVGAR0155NAL				LEV 2			PC			*	
				E	MISSION C	REDIT	INFO	RMATION				
	EDIT FO	X FLEET AVE. R EXTENDED RANTY		NMOG CREDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N					N				N		N	
				NMOG	AND FLEE	TAVE	RAGE	INFORMA	ΓΙΟΝ			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO HCHO/NMHC RATIO HCHO/NMHC RATIO (g/mi)				(0-3750					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		0.03		0.065			0.074		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

CALIFORNIA AIR RESOURCES BOARD

VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0143 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

135

HALL TONI

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

(1) 本国家公司在1997年19月1日(1) 本区和19月1日(1) 本国人的

公共400组合「CTCT运行中的网络公司运输

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this $24/\frac{1}{2}$ day of May 2019.

Durever

Allen Lyons, Chief Compliance, Automotive Regulations and Science Division

113-13124 XCR+DOA (02)-0-20120-0-2020 (020-0-2020-0-2020)

eenta amateria em

bes én Rhademand for Nation Nations a Pracédiane Constitui Engrée (Displadoreman Reference militére Samhi OBE-Constantium Earlightón Support de Land Cartina Egele Le Leis and Action de remainement (SDV) over 45,000 paralas in GVNR Repet in tha Europhie Chief a publication (SD2 and the Sector 1981) e geoblaciae foi MOV nontrage to 15 OCE Sector 199 Geoble (1903 athlift) as proteche)

Executive Order: A-413-0143 New Passenger Cars, Light-Duty Trucks and VOLKSWAGEN GROUP CALIFORNIA AIR RESOURCES BOARD Medium-Duty Vehicles OF AMERICA, INC. Page 3 of 4 ATTACHMENT EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP FUEL TYPE NMOG+NOx co NOx нсно PM (mg/mi) (g/mi) (g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT STD CERT STD CERT STD * FTP@50K * * * * * * * * * * GASOLINE-0.7 0.003 FTP@UL TIER3 E10 0.0866 0.160 0.67 4.2 4 0.0010 PREM GASOLINE-0.1154 0.320 0.37 4.2 2.4 30 TIER3 E10 50°F @4K PREM NMOG+NOx (g/mi) CO (g/mi) FUEL TYPE STD CERT STD CERT * * HWFET @ 50K GASOLINE-TIER3 E10 PREM 0.0466 0.160 HWFET @ UL 2.02 10.0 GASOLINE-TIER3 E10 PREM 20°F @ 50K SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS SC03 COMPOSITE US06 NMOG+NOx PM FUEL TYPE NMOG+NOx CO PM NMOG+NOx CO CO (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) (mg/mi) (g/mi) (g/mi) * CERT * * @ 4K + STD * * * * * * 0.0685 0.57 * CERT * 3.0 * GASOLINE-TIER3 E10 STD * 6 * * 0.083 4.2 * @ UL PREM 0.160 BIN WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING RL (g/mi) @ UL **EVAPORATIVE** FUEL TYPE 2DHS (g/test) @ UL 3DHS (g/test) @ UL FAMILY CERT STD FEL CERT STD FEL CERT STD GASOLINE-TIER3 E10 * 0.354 0.65 * 0 0.05 0.491 0.50 LVGAR0155NAL PREM

	n new Organia 1995 - Angel Angel		a ald	VOLKS	SWAGEN	GROU	P	New Pa		cutive Orde ger Cars, L		
AN	CALIF	ORN RCES B	OARD		AMERICA		1. 19				edium-Dut	
ORVR / FU	EL ONLY / CA	ANISTER	BLEED	EVAPORA	ATIVE EN	ISSIO	N STAND	ARDS A	ND C	ERTIFICA	TION LEV	ELS
				3 J 4 33	建制建筑 医白红的	FUEL (ONLY EV	a the state of the	A CALLER	TER BLEE	A CONTRACTOR OF THE OWNER	-
EVAPORATIVE FAMILY	'gallon) (jallon) @ UL		YPE	1444 (14) 7 (million 14)	IG TEST	(g	/test)		BLEED C. TEST (g/t	est) @ 4	
an ang sa	FUEL TYPE	CERT	STD	California de la constante de	in the	CERT	STD	CEI	RT	STD	CERT	STD
LVGAR0155NAL	GASOLINE- TIER3 E10 PREM	0.011	0.20			* *		*		+*** • 4:1 Neture	*	*
A.	EFFECTIVE	LEAK D	IAMET	ER STAN	IDARD A	ND CI	ERTIFIC	ATION	LEV	EL (INCHI	ES)	
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y		CE	RT				STD	
*	140	197	*	- 28 ⁰ - 1		00	*	1.08.	1		* .	
ILEV: ultra LEV; DSTWC: adsorb CRC/SCR-N or ontinuous/periodi eated/oxygen se DQS: reductant econdary air injec irect/indirect fuel nes on-board dia	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/- gnostic: DOR	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo direct oz	vehicle; ght rating EV: zero sorbing c atalytic ro esel part S: wide ra ammonia ric driver /super ch	ECS: emis ; LVW: load o-emission v atalyst; WU eduction-ur ticulate filte ange/linear sensor; EC n); PAIR: p narger; CA ucina: HCT	ssion con ded vehicle; T J: warm-u rea/ammo r (active) r/heated a GR: exha ulsed AIF C: charge r hydroca	trol syst cle weig ZEV: tr ponia; NH ; GPF: I uir-fuel r ust gas 2; SFI/M e air coo rbon tra	tem; CER ht; ALVW: ansitional yst; NAC: 13OC: am PM filter fo atio sensc recirculati IFI: seque oler; FFH: ap; BCAN:	T: certifi adjuste ZEV; TV NOx ad monia o or spark- or; NOX on; EGI ntial/mu fuel fired bleed o	cation ed LV WC/C sorpti xidati -ignite S: NC RC: E Itipor d hea carbon	h; STD: star W; LEV: lov C: 3-way/o ion catalyst ion catalyst ad engine; H x sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p	w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM so AIR/AIRE: on; DFI/IFI full/partial/p prefix 2: pa	: family vehicle; talyst; OX: : ensor; : artial wit rallel; (2)
mission limit; GV JLEV: ultra LEV; 3 DSTWC: adsorb CRC/SCR-N or 9 ontinuous/periodi eated/oxygen se RDQS: reductant of econdary air inject irect/indirect fuel nes on-board dia uffix: series; CNC c10: "10%" ethano ontinuously varia utomated manua ybrid electric veh ome/select mode	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/ gnostic; DOR G/LNG: compr ol ("90%"gaso ble transmissi I-selectable tr icle; NMOG +	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo direct oz essed/liqu line) fuel; on; SCV: ansmissic NOx Flee	vehicle; ght rating EV: zero sorbing c atalytic re esel part S: wide ra ammonia ric driver /super ch cone redu uefied na A: auton selectab on; OT: o et Ave. C	ECS: emis ; LVW: load o-emission f atalyst; WU eduction-ur ticulate filte ange/linear sensor; EC h); PAIR: p harger; CA ucing; HCT tural gas; I natic (with I ble continue ther transm Credit for Ex	ssion con ded vehicle; T J: warm-u rea/ammo ar (active) /heated a GR: exha ulsed AIF C: charge hydroca LPG: lique lockup); N bously vari nission; A xtended V	trol syst le weig ZEV: tr p cataly cataly ; GPF: 1 ir-fuel r ust gas ; SFI/M atr coo rbon tra efied pe A: manu able tra kER: all- Varrant	tem; CER' ht; ALVW: ansitional yst; NAC: 13OC: am PM filter for atio sensor recirculati IFI: seque ler; FFH: ap; BCAN: troleum g- ial transm nsmission -electric ra y: N = no o	T: certifi adjuste ZEV; TV NOx ad monia o or spark- r; NOX on; EGF ntial/mu fuel fired bleed c as; E85 ission; \$; AM: at nge; EA credits, '	cation ad LV WC/C sorpti xidati -ignite S: NC RC: E Itipor d hea :arbon : "85% SA: se utoma AER: Y = c	h; STD: star W; LEV: lov DC: 3-way/o ion catalyst ion catalyst ad engine; H Dx sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p 6" ethanol (emi-automa ated manua equivalent / redits, S = c	ndard; FEL w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM s AIR/AIRE: on; DFI/IFI ull/partial/p prefix 2: pa "15%"gasc tic transmi I transmiss AER; PHEY credits for	: family vehicle; talyst; OX: : ensor; : artial wit rallel; (2) line) fue ssion; CV ion; AMS
LEV: ultra LEV; 3 DSTWC: adsorb CRC/SCR-N or 5 ontinuous/period eated/oxygen se DQS: reductant econdary air inject irect/indirect fuel nes on-board dia uffix: series; CNC 10: "10%" ethanc ontinuously varia utomated manua ybrid electric veho ome/select mode	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/ gnostic; DOR: G/LNG: compr of ("90%"gaso ble transmissi I-selectable tr icle; NMOG + ils	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo direct oz essed/liqu line) fuel; on; SCV: ansmissic NOx Flee	vehicle; ht rating EV: zero sorbing c atalytic re- esel part S: wide ra- ammonia ric driver /super ch- cone redu- uefied na- A: auton selectab- on; OT: o- et Ave. C	ECS: emis ; LVW: load o-emission f atalyst; WU eduction-ur ticulate filte ange/linear sensor; EC h); PAIR: p harger; CA ucing; HCT tural gas; I natic (with I ble continue ther transm Credit for Ex	ssion con ded vehicle; T J: warm-u rea/ammo ar (active) /heated a GR: exha ulsed AIF C: charge hydroca LPG: lique lockup); N bously vari nission; A xtended V	trol syst le weig ZEV: tr ip cataly onia; NF ; GPF: 1 iir-fuel r ust gas 8; SFI/M e air coc rbon tra efied pe A: manu able tra kER: all- Varranty	tem; CER' ht; ALVW: ansitional yst; NAC: 13OC: am PM filter for atio sensor recirculati IFI: seque ler; FFH: ap; BCAN: troleum g- ial transm nsmission -electric ra y: N = no o	T: certifi adjuste ZEV; TV NOx ad monia o or spark- r; NOX on; EGI ntial/mu fuel fired bleed c as; E85 ission; \$; AM: au nge; EA credits, `	cation ed LV WC/C sorpti xidat -ignite ignite 	n; STD: star W; LEV: lov DC: 3-way/o ion catalyst ion catalyst ed engine; H ix sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p 6" ethanol (emi-automa ated manua equivalent / redits, S = c	ndard; FEL w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM sr AIR/AIRE: on; DFI/IFI full/partial/p prefix 2: pa "15%"gasc tic transmis I transmiss AER; PHEN credits for	: family vehicle; talyst; OX: : ensor; : artial wit rallel; (2) line) fue ssion; CV ion; AMS
LEV: ultra LEV; 3 DSTWC: adsorb CRC/SCR-N or S ontinuous/periodi eated/oxygen sei DQS: reductant e condary air inject rect/indirect fuel nes on-board dia uffix: series; CNC 10: "10%" ethano ontinuously varia utomated manua /brid electric veh ome/select mode	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/- gnostic; DOR compro- ble transmissi I-selectable tr icle; NMOG + is 2020 M	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo direct oz essed/liqu line) fuel; on; SCV: ansmissic NOx Flee	vehicle; ht rating EV: zero sorbing c atalytic re- esel part S: wide ra- ammonia ric driver /super ch- cone redu- uefied na- A: auton selectab- on; OT: o- et Ave. C	ECS: emis ; LVW: load -emission natalyst; WU eduction-ur ticulate filte ange/linear sensor; EC h); PAIR: pharger; CAM ucing; HCT tural gas; I natic (with I ble continue ther transm Credit for Ex	ssion con ded vehic vehicle; T J: warm-u rea/ammo r (active) /heated a GR: exhal ulsed AIF C: charge : hydroca lockup); N ously vari nission; A xtended V	trol syst cle weig ZEV: tr up cataly onia; NF ; GPF: 1 iir-fuel r ust gas c; SFI/M e air coc rbon tra efied pe A: manu able tra kER: all- Varrant MO	tem; CER' ht; ALVW: ansitional yst; NAC: 13OC: am PM filter for atio senso recirculati IFI: seque oler; FFH: ap; BCAN: troleum g ial transm nemission electric ra y: N = no o	T: certifi adjuste ZEV; TV NOx ad monia o or spark- r; NOX on; EGI ntial/mu fuel fired bleed c as; E85 ission; \$; AM: au nge; EA credits, `	cation cation WC/C Sorpt xidat cignite S: NC RC: E RC:	h; STD: star W; LEV: lov DC: 3-way/o ion catalyst ion catalyst ed engine; H ix sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p %" ethanol (emi-automa ated manua equivalent / redits, S = c	ndard; FEL w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM sr AIR/AIRE: on; DFI/IFI full/partial/p porefix 2: pa "15%"gasc tic transmi I transmiss AER; PHEN credits for	: family vehicle; talyst; : OX: : ensor; : artial wir rallel; (2 line) fue ssion; C ion; AM. /: plug-in
LEV: ultra LEV; 3 DSTWC: adsorb CRC/SCR-N or S ontinuous/periodi ated/oxygen se DQS: reductant acondary air inject rect/indirect fuel hes on-board dia uffix: series; CNC 10: "10%" ethand ontinuously varia utomated manual ybrid electric veh ome/select mode	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/- gnostic; DOR compro- ble transmissi I-selectable tr icle; NMOG + is 2020 M	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo c direct oz essed/liqu line) fuel; on; SCV: ansmissic NOx Flee DDEL R8	vehicle; ht rating EV: zero sorbing c atalytic re- esel part S: wide ra- ammonia ric driver /super ch- cone redu- uefied na- A: auton selectab- on; OT: o at Ave. C	ECS: emis ; LVW: loan -emission v atalyst; WU eduction-ur ticulate filte ange/linear sensor; EC n); PAIR: p narger; CA ucing; HCT tural gas; I natic (with l be continue ther transn Credit for E) R: VEI H CLASS PC	ssion con ded vehic vehicle; T J: warm-u rea/ammo ar (active) /heated a GR: exha ulsed AIF C: charge hydroca LPG: liqui lockup); N busly vari nission; A xtended V HICLE ENGINE	trol syst cle weig ZEV: tr ip cataly onia; NF; GPF: I ir-fuel r ust gas croon tra efied pe <i>I</i> : manuable tra ER: all- Varranty MO	tem; CER' ht; ALVW: ansitional yst; NAC: 13OC: am PM filter for atio senso recirculati IFI: seque oler; FFH: ap; BCAN: troleum g ial transm nsmission electric ra y: N = no o DELS TRANS TY AMS7	T: certifi adjuste ZEV; TN NOx ad monia o or spark. r; NOXS on; EGI ntial/mu fuel fired bleed c as; E85 ission; S ; AM: at nge; EA credits, `` INFC	cation ed LV WC/C sorpti xidat -ignite S: NC RC: E ltipor d hea carbon SA: se utoma AER: Y = c DRN EVA	n; STD: star W; LEV: lov OC: 3-way/o ion catalyst ion catalyst ed engine; H bx sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p 6" ethanol (emi-automa ated manua equivalent / redits, S = c MATION PORATIVE FAMILY AR0155NAJ	ndard; FEL w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM sr AIR/AIRE: on; DFI/IFI ull/partial/p prefix 2: pa "15%"gasc tic transmis AER; PHEN credits for	: family vehicle; talyst; OX: ensor; artial wi rallel; (2 line) fue ssion; C ion; AM /: plug-i
LEV: ultra LEV; 1 DSTWC: adsorb CRC/SCR-N or S ontinuous/period eated/oxygen sei DQS: reductant econdary air injed rect/indirect fuel hes on-board dia uffix: series; CNC 10: "10%" ethanc ontinuously varia utomated manua ybrid electric veh ome/select mode MAKE AUD I	WR: gross ve SULEV: super ing TWC; HAC SCRC-NH3: so ic trap oxidize nsor; WR-HO2 quality sensor ction (belt driv injection; TC/3 gnostic; DOR: S/LNG: compro- ble transmissi I-selectable tr icle; NMOG + iss 2020 M	hicle weig ULEV; Z C: HC ads elective c r; DPF: di 2S or AFS ; NH3S: a en)/(elect SC: turbo c direct oz essed/liqu line) fuel; on; SCV: ansmissic NOx Flee DDEL R8	vehicle; ht rating EV: zero sorbing c atalytic re- esel part S: wide ra- ammonia ric driver /super ch- cone redu- uefied na- A: auton selectab- on; OT: o at Ave. C	ECS: emis ; LVW: load -emission f atalyst; WU eduction-ur ticulate filte ange/linear sensor; EC h); PAIR: p narger; CA ucing; HCT tural gas; I matic (with I ble continue ther transm Credit for Ex R: VEI H CLASS PC	ssion con ded vehic vehicle; T J: warm-u rea/ammo r (active) /heated a GR: exha ulsed AIF C: charge : hydroca LPG: lique lockup); N busly vari nission; A xtended V HICLE ENGINE 5.:	trol syst cle weig ZEV: tr ip cataly onia; NF; GPF: I ir-fuel r ust gas croon tra efied pe <i>I</i> : manuable tra ER: all- Varranty MO	tem; CER' ht; ALVW: ansitional yst; NAC: 13OC: am PM filter for atio senso recirculati IFI: seque oler; FFH: ap; BCAN: troleum g ial transm nsmission eelectric ra y: N = no o DELS TRANS TY AMS7	T: certifi adjuste ZEV; TN NOx ad monia o or spark. r; NOXS on; EGI ntial/mu fuel fired bleed c as; E85 ission; S ; AM: at nge; EA credits, `` INFC	cation ad LV WC/C sorpt xidat -ignite S: NC RC: E Iltipor d hea carbon -" 7859 SA: se tarbon d hea carbon - " 7859 SA: se tarbon - " 7859	n; STD: star W; LEV: lov DC: 3-way/o ion catalyst ion catalyst ed engine; H ix sensor; F GR cooler; t fuel injecti ter; F/P/\$: f n canister; p 6" ethanol (emi-automa ated manua equivalent / redits, S = o MATION PORATIVE FAMILY AR0155NAI	ndard; FEL w emission xidizing ca ; SCR-U or ; CTOX/PT HO2S/O2S PMS: PM sr AIR/AIRE: on; DFI/IFI full/partial/p porefix 2: pa "15%"gasc tic transmis AER; PHEV credits for	: family vehicle; talyst; OX: ensor; artial wi rallel; (2 line) fue ssion; C ion; AM /: plug-in