

VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0144

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	IIIP IN	FORM	/ATION						
			- <del></del>		TEST GRO	JOF III	TOK			т				
MOD YEA		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE			
202	0 F/	GAV04.0PAA			PC		I		SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								ORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP		SF	FTP FTP			SFTP			
150000 150000					ULEV125	LEV	3 CO	MPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)			
1	1 2TWC, 2WR-HO2S, 2HO2S, DFI, 2CAC, 2TC							FULL *						
*	* *							ARTIAL	*	(0) (1)	4.0			
*	* *							TIAL WITH FINES	ALL MODELS					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	LVGAR0	L90ECN	I	LEV 3 OPT	ON2 WITH	FEL		P	PC .		*			
					EMISSION C	REDIT	INFC	RMATION						
5.50	REDIT F	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR N ZERO-EVAP		ZEV	NMOG CREDIT FOR DO			OPTIONAL EXH. STD FOR WORK TRUCKS			
	и							N N						
				NMOG	AND FLEE	TAVE	RAGE	INFORMA	TION					
NMOG CH4 RAF NMOG/NMHC RATIO RATIO NMOG+NC									NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)					
*	*	1.10		0.03	C	0.065			0.074		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0144

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



LVGAR0190ECN

TIER3 E10

PREM

VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0144 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

EXHAUST AND EVAPORATIVE EMISSION STANDARDS	AND CERTIFICATION I EVELS
EXTRUST AND EVAPORATIVE ENGISSION STANDARDS	

	EXH	AUS	T AN	D EVA	PORA	TIV	E EMIS	SION	STAN	IDARE	S AND	CERT	IFIC	ATION	LEVE	ELS			
		EXH	AUST	EMISS	ION ST	AND	ARDS A	ND CER	TIFICA	TION L	.EVELS (	FTP, HW	/FET,	, 50°F, 20	)°F)				
	FU	FUEL TYPE		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
						NMOG+NOx (g/mi)			CO (g/mi)			Ox /mi)		HCHO (mg/mi					
				CERT	s	STD		ST	STD (		STD	CERT		STD	CEF	₹T	STD		
FTP@50	ok	K *		*		*	*	*		*	*	*	* *		*		*		
FTP@L		GASOLINE- TIER3 E10 PREM		0.096	8 0.	125	0.72	2.	1	*	*	1.2	2	4	0.00	20	0.01		
50°F @4		SOLIN ER3 E PREM	E10	0.076	2 0.	250	0.31	. 2.	1	*	*	1.4	1	16	6				
	-11-						\			NI	NMOG+NOx (g/mi)			CO (g/mi)					
					FUEI	. 111	<b>'</b> E			CERT STD				CERT		STD			
HWFET @ 50K						*					*	*							
HWFET @ UL				GASOL	INE-TI	ER3	E10 PF	REM		0.0	0.0454 0.125								
20°F	@ 50K			GASOLINE-TIER3 E10 PREM								1.55			10.0				
				SFTP E	XHAUS	TEN	IISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	_S					
			A HE				US06				SC03		Γ		MPOS	SITE			
	FUEL	TYPE		NMOG+NOx (g/mi)		CO (g/mi)			NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)			O (mi)	PM (mg/mi			
@ 4V				CERT		*					* .	*	TRAFFIC TRAFFICA						
@ 4K			STI	D	*	$\dashv$	*	100	U Policio		*	*	1.00						
			CEF	RT	*	$\top$	*		*		*	*	(	0.0668		0.0668		91	*
@ UL	GASOI TIERS	E10	STI	D	*		*		*		* .	*		0.083	4	. 2	*		
			BII	<b>V</b>							0.00			0.110					
		WI	HOLE	VEHICL	E EVA	POR	ATIVE E	MISSIO	N STAI	NDARD	S AND C	ERTIFIC	ATIC	N LEVE	LS				
	ORATI						VHOLE VEHICLE EVAF			ORATIVE TESTING  2DHS (g/test) @ UL				RL (g/mi) @ UL			UL .		
FA	MILY						STD	FEL CE				FEL		CERT			STD		
	01007			LINE-	0.200	+	200	0 500			0.300	1	PEL CEI				0.05		

0.500

0.208

0.300

0.500

0.000

0.05

0.300

0.320



VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0144

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
		FUEL ONLY EVAP & CANISTER BLEED													
EVAPORATIVE FAMILY	ORVR (g/	ORVR (g/gallon) @ UL			ГҮРЕ	3DHS R (g/test	2DHS RIG TEST (g/test) @ UL			BLEED CANISTE TEST (g/test) @					
	FUEL TYPE	CERT	STD			CERT	STD	CER	RT STD		CERT	STD			
LVGAR0190ECN	GASOLINE- TIER3 E10 PREM	0.010	0.20	GASOLINE- TIER3 E10 PREM		*	*	*		*	0.007	0.020			
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)														
EVAPORATIVE FAMILY LEA			K FAMIL	LY CERT			RT		STD						
LVGAR0190ECN LVGAR0190EC			190ECN	-001							0.02	0.007 0.020 ES). STD			

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle, HDV: heavy-duty vehicle, ECS: emission control system, CERT: certification, STD: standard, FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BENTLEY	CONTINENTAL GT	PC	4.0	AMS8	LVGAR0190ECN	1	\$
BENTLEY	CONTINENTAL GT	PC	4.0	AMS8	LVGAR0190ECN	1	\$