

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	DUP IN	FORM	IATION				
MODE		TEST GROUP VEHICLE CLASS				LASS(ES) FUEL CATEGORY				FUEL TYPE		
2020	LV	GAV02.0V3T		PC DEDICATED SINGLE FUE VEHICLE						GASOLINE		
l	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATEG	ORY	INTERIM / IN	TE	RMEDIATE IN-USE STD	
EXH	/ORVR	EVAP			-TP		SF	ГР	FTP		SFTP	
15	0000	15000	D	LEV3	SULEV30	LEV	3 CO	MPOSITE	PM	44 14	PM	
SPE	CIAL FE	ATURES & EX			ON CONTRO	L Maller	-511% -	OBD S	TATUS	ALCOMON AND	ENGINE DISPLACEMENT (L)	
1	1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, TC, CAC, AIR * *							FULL	*		an an an that an te	
*							P	PARTIAL ALL MOD		A STREET	2.0	
*	*					and a forgetter	PARTIAL WITH FINES		*	on had an had had a se		
		E	VAPO	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	N		
EVA	P / ORV	R FAMILY	EV	APORATIVE	STD CATE	GORY			SSION STD E CLASS		SPECIAL FEATURES	
L	VGAR01	10VCA	I	LEV 3 OPTI	EV 3 OPTION2 WITH FEL			PC		*		
				E	EMISSION C	REDIT	INFC	RMATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					EDIT FOR N ZERO-EVAP				MOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS	
		N			N		N			N		
				NMOG	AND FLEE	T AVE	RAGE	INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	нс	CHO/NMHC RATIO	C NMOG+NOX FLEE PC+LDT (0-3750 I (g/mi)			/) LDT	OG+NOX FLEET STE DT (3751 LVW-8500 /WR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		0.03	C	0.065			0.074		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0155 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of October 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division

nam anna a chailtean fha Frainn an Anna

soli (se e e origendar e beneficier e cento dopto El contra e sector de la contra e sector de la contra e si astro-origendar e e origendar e substante de la contra dobte El contra e sector e e origen e origentar a para e trabaccar i dato ante a de canto a forda e ante conferencia e dobte e dato e trabaccar e se



GASOLINE-

TIER3 E10

0.2560

0.300

LVGAR0110VCA

VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0155 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon
monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity
adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss;
ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K:
1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		M mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K	TP@50K GASOLINE- TIER3 E10		*	*	*	*	*	*	0.1	*	*	*		
FTP@UL		OLINE- R3 E10	0.0153	0.030	0.12	1.0	*	*	0.1	4	0.0000	0.003		
50°F @4K		OLINE- R3 E10	0.0207	0.060	0.08	1.0	*	*	0.2	8				
							NN	NMOG+NOx (g/mi)			CO (g/mi)			
			FUEL TYPE					RT	STD	CER	RT	STD		
HWFET @ 50K				*				*		areas and a second		al and a second		
HWFET @ UL		GASOLINE-TIER3 E10					0.0	029	0.030		Constant Sec.	1		
20°F @ 50K			GASOL	INE-TIER	R3 E10					0.2	20	10.0		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06			SC03			COMPOSITE					
	FUEL TYP	'E	NMOG+NOx (g/mi)	CO (g/mi)			OG+NOx (g/mi)	CO (g/mi)		DG+NOx g/mi)	CO (g/mi)	PM (mg/mi)			
@ 4K	*	CERT	* *	*			*	*							
U		STD	*	*			*	*							
	CE		*	*	0	. 0	*	*	0.0145		0.14	*			
@ UL		1 810	*	*		5	*	*	0.083		4.2	*			
		BIN						and the second s				a de la com			
	N	WHOLE V	EHICLE EVAP	ORATIVE E	MISSION	STANDAR	RDS AND C	ERTIFIC	ATIO	N LEVELS					
				WHOLE \	/EHICLE	EVAPORA	TIVE TEST	ING							
	UL GASOLINE- TIER3 E10 W			YPE 3DH	E 3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL		
			CERT	STD	FEL	CERT	STD	FE	L	CERT		STD			

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

0.2194

0.300

0.300

0.001

0.05

0.300

	EVAPORATIVE FAMILY				FUEL ONLY EVAP & CANISTER BLEED								
		ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
		FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
	LVGAR0110VCA	GASOLINE- TIER3 E10	0.027	0.20	GASOLINE- TIER3 E10	*	*	*	*	0.003	0.020		

CALIFORNIA AIR RESOURCES BOARD EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)

EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
LVGAR0110VCA	LVGAR0110VCA-001		0.02

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2	020 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		a se a
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
VOLKSWAGEN	GTI	PC	2.0	AMS7	LVGAR0110VCA	1	P
VOLKSWAGEN	GTI	PC	2.0	M6	LVGAR0110VCA	1	P
VOLKSWAGEN	JETTA GLI	PC	2.0	AMS7	LVGAR0110VCA	1	P
VOLKSWAGEN	JETTA GLI	PC	2.0	M6	LVGAR0110VCA	1	P