

# VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0166

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

11036 10	JI WITICIT	Certification	o gi u	intou.									
TEST GROUP INFORMATION													
MODE	TEST GROUP   VEHICLE CLASSIES)						FUEL CATEGORY				FUEL TYPE		
2020	LVG	AV03.0N7N			PC		HYBRID ELECTRIC VEHICLE				GASOLINE		
	JSEFUL	VEH	ICLE EMISSION CATEGORY			ORY	INTERIM / IN	TE	RMEDIATE IN-USE STD				
EXH/ORVR EVAP				F	FTP			ГР	FTP		SFTP		
150000 150000				LEV3	ULEV70	LEV70 LEV 3 CO		MPOSITE	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	GUSSER TRAIN	ENGINE DISPLACEMENT (L)		
1	WU-TWC	, TWC, WR-I	102S,	HO2S, DE	FI, TC, CA	C	77	FULL	*				
*			*				PARTIAL		*		3.0		
*	* *							TIAL WITH	ALL MODELS		1100		
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	/ INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	′	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
LVGAR0150NCS LEV					TION2 WITH FEL			PC			*		
				E	MISSION C	REDI	TINFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR ZERO-EV.							I-PZEV NMOG CREDIT FOR DO			R	OPTIONAL EXH. STD FOR WORK TRUCKS		
и							n n						
				NMOG	AND FLEE	TAVE	RAGI	INFORMA	TION				
NMOG RAF	NMOG/NMHC			HO/NMHC RATIO	NMOG+NOX FLEE PC+LDT (0-3750   (g/mi)						NMOG+NOX FLEET STE MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.03	. (	0.065 0.074					*		
										-	Cantral Customa Phoso		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0166

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of November 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



TIER3 E10

TIER3 E10

**VOLKSWAGEN GROUP** OF AMERICA, INC.

Executive Order: A-413-0166 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

### **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

										EVELS (	FTP. HWI				LO		
	FUEL		CH4: mono: adjust	methane xide; NC tment fa R [a HC/	e; NMO 0x: oxide ctor; 2D	G: non-Ces of nitr HS/3DH	CH4 orga ogen; H0 S [g HC/ d]: on-bo	nic gas CHO: fo test]: 2 ard ref	s; HC: ormald 2/3 day	hydrocarb ehyde; Pl s diurnal+ vapor rec st procedu	on; NMH I: particul hot-soak; overy; g:	C: no late m RL [g	n-CH4 h natter; R g HC/mi mg: mil	HC; CO AF: rea ]: runni lligram;	activ ng Id	ity oss;	
				NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCH (mg/r				PM (g/mi)		
		(9)	CEF	RT S	STD	CERT	STD	) (	CERT	STD	CERT	Г	STD	CERT		STD	
FTP@5	ok ,	r	*		*	*	*		*	*	*		*			*	
FTP@L	L GASOI		0.05	503 0	.070	0.39	1.7		*	*	*	* 4		0.0010 0		0.003	
50°F @4	IK I	LINE- B E10	0.12	211 0	.140	0.96	1.7		*	*	2.9	16		(5) 200M	KAME OF STREET		
			FUEL TYPE						NMOG+NOx (g/mi)			CO (g		ر/mi)			
								CE	ERT STD		CERT		T STD		STD		
HWFE	@ 50K		*							* *							
HWFE	T@UL		GASOLINE-TIER3 E10						0.0	0.0210 0.070							
20°F	@ 50K		GASOLINE-TIER3 E10										0.69 10.0				
			SFTP	EXHAL	JST EM	ISSION	STANDA	RDS	AND C	ERTIFIC	ATION LE	VEL	S				
			US06						SC03				COMPOSITE				
	FUEL TY	PE NI		NMOG+NOx (g/mi)		CO PM (g/mi) (mg/m			NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NO (g/mi)		x C (g/		PM (mg/mi)	
@ 4K	*	* CERT		*		*				*	*						
)		STI	)	*		*				*	*						
	CE		T	*		*	3.	0		*	*	0	.0338	0.	81	*	
@ UL	GASOLIN TIER3 E	1 5 11	0	*		*	6	i		*	*	0	.083	4	. 2	*	
		BIN	1									0	.090				
		WHOLE	VEHI	CLE EV	APORA	TIVE E	MISSION	STAN	IDARE	S AND C	ERTIFICA	ATIO	N LEVE	LS			
					WI	HOLE V	EHICLE	EVAP	ORAT	IVE TEST	ING		_				
	ORATIVE MILY	FUEL TYPE		FUEL TYPE 3DHS (g/		/test) @ UL			2DHS (g/test)		@ UL		RL (g/mi) @		1) @	g UL	
				CEF	ERT STD		FEL	CEF	₹T	STD	FEL	FEL C		ERT		STD	
LVGAR0150NCS		ı	OLINE- 3 E10 0.209 0		09 0	. 300	0.300 0.1		55	0.300	.300 0.300		0.000		0 0.05		
(	ORVR / FU	EL ONLY	// CAI	NISTER	BLEED	EVAP	DRATIVE	EMIS	SION	STANDA	RDS AND	CEF	RTIFICA	TION L	ΕVI	ELS	
	ORATIVE			RVR (g/gallon) @ UL		30			UEL ONLY EVAP		2DHS RIG T (g/test) @		TEST BLEED CA				
17	MILY	FUEL T	YPF	YPE CERT STD		FUEL TYPE			(g/test) @ UL ERT STD		CERT		STD			STD	
LVCA	R0150NCS	GASOLI	NE-	0.039	0.20		LINE-	<del> </del>	*	*	*	1	*	0.01		0.020	



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0166

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LVGAR0150NCS	LVGAR0150NCS-001	*	0.02						

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD		
AUDI	A6 ALLROAD	PC	3.0	AMS7	LVGAR0150NCS	1	\$		
AUDI	A6 QUATTRO	PC	3.0	AMS7	LVGAR0150NCS	1	\$		
AUDI	A7 QUATTRO	PC	3.0	AMS7	LVGAR0150NCS	1	\$		