

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	NATION					
MOD YEA		EST GROUP		VEHICI	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
202	0 LV	GAV02.5NAG			PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEHICLE EMISSION CATEG				GORY INTERIM / INT			ERMEDIATE IN-USE STD		
EX	H/ORVR	EVAP	FTP			SF	TP	FTP		SFTP			
1	50000	150000		LEV3	ULEV125 LEV 3 C			COMPOSITE *		ас. -	PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S) STATUS		ENGINE DISPLACEMENT (L)		
1 TWC, 2TWC, WR-HO2S, HO2S, DFI+SFI, TC, CAC								FULL	*	18. A.			
*						P	ARTIAL	*		2.5			
* * PARTIAL WITH ALL MODELS													
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							, EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	LVGAR01	10NBA		L	LEV 2			PC			*		
				E	EMISSION C	REDIT	r info	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG C	REDIT FOR DO	R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEE	Γ AVE	RAG	E INFORMA	TION				
NMOG CH4 FTP RAF RAF NMOG/NMHC RATIO				a a contrato respective in the li	NMOG+NOX FLEET S PC+LDT (0-3750 LVV (g/mi)					0	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.03 0.065				0.074			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this $3\ell^{st}$ day of December 2019.

Kim Ryor

Por Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0167 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					G+NOx g/mi)		CO (g/mi)			IOx /mi)		HCH mg/n	-		PN (g/n	
				CERT	ST	CER	T ST	D	CERT	STD	CER	T	STD	CER	T	STD
FTP@50	ж	*		*	*	*	*		*	*	*		*	*		*
FTP@U	GASOLINI FTP@UL TIER3 E: PREM			0.0568	0.12	25 1.72	2 2.	1	*	*	*		4		00	0.003
50°F @4K TIEF		OLIN R3 E PREM		0.0454	0.25	50 0.5	2.	1	*	*	0.8		16			
									N	MOG+NO	x (g/mi)			CO (g	/mi)	
				FUEL TYPE					CERT STD			CERT		STD		
HWFET @ 50K					*				*		*	*				
HWFE	T @ UL			GASOLINE-TIER3 E10 PREM					0.0236 0.12		,			1.55	$\left\ \frac{\partial f}{\partial g} \right\ _{t=0}^{\infty} \left\ f - f \right\ _{t=0}^{\infty} \left\ \frac{\partial f}{\partial g} \right\ _{t=0}^{\infty} \left\ f - f \right\ _{t=0}^{\infty} \left\ \frac{\partial f}{\partial g} \right\ _{t=0}^{\infty} \left\ \frac{\partial f}{\partial $	
20°F @ 50K			GASOLINE-TIER3 E10 PREM								2.68		10.0			
	0			ETP E	TAUST	EMISSION				ERTIFICA		EVEL	S			
			100			US06				SC03				MPOS	SITE	
	FUEL T	EL TYPE			NMOG+NOx (g/mi)		CO PN (g/mi) (mg/i		NMOG+NOx (g/mi)		CO NI (g/mi)		IMOG+NOx (g/mi)		:0 /mi)	PM (mg/mi)
@ 4K	*		CERT		* *					*	*	n an shering an the second			2 (1) (2)	
e				-	*	*		1.419.4		*	*					
			CERT	Г	*	*	1	.0	* * 0		0.0458 1.7		.70	*		
@ UL	GASOLI TIER3 PRE	E10	STD		*		* 6			*	*		0.083		. 2	*
		BIN		$d_{\rm ext} = \frac{1}{2} \sqrt{2} d_{\rm ext}$	a Angelan di setta setta Angelan setta s	a lagarage			n 19 an stranger and a state		ale a state		0.110		in de la composition de la composition Composition de la composition de la comp	
		WH	OLE V	EHICL	EEVAP	DRATIVE E	MISSION	N STA	NDAR	DS AND C	ERTIFIC	ATIO	N LEVEL	S		
		1								IVE TEST						
EVAPORATIVE FAMILY		FUEL TYPE		YPE	3DHS (g/test) @ UL			2DHS (g/test		:) @ UL		RL (g/mi) (ni) @	UL	
				CER		STD	FEL	CE	RT	STD	FEL		CERT			STD
LVGAR0110NBA			ASOL IER3 PRE	E10	0.340	0.50	*	0.3	355	0.65	*		0.00		.001 0.05	

A	CALIF	ORN IRCES B	NA OARD	VOLKSWAGEN GROUP OF AMERICA, INC.			P N	Executive Order: A-413-0167 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4					
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
						FUEL C	NLY EVA	ILY EVAP & CANISTER BLEED					
EVAPORATIVE FAMILY	ORVR (g	ORVR (g/gallon) @ UL		FUEL TYPE			IG TEST) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	E CERT	STD			CERT	STD	CER	T STD	CERT	STD		
LVGAR0110NBA	GASOLINE- TIER3 E10 PREM		0.20	*		*	*	*	*	*	*		
	EFFECTIVE	LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION L	EVEL (INCH	IES)			
									STD				
*		*			•				*				
*: not applicable; # LDT<6000#GVWF	3751-5750#	LVW: LD	T3: LDT	6001-850	0#GVW	JR,3751-57	50#ALVW;	LDT4:	LDT 6001-850	0#GVWR,5	751-		

8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85% ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
AUDI	RS3	PC	2.5	AMS7	LVGAR0110NBA	1	\$
AUDI	TT RS	PC	2.5	AMS7	LVGAR0110NBA	1	\$