

### VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0174

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODI		EST GROUP		VEHIC	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
202	0 LV	GAV01.4V3P			PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY				INTERIM / IN	EDIATE IN-USE STD			
EX	H/ORVR	EVAP	FTP SFTP			TP	FTP		SFTP				
150000 150000				LEV3	SULEV30	30 LEV 3 COMPOSI			PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	ATUS		NGINE DISPLACEMENT (L)		
1	WU-TWC	C, TWC, WR-H	HO2S, DF	I, AIR, T	c,		FULL	*					
*			*				Р	ARTIAL	*		1.4		
*							RTIAL WITH ALL MODELS		1				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	LVGAR01	.10VBE	L	LEV 2			PC			*			
				E	EMISSION C	REDI	TINFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR ZERO-EVA							ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
	и и							N N					
NMOG AND FLEET AVERAGE INFORMATION													
NMO0 RAF	NIMO(2/NIMIH)				NMOG+NOX FLEET S PC+LDT (0-3750 LV (g/mi)			V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m	)			
*	*	1.10		0.03	С	0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0174

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of January 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 



**VOLKSWAGEN GROUP** OF AMERICA, INC.

Executive Order: A-413-0174 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

	EXH				and the state of t										LEVEL	S		
	FU	EXI		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP														
						N	MOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HCH <sup>(</sup> (mg/n				PM /mi)
				CE	RT	STD	CER	T ST	D	CERT	STD	CERT	Г	STD	CERT	STD		
FTP@50	ok	*		,	ł .	*	*	*		*	*	*		*	*	*		
FTP@U	11 1	GASOLINE- TIER3 E10		0.0	215	0.030	0.10	1.	0	*	*	0.2		4	0.0000	0.003		
50°F @4	F@4K GASOLINE- TIER3 E10			0.0	167	0.060	0.13	1.	0	*	*	0.2		8				
										N	MOG+NO	ox (g/mi)	十		CO (g/m	i)		
					FU	JEL TY	PE	E		CI	ERT	STD		CER	T	STD		
HWFE1	T @ 50K			*							*	*	*					
HWFET @ UL			GASOLINE-TIER3 E10						0.	0.030		Shearing						
20°F @ 50K COLD C			CO E1	CO E10 REGULAR GASOLINE (TIER3)									0.49		10.0			
				SFTF	EXHA	UST E	MISSION	STAND	ARDS	AND C	ERTIFIC	ATION LE	VEL	S				
					US06					SC03				CC	=			
	FUEL TY		YPE		NMOG+NOx (g/mi)		CO (g/mi)					CO (g/mi)		OG+NO: g/mi)	x CO (g/mi	PM (mg/mi)		
@ 4K	*		CE	RT *		*	*			*	*							
0				.D *		*	*		*		*							
		GASOLINE- FIER3 E10 BI		RT 0		*	* 2.0		*		*	0.0272		1.30	*			
@ UL				1 810 1		*		*			*	*		.083	4.2	*		
				N								C	0.040					
		W	HOLE	VEHI	CLE E							ERTIFICA	ATIO	N LEVE	LS			
<b>-</b> 1/4-	OD 4 T"	_					VHOLE \	/EHICLE	EVAI	PORAT	IVE TEST	ING		_	)  <i>                                     </i>	a. I II		
	ORATIV MILY					TYPE 3DHS (g/test) @ UL					2DHS (g/test) @ UL		@ UL			RL (g/mi) @ UL		
						RT STD		FEL	CE	RT STD		FEL	FEL CE		RT	STD		
LVGAR0110VBE		BE		LINE- 3 E10	ח ופכיכי חו		0.50	* 0.2		263	0.65	*		0.000		0.05		
C	ORVR /	FUEL	ONL	Y / CA	NISTE	RBLE	D EVAP	ORATIV							TION LE	/ELS		
EVAPORATIVE FAMILY		/E	ORV	/R (g/g	R (g/gallon) @ UL			31			UEL ONLY EVAR DHS RIG TEST		2DHS RIG T		TEST   BLEED CAN			
		-	ner :	TVDE	CERT	CTT		L TYPE		(g/test) @ UL		(g/tes	1			test) @ 4K		
LVGAF	LVGAR0110VBE		ASOL	INE-				*		ERT *	STD *	CERT *	+	STD *	CERT *	STD *		
		ľ	IER3	E10														



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0174

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
*	*	*	*							

f: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ŽEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-Ū or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas: E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER: PHEV: plug-in hybrid electric vehicle: NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L) TRANS TYPE		EVAPORATIVE FAMILY	EXH ECS	OBD
VOLKSWAGEN	GOLF	PC	1.4	SA8	LVGAR0110VBE	1	\$
VOLKSWAGEN	GOLF	PC	1.4	М6	LVGAR0110VBE	1	\$
VOLKSWAGEN	JETTA	PC	1.4	м6	LVGAR0110VBE	1	\$