

VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0175

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	NFOR	MATION						
MOD YEA		EST GROUP		VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE			
202	0 L	VGAV01.4V7P			PC	PC DEDICAT			SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD			
EX	H/ORVR	EVAP	FTP SF				TP	FTP		SFTP				
1	50000	150000	LEV3	3 ULEV70 LEV 3 COMPO			OMPOSITE	*	_	PM				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			GINE DISPLACEMENT (L)			
1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, AIR, TC, CAC								FULL	L *					
*			*				P	PARTIAL *		1.4				
*			*				and the second	TIAL WITH	ALL MODELS	MODELS				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS	SPECIAL FEATURES				
	LVGAR0110VBE LEV 2							I	PC	*				
					EMISSION C	REDI	ΓINFO	ORMATION						
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP							ZEV	NMOG C	REDIT FOR DOI	ס ו כ	OPTIONAL EXH. STD FOR WORK TRUCKS			
и									И		N			
				NMOG	AND FLEE	ΓAVE	RAG	E INFORMA	TION					
NMO(I NIMOGINIMHC I DCTIDI							V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m					
. *	*	1.10		0.03 0.065 0.074 *						*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0175 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of January 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-TIER3 E10

0.015

0.20

LVGAR0110VBE

VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0175 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICAT	TION LEV	ELS!
---	----------	------

	EXH	AUS	ST A	ND E	VAF	POR	ATIVE	EMIS	SION S	ATA	IDAR	DS AN	O CEF	TIFI	CATIO	NL	EVELS			
		EX	HAU									LEVELS								
	FUEL TYPE		mo adj OR 100	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP								rity oss;								
				N		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)			HCH((mg/m				VI ni)			
				С	ERT	T :	STD	CERT	STE	5	CERT	STD	С	ERT	STD		CERT	STD		
FTP@5	0K	*		*			*	*	*		*	* *		*			*	*		
FTP@L	GASOLINE- TIER3 E10		1 ()	0527	0	.070	0.27	1.7	7	*	*	0.6		4	C	0.0000 0.00				
50°F @	1 1 1	SOL:		1 (1)	0.0311 0.1		.140	0.12	1.7	7	* *		C	0.4		V.	e suest			
						FUE	L TYPE	of			NMOG+NOx (g		Ox (g/n	(g/mi)		СО		O (g/mi)		
										С	CERT STD		D	CE	CERT		STD			
HWFE	Γ @ 50I	<					*					*	,	, 						
HWFET @ UL GASOLIN					OLINE-TIER3 E10			0.	0.0282 0.070		70									
20°F	@ 50K		COLD	CO :	E10 F	REGU:	LAR GA	SOLINE	(TIER	.3)				ili sisela Vi	0	. 48		10.0		
			200	SF'	TP EX	HAU			STANDA	ARDS	AND (SC03		LEV		201/	POSITE			
	FUEL	UEL TYPE		NMO			US06 MOG+NOx CO PM				NMOG+NOx C			NMOG+NO						
	. 022					1		(g/mi) (mg/m					(g/mi)				(g/mi)	(mg/mi)		
@ 4K	,	* CE		ERT	RT *			*				*	*							
			S	STD		*		*		存款	12 23 23 4	*	*	3-11 12-11 1-11						
		ENSOT THE		ASOLINE- STO		CERT		*		* 0.0		0	* .		*	* 0		0.0466		*
@ UL						STD		*		*	6	5		*	*		0.083		4.2	*
				BIN											0.090					
		V	/HOL	E VE	HICLE	EV						OS AND		ICAT	ION LE	/ELS	l			
E)/A D	00 A TIV	,_			-		WH	IOLE V	EHICLE	EVAF	PORAT	IVE TES	TING		_	DI	(almi) @	.111		
	ORATI\ \MILY			FUEL TYPE		3DHS (g/		test) @ UL			2DHS (g/te					RL (g/mi				
						CERT S		TD FEL		CE	RT	RT STD		EL	. CEI			STD		
LVGAF	R0110V	BE	E GASOLINE- TIER3 E10			0.228 0		.50 *		0.2	263 0.65			*	0	0.000		0.05		
C	ORVR /	FUE	ON	LY/C	ANIS	TER	BLEED	EVAPO	DRATIVE	EMI	SSION	STANDA	ARDS A	ND C	ERTIFIC	ATI	ON LEVI	ELS		
												NLY EVA								
	ORATI\ \MILY	/E	OF	RVR (g	/gallon) @ UL			FUEL			G TEST @ UL		2DHS RIG 7 (g/test) @							
			FUEL	. TYPI	E CE	RT	STD			CE	ERT	STD	CE	RT	STD	(CERT	STD		



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0175

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
*	*	*	*							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

_								
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD	
					T. T. C. A. D. O. 1 A. T. D. F.	1	\$	
MOLKSWAGEN	JETTA	PC	1.4	sa8	LVGAR0110VBE		Ψ	