

#### GENERAL MOTORS LLC.

Executive Order: A-006-2270

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODI YEA		EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
202	L MG	MGMXT03.0351 LDT4					DEDICATED VEH				DIESEL		
	USEFUI	_ LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY				INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP SF			TP	P FTP		SFTP			
1	150000 *			LEV3	ULEV125 LEV 3 COMPO			OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
OC+DPF-SCRC, SCRC+NH3OC, DFI, CAC, TC, HP-EGR, LP-EGR, EGRC, NOXS(3), PMS, RDQS								FULL	*				
*			*				F	PARTIAL	*		3.0		
*	*							ARTIAL WITH FINES					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	RY EVAP EMISSION STE VEHICLE CLASS			SPECIAL FEATURES			
	*		*			*			*				
EMISSION CREDIT INFORMATION													
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					NMOG CREDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N					N				N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF					0-375		V) LDT	NOX FLEET STD (3751 LVW-8500 R) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	* * * 0.058						0.065 *			*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



#### GENERAL MOTORS LLC.

Executive Order: A-006-2270

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

# BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have five (5) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred twenty five dollars (\$125) per vehicle for the third through fifth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

Allen Lyons, Chief

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this //th day of August 2020.

Emissions Certification and Compliance Division



GENERAL MOTORS LLC.

Executive Order: A-006-2270 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

	EVIIA	LICT	AND			) A TIV				NDADI	20. A N	D 055	TIFIC	NATION		/F1.6			
	EXHA						VE EMIS									/ELS			
FUEL TYPE				CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
				NMHC+NOx (g/mi)			(	CO (g/mi)			NOx (g/mi)		HCH (mg/r			PM (g/mi)			
						STD	CERT	S	STD	CERT	STD	CE	RT	STD	STD CE		STD		
FTP@5	P@50K *		*			*	*		*	*			*	*	*		*		
FTP@L		ESEL-EPA		0.094		0.125	0.3	2	2.1	*	*	*		4	0.	000	0.003		
50°F @	0°F @4K *			*		*	*		*		* * *			*					
					FU	EL TY	PE				NMHC+NOx (g/mi)			CO (g/mi		(g/mi)			
										+	CERT		D	CERT			STD		
HWFE	Г@ 50К				*						*	*				_			
HWFET @ UL				DIESEL-EPA						0.	027	0.1	25						
20°F @ 50K *													*		*				
			S	FTP E	XHAU	UST E	MISSION	STAN	IDARD	S AND C	ERTIFIC	CATION	LEVE	LS					
				<u> </u>			US06				SC03				COMPOSITE				
	FUEL T	ГҮРЕ		NMHC+NOx (g/mi)		CO (g/mi)	(n	PM (mg/mi)		C+NOx mi)	CO NI (g/mi)				CO g/mi)	PM (mg/mi)			
@ 4K	*	STD			*		*				*	*							
					*		*				*	*							
		CER IESEL-EPA STI		1	*		*		0.3		* *			0.130		0.1	*		
@ UL	DIESEL-				*		*	$\perp$	6		*		0.077		4.2		*		
			BIN											0.180					
		WH	OLE V	EHICL	E EV		RATIVE E						CATIO	JN LEVE	LS				
	ORATIVE	I FIRE		YPE	3	3DHS (g/test) @ l			EEVA			TESTING /test) @ UL		RL (g/		mi) @ UL			
	VI¥II I⊏ Ï					RT	STD	FEL	С	ERT	RT STD		EL			Τ	STD		
	*	*			*	_	*		+	*	*	+ -	*		*		*		
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																			
										FUEL ON	ILY EVA								
EVAPORATI FAMILY		VE ORVR		R (g/gallon) @ UL		@ UL	FUE	_ TYPI		DHS RIG (g/test)		2DHS RIG (g/test)					ANISTER est) @ 4K		
		FUEL T		PE CERT STD				C	ERT	STD	CER	Т	STD C		RT	STD			
	*	*			*	*		*		*	*			*	*		*		
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)																			
EVAF	PORATIV	E FAI	FAMILY LEAK FAI			VILY			CER	CERT			STD						
	J.								4					4					



GENERAL MOTORS

Executive Order: A-006-2270

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

': not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	SILVERADO 4WD	LDT4	3.0	A10	*	1	\$
GMC	SIERRA 4WD	LDT4	3.0	A10	*	1	\$
GMC	SIERRA 4WD AT4	LDT4	3.0	A10	*	1	\$