

Executive Order: A-008-0515

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD YEA		EST GROUP	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
202	1 MB	MXJ03.0B5X		LDT2, PC DED					SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								TEGORY INTERIM / INTERMEDIATE IN-USE S					
EX	H/ORVR	EVAP		FTP SF			TP	FTP		SFTP			
1	50000	15000	LEV3	ULEV70	V70 LEV 3 COMPOS			*		РМ			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	T	WC, WR-HO2S	2S, DFI,	TC, CAC			FULL	*					
*			*				Р	ARTIAL	SOME MODELS		3.0		
*			r			10 00000000	TIAL WITH FINES	SOME MODELS					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								VAP EMISSION STD VEHICLE CLASS SPECIAL FEAT				
MBMXR0150G30 LEV 3 OPTION2 WITH						FEL		PC			*		
				E	EMISSION C	REDIT	INFO	RMATION					
2525	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-I ZERO-EVAP							NMOG C	NMOG CREDIT FOR DOR OPTIONAL EXH. FOR WORK TRU				
		N		N			N N						
	NMOG AND FLEET AVERAGE INFORMATION												
NMO(CH4 RAF	FTP NMOG/NMHO RATIO	CHO/NMHC RATIO	NMOG+NO PC+LDT (V) LDT	+NOX FLEET S (3751 LVW-850 R) + MDPV (g/m	0	MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10	1.10 * 0.058						0.065 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-008-0515

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed Toyota Supra vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1614 day of March 2020.

Allen Lyóns, Chief

Emissions Certification and Compliance Division



Executive Order: A-008-0515

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

0.004

0.020

ATTACHMENT

								A	ITAC	HIVII									
	EX	HAU	IST	AND) EV	APOR	ATIVE	EMIS	SSION S	ATA	IDAR	DS AND	CERT	FIC	NOITA	LEVEL	.S		
		E	XHA	UST	EMIS	SION S	TANDA	RDS A	ND CERT	IFIC/	ATION I	LEVELS	(FTP, HW	FET,	50°F, 20)°F)			
		FUFI	TVE	r a (nono: adjust DRVF	xide; N0 tment fa R [g HC/	0x: oxide ctor; 2D gallon d	es of nit HS/3DI ispense	CH4 orga trogen; H0 HS [g HC/ ed]: on-bo enheit; FT	CHO: 'test]: ard re	formalo 2/3 day fueling	lehyde; P 's diurnal- vapor red	M: particu +hot-soak covery; g:	llate n ; RL [gram	natter; R g HC/mi] ; mg: mil	AF: reac]: running lligram; n	tivity		
		FUEL TYPE			N	MOG+N (g/mi)	IOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCH(P M g/mi)		
					CEF	₹T	STD	CER	T STE)	CERT	STD	CER	Т	STD	CERT	STD		
FTP@5	0K	1	k		*		*	*	*		*	*	*		*	*	*		
FTP@L	II I	GASOLINE- TIER3 E10		-	0.0	40 0	.070	0.3	1.7		*	*	*		4	0.000	0.003		
50°F @4	0°F @4K GASOLINE- TIER3 E10			0.0	33 0	.140	0.3	1.7	'	*	*	*		16	i garan di Karang di	A 18 34 - 1			
76175						FUI	FI TYP	F				MOG+NO				CO (g/mi)			
					FUEL TYPE					CI	ERT	STD		CER	T	STD			
HWFE	HWFET @ 50K *											*	*						
HWFE	HWFET @ UL GASOLINE-TIER3 E10										0.	017	0.070		n er g				
20°F	@ 50	K	СО	LD C) E1	0 REGU	LAR GA	SOLIN	E (TIER	3)				1.0 10.0			10.0		
				5	FTP	EXHAL	JST EM	ISSION	STANDA	RDS	AND C	ERTIFIC	ATION LI	EVEL	S				
					US06 NMOG+NOx CO PM						SC03			COMPOSITE					
	FUE	FUEL TYPE					/IOG+NOx (g/mi)		Pi (mg/		NMOG+NOx (g/mi)		2202 20020 10000		OG+NO) g/mi)	CO (g/m			
@ 4K		*	* CE		CERT *		*				*	*				275 kg			
		S ⁻		STD	*		*				*	*							
		ASOLINE- IER3 E10 ST		CA COT TATE		CERT		* *		* 1				*	*	0.039		0.4	*
@ UL						STD		* .		*	6	5		*	*		0.077	4.2	2 *
				BIN										C	0.070				
			WH	OLE \	/EHI	CLE EV			MISSION					ATIO	N LEVE	LS			
							Wł	HOLE \	/EHICLE	EVAF	PORAT	IVE TEST	ING		_	I (/!\	.		
	EVAPORATIVE FAMILY		FUEL TY		TYPE 3DHS (g/		/test) @ UL		2DHS (g/test)				RL (g/mi) @ l						
						CERT STD		D FEL		RT STD		FEL		CERT		STD			
	MBMXR0150G30 GASOLI TIER3			E10	0.1		0.300 0.300 0.226 0.300 0.300 0.01						0.05						
(ORVE	R / FUI	EL C	DNLY	CAI	NISTER	BLEED	EVAP	ORATIVE								VELS		
_,	. -			00.45	lat-	2 ۲ مالم	e 111						P & CAN				CANISTED		
EVAP FA	ORA MIL		VE ORVR (g/ga			(g/gallon) @ UL			FUEL TYPE		DHS RIG TEST (g/test) @ UL			2DHS RIG 1 (g/test) @		BLEED CANIS			
	.,		FU	EL TY	PE.	CERT	STD				RT	STD	CERT		STD	CERT	STD		

GASOLINE-

TIER3 E10

GASOLINE-

TIER3 E10

0.04

0.20

MBMXR0150G30



Executive Order: A-008-0515

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MBMXR0150G30	MBMXR0150G30-001	0.00	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV: ZEV: zero-emission vehicle: TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor: NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	X3 M40I	LDT2	3.0	SA8	MBMXR0150G30	1	P
BMW	X4 M40I	LDT2	3.0	SA8	MBMXR0150G30	1	P
BMW	Z4 M40I	PC	3.0	SA8	MBMXR0150G30	1	P
TOYOTA	SUPRA 3.0	PC	3.0	SA8	MBMXR0150G30	1	\$