

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP I	NFOR	MATION					
MODE YEA		TEST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	FUEL CATEGORY FUEL T				
202:	LM	GMXV01.3545			PC	PC DEDICATED SING VEHICLE					GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							CATE	GORY INTERIM / INTERMEDIATE IN-USE STD					
EXI	I/ORVR	R EVA		FTP		SF	тр	FTP		SFTP			
1!	50000	15000	0	LEV3	SULEV30	LEV	' 3 C	OMPOSITE	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	1	DFI, WR-HO2S	, но2	S, TC, C	AC, TWC			FULL	ALL MODELS				
*	* *							PARTIAL	*		1.2, 1.3		
*			*				PAF	RTIAL WITH *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS SPECIAL FEA				
1	MGMXR0	1023BB	L	EV 3 OPTI	ION2 WITH	FEL		I	2C	НСТ			
				I	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N N				
				NMOG	AND FLEET		RAG	E INFORMA	TION				
NMOG RAF						0-375		V) LDT					
*	*	1.10		*	0	.058	8		0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-006-2241 dated January 30, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>/8th</u> day of November 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	_											
				NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HO /mi)		PM g/mi)
			CERT	STD	CERT STD C		CERT	STD	CERT	STD	CERT	STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.030	0.030	0.3	1.0	*	*	*	4	0.000	0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
							NN	NMOG+NOx (g/mi) CO (g/mi)				
FUEL TYPE					CE	RT	STD	CER	т	STD		
HWFET @ 50K				*			*	* *				
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.016 0.030					
20°F @ 50K		COLD (CO E10 RE	EGULAR GA	ASOLINE	(TIER3)				0.6	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	ΓΡΕ	XHAL	JST EN	IISSION	I STAND	ARDS	AND	CERTIFIC	ATION LE	VELS			
							US06				SC03		С	OMPOSI	E	
	FUEL TY	TYPE		NMOG+NOx		Ox	СО	P	М	NMOG+NOx		CO	NMOG+NC	Ox CO	PM	
					(g/mi)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/m	i) (mg/mi)	
@4K *			CERT		*		*			*		*				
			STD	*			*				*	*				
			CERT	*			*		L	*		*	0.020	1.0) *	
@ UL	GASOLIN TIER3 E	I SID		*			* (5	*		*	0.077	4.2	*	
			BIN										0.050			
		WHO	OLE VEI	HICL	E EV/	APOR/	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	ELS		
						WHOLE VEHICLE EVAPORATIVE TESTING										
	ORATIVE			FUEL TYPE				g/test) @ UL STD FEL		2Dł	HS (g/test) @ UL			RL (g/mi)	@ UL	
										RT STD		FEL	CE	RT	STD	
MGMXR01023BB			ASOLINI IER3 E:	_	0.15	53 0	.300	0.300	0.1	58	0.300	0.30	0.	.00 0.05		
(ORVR / FUI	EL O	NLY/C	ANI	STER	BLEEI) EVAP	ORATIVE	EEMIS	SION	I STANDA	RDS AND	CERTIFIC/	ATION LE	VELS	
									FU	JEL C	ONLY EVA	P & CANIS	STER BLEE	D		
	ORATIVE AMILY	ORVR (g/ga		/gallon) @ UL			FUE	FUEL TYPE		3DHS RIG TEST (g/test) @ UL			RIG TEST t) @ UL		ED CANISTER T (g/test) @ 4K	
		FUE	EL TYPE	C	ERT	STD			CE	RT	STD	CERT	STD	CERT	STD	
MGMXI	R01023BB		SOLINE- ER3 E1(0	.08	0.20		OLINE- R3 E10	*	•	*	*	*	0.010	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MGMXR01023BB	MGMXR01023BB-LK1	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BUICK	ENCORE GX AWD	PC	1.3	A9	MGMXR01023BB	1	F
BUICK	ENCORE GX FWD	PC	1.3	cv	MGMXR01023BB	1	F
BUICK	ENCORE GX FWD	PC	1.2	CV	MGMXR01023BB	1	F
CHEVROLET	TRAILBLAZER AWD	PC	1.3	A9	MGMXR01023BB	1	F
CHEVROLET	TRAILBLAZER FWD	PC	1.2	CV	MGMXR01023BB	1	F
CHEVROLET	TRAILBLAZER FWD	PC	1.3	cv	MGMXR01023BB	1	F