

Executive Order: A-006-2250

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FORM	MATION	(i) (i) (ii)				
MODE		ST GROUP		VEHIC	LE CLASS(I	ES)		FUEL C	ATEGORY		FUEL TYPE		
2021	MG	MXV02.0031			PC		I		SINGLE FUEL HICLE		GASOLINE		
1	JSEFUL	LIFE (miles)		VEH	ICLE EMIS	SION C	ATEG	ORY	INTERIM / INT	ΓER	MEDIATE IN-USE STD		
EXH	/ORVR	EVAF)		FTP		SF	ГР	FTP		SFTP		
15	0000	15000	0	LEV3	ULEV70	LEV	3 CO	MPOSITE	*		PM		
SPE	CIAL FE	ATURES & E	XHAI		ON CONTRO	DL		OBD S	TATUS	E	NGINE DISPLACEMENT (L)		
1	D	FI, CAC, TO	c, w	R-HO2S, TW	C/HO2S		1. 1.	FULL	ALL MODELS	(3)4-1-12			
*				*			P	ARTIAL	*	2.0			
*		***************************************		*			15.35	TIAL WITH	*				
		E	VAP	ORATIVE &	REFUELING	G (EVA	P/OR	VR) FAMILY	INFORMATION	ĺ			
EVA	P / ORV	R FAMILY	E۱	/APORATIVE	STD CATE	EGORY			SSION STD E CLASS	5	SPECIAL FEATURES		
М	IGMXR01	103AA		LEV 3 OPTI	ON2 WITH	FEL		E	oc		HCT		
M	IGMXR01	3030B		LEV 3 OPTION2 WITH FEL				PC			HCT		
		l		E	EMISSION (CREDIT	INFC	RMATION			10		
	EDIT FO	X FLEET AVE OR EXTENDED RANTY			EDIT FOR I					2	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEE	T AVE	RAGE	INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	С	CHO/NMHC RATIO	NMOG+NO PC+LDT			LVW) LDT (3751 LVW-8500 MDV		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*		0.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-006-2250 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

YTH MANAMA

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seg. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

The state of the s

Executed at El Monte, California on this 1674 day of March 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-006-2250

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG (g/r			O mi)		Ox mi)	HC (mg			M mi)
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	***	*	*	*	*		*	***	* * * * * * * * * * * * * * * * * * * *	* * * * * * * * * * * * * * * * * * * *	*
FTP@UL	GASOLINE- TIER3 E10	0.035	0.070	1.3	1.7	* * *	*	*	4	0.001	0.003
50°F @4K		*	* * * * * * * * * * * * * * * * * * * *	* *	*	*	d 3* 9.		2. * 2.5		10.25 Feb. 40.5

	FUEL TYPE	NMOG+N	lOx (g/mi)	CO (cert	(g/mi)
	POELTIPE	CERT	STD	CERT	STD
HWFET @ 50K		*	1015		
HWFET @ UL	GASOLINE-TIER3 E10	0.001	0.070		
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			4.9	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			rain de la company. Pais de la company de la c	US06	Despiration	SC03	ni tigaeri e. Trigandire ni	COM	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT		*		*	*			
0,,,,,		STD	*	*		*	*			
Kerin Eje	70 K 4	CERT	*	***	0.0	* ***	*	0.033	1.1	· · · · · · · · · · · · · · · · · · ·
@ UL	GASOLINE- TIER3 E10	STD			6	*	*	0.077	4.2	*
	9 3 2	BIN						0.080		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	ar integral		WHOLE							
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (@ UL	2DI	HS (g/test) (@ UL	RL (g/	mi) @ UL	
	5	CERT	STD	FEL	CERT	STD	FEL	CERT	STD	
MGMXR01103AA	GASOLINE- TIER3 E10	0.211	0.300	0.300	0.251	0.300	0.300	0.00	0.05	
MGMXR013030B	GASOLINE- TIER3 E10	0.262	0.300	0.300	0.214	0.300	0.300	0.00	0.05	



Executive Order: A-006-2250

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @	D UL	FUEL TYPE		IG TEST) @ UL	2DHS R (g/test	Charles in American	BLEED C TEST (g/t	24		
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
MGMXR01103AA	GASOLINE- TIER3 E10	0.05	0.20	GASOLINE- TIER3 E10	*	r de agredade El caractera d	STEPHAN	*	0.009	0.020		
MGMXR013030B	GASOLINE- TIER3 E10	0.01	0.20	GASOLINE- TIER3 E10		repret i rajih repret i rajih	3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3	*	0.017	0.020		
	EFFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INC	HES)			

 EVAPORATIVE FAMILY
 LEAK FAMILY
 CERT
 STD

 MGMXR013030B
 MGMXR013030B-LK1
 *
 0.02

 MGMXR01103AA
 MGMXR01103AA-LK1
 *
 0.02

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD
CHEVROLET	CAMARO	PC	2.0	M6,SA8	MGMXR013030B	1 .	*
CHEVROLET	MALIBU	PC	2.0	A9	MGMXR01103AA	1	*