\sim	
CALIFORNIA AIR RESOURCES BOAR	Ą
AIR RESOURCES BOAR	D

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP IN	FOR	MATION			Colorest and			
MODE		TES	T GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE			
2021	LM	MGMX	W02.7105			PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSIO							ION C	CATEGORY INTERIM / INTERMEDIATE IN-US					EDIATE IN-USE STD		
EXH/ORVR EVAP						FTP SFT				FTP			SFTP		
150000 150000 LEV3 ULEV50						ULEV50	LEV 3 COMPOSITE *				PM				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS		ENGINE DISPLACEMENT				
1	1 DFI, TC, CAC, TWC, WR-HO2S, HO2S								FULL	ALL MODEL	S				
*	* *							P	ARTIAL	*			2.7		
*	* *								TIAL WITH	*					
			E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATI	ON				
EVA	P / OR	RVR I	FAMILY	EVA	PORATIVE	E STD CATE	GORY		EVAP EMISSION STD VEHICLE CLASS			SPI	SPECIAL FEATURES		
1	MGMXR	0110	3AA	LE	EV 3 OPTI	CON2 WITH	FEL		E	PC .	HCT				
					I	EMISSION CI	REDIT	INFO	ORMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N N						
1					NMOG	AND FLEET	AVE	RAG	INFORMA	TION					
NMOG RAF	CH4 RAF		FTP IMOG/NMHO RATIO		ICHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)) LDT						
*	*		1.10		*	0	.058			0.065			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 15th day of June 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division

R	A	A		A L I RES	FO	R I es b	VIA		GENERA L	L MOT LC.	ORS		E) New Passe			Light-D	outy T n-Dut			
								A	TTAC	HM	ENT									
	E	XHAU	JST		DEVA	POF	RATIV	EEMI	SSION	STAN	DAR	DS AN	D CERTI	FIC	ATION	LEV	ELS	3		
		E	EXH/	AUST	EMISS	ION S	STAND	ARDS A	ND CER	TIFICA	ATION I	EVELS	(FTP, HW	FET,	50°F, 2	20°F)				
		FUEL	TY		monoxi adjustn ORVR	de; N nent fa [g HC	Ox: oxio actor; 2 /gallon	des of ni DHS/3D dispens	itrogen; F HS [g HC ed]: on-b	ICHO: C/test]: oard re	formald 2/3 day fueling	lehyde; F s diurnal vapor re	bon; NMH PM: particu +hot-soak covery; g: ure; SFTP	late RL gram	matter; [g HC/m n; mg: m	RAF: r ni]: runi nilligrar	eactiv ning l n; mi.	vity oss;		
				ľ	NM	OG+I	NOx	1	co		N	Ox		нсн	0	1	P	M		
					(g/mi)				(g/mi)		(g	/mi)		mg/n	ni)		(g/	mi)		
					CERT		STD	CER			CERT	STD		Г	STD		RT	STD		
FTP@5	UK	GASO	*	E-	*		*	*	*		*	*	*		*		t	*		
FTP@L	IL	TIER			0.020		0.050	0.4	1.	7	*	*	*	*		4		4 0.00		0.003
50°F @	4K		*		*		*	*	*		*	*	*		*					
						FU	EL TY	E				NMOG+NOx (g/mi)			T		(g/mi)			
		FOLG					*					ERT STD			CERT		STD			
HWFE																				
HWFE					GASOL	INE-	TIER3	E10 P	REM	EM 0.(0.050							
20°F	@ 50	DK	CC	-					E (TIE	-					1.	5		10.0		
				1	SFTP E	XHA			I STAND	ARDS	AND C		ATION LE	VEL						
	EU	JEL TYPE						US06 CO		M	NIMO	SC03	со	NIRA	COMP		SITE	PM		
	FU	UEL ITPE			NMOG+NOx (g/mi)			(g/mi) (mg/m			1	mi)	(g/mi)	(g/mi)			J/mi)	(mg/mi)		
		*		CERT		* *		*			*	*								
@4K								*				*								
				CER		*		*		1		*	*	(0.026).6	*		
@ UL	TI	ASOLINE- IER3 E10 STD PREM				* 6		6		*	*	0.077		4.2		*				
		vanderd		BIN				1.1						0.070						
			WH	OLE	VEHICL	E EV	APOR		MISSION	STAN	DARD	S AND C	ERTIFICA	TIO	N LEVE	LS				
							W	HOLE	/EHICLE	EVAP	ORATI	VE TEST	ING							
EVAP	MIL		- I CHEI		TYPE 3DH			(g/test) @ UL			2DHS (g/test) (@ UL		RL (g/mi)		ni) @	@ UL		
	GAS			ASOL			STD	TD FEL (RT	STD	FEL	FEL CE		ERT		STD			
MGMXR			Т	IER3	E10	0.2		.300	0.300	0.2		0.300	0.30		0.00 0.05					
C	RVF	R / FUI	ELC	DNLY	/ CANIS	STER	BLEE	EVAP	ORATIV				RDS AND				LEVE	ELS		
EVAP(FA	ORA			ORVR	t (g/gall	on) (DUL	FILE	3D			TEST	2DHS RIG TES (g/test) @ UI			EST BLEED CANISTER				
			FU	EL TY	PEC	ERT	STD			CE	1	STD	CERT	1	STD	CER	1	STD		
MGMXR	011	03AA	1	SOLIN ER3 H	1 0	.05	0.20		DLINE- R3 E10	-	•	*	*		*	0.00		0.020		

MC IN AIR RESC	FORNIA DURCES BOARD	LLC.			Executive Order: A-006-2267 Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LY LEAK FAMILY		CERT	ſ	STD						
MGMXR01103AA	MGMXR01103AA-LI	K1	*		0.02						
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/ii full/partial/partial with fines or prefix 2: parallel; (2) suffix: set device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MD 2: heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-em dAC: HC adsorbing cata 3: selective catalytic redu izer; DPF: diesel particu d02S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection ndirect fuel injection; TC n-board diagnostic; DOF eries; a hyphen (-) betwee coated DPF); CNG/LN4 E10: "10%" ethanol ("90 continuously variable tr ion; AMS: automated ma V: plug-in hybrid electric	01-850 V 850 CS: en /W: lo hission lyst; W uction- late fil e/linea nsor; I in (bell c/SC: tr con CSC: tr con 0%"ga ansmin anual-	0#GVWR,3751-5750 1-10000#GVWR; ME hission control system aded vehicle weight; vehicle; TZEV: trans /U: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea t driven)/(electric drive urbo/super charger; C ct ozone reducing; H0 er treatment ECS ind npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectabl selectable transmissi	#ALVW; LDT4: I V5: MDV 1000 n; CERT: certifica ALVW: adjusted itional ZEV; TW NAC: NOx ads OC: ammonia ox filter for spark-io sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon icates multiple f tural gas; LPG: atic (with lockup e continuously v on; OT: other tra	kidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; .P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi						

2021 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD					
CADILLAC	CT4	PC	2.7	SA10	MGMXR01103AA	1	F					
CADILLAC	CT4 AWD	PC	2.7	SA10	MGMXR01103AA	1	F					
CADILLAC	CT4 V	PC	2.7	SA10	MGMXR01103AA	1	F					
CADILLAC	CT4 V AWD	PC	2.7	SA10	MGMXR01103AA	1	F					