

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2021	. мо	MXV03.0043			PC		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICLE EMIS						ION (ATE	TERI	ERMEDIATE IN-USE STD				
EXH/ORVR EVAP				FTP			SF	SFTP FTP			SFTP		
150000 150000				LEV3	3 ULEV70 LEV 3 CO			COMPOSITE PM			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	ATUS		NGINE DISPLACEMENT (L)		
1	DFI	, 2TC, CAC,	2WR-I	HO2S, 2T	WC, 2HO2S			FULL	ULL ALL MODELS				
*		*						PARTIAL	*	3.0			
*	* *							TIAL WITH	*				
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OF	VR) FAMIL	(INFORMATIO	1			
EVA	\P / OR\	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	ORY EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES		
1	MGMXR0	L103AA	LE	V 3 OPTI	CON2 WITH	FEL		E	°C		HCT		
				I	EMISSION CI	REDIT	r info	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY									OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		IO/NMHC RATIO	NMOG+NOX FLEE PC+LDT (0-3750 L (g/mi)						MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-006-2268 dated June 16, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{/8t/k}$ day of November 2020.

len/Lyons, Chief

Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				NMOG+NOx (g/mi)			CO (g/mi)				NOx g/mi)		HCH mg/			PM (g/mi)			
				CERT	r	STD	CER	т ст	D	CERT	STE	CER	CERT		CE	RT	STD		
FTP@5	0K	*		*		*	*	*		*	*	*	\neg	*	* *		*		
FTP@l	GASOLINE- COL TIER3 E10 PREM			0.058	во	.070	0.5	1.	7	*	*	*	*		4		0.0	001	0.003
50°F @	50°F @4K *			*		*	*	*		*	*	*	*						
)			N	NMOG+NOx (g/mi)				CO (g/mi)				
					FUI	EL TYF	'E			С	CERT		STD		CERT		STD		
HWFE	T @ 50k					*					*								
HWFE	T @ UL			GASOL	INE-1	TIER3	E10 P	E10 PREM		0.	0.004 0.07)						
20°F	@ 50K	c	DLD CO) E10	PREM	IUM G	ASOLIN	E (TIE)	R3)					1.9	9	:	10.0		
			S	FTP E	XHAL	JST EN	ISSION	I STAND	ARDS	AND	CERTIFIC	CATION LI	EVEI	_S					
					US06						SC03			COMPOS			DSITE		
	FUEL TYPE				OG+N	Ox	CO		PM		G+NOx	CO N				со	PM		
					(g/mi)		(g/mi)		g/mi)	(9	g/mi)	(g/mi)		(g/mi)	(9	g/mi)	(mg/mi)		
@ 4K	*	* CI			*		*				*	*							
					*		*				*	*							
		ASOLINE- LER3 E10 STE PREM BIN		·	*		*		2		*	*		0.032		0.4	*		
@ UL	TIER3				*		*		6		*	*	0.077			4.2	*		
													0.080						
		WF	IOLE V	'EHICL	E EV	APOR/	ATIVE E	MISSIO	N STA	NDAR	DS AND	CERTIFIC	ΑΤΙΟ	N LEVE	LS				
				WHOLE VEHICLE EVAP						PORAT	IVE TES								
	PORATIVE FUEL TYPE		3	3DHS (g/test) @ UL				2DH	2DHS (g/test) @ UL			RL (g/mi) @ UL			UL				
				CERT		IT -	STD	FEL	FEL CE		STD	FEL	-	CERT		STD			
MGMXF	MGMXR01103AA		ASOLI SIER3		0.211 0		.300	0.300	300 0.25		0.300	0.30	00	0.00		0.05			
0	DRVR / I	UEL	ONLY	CANI	STER	BLEE) EVAP	ORATIV	E EMI	SSION	STAND	ARDS AND) CE	RTIFICA	TION	LEVE	LS		
FUEL ONLY EVAP & CANISTER BLEED																			
	EVAPORATIVE FAMILY					llon) @ UL FUEL T					HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @				ED CANISTER Γ (g/test) @ 4K		
			JEL TY	PE C	ERT	STD		1		ERT	STD	CERT		STD	CEF	RT	STD		
MGMXF	R011037		SOLIN ER3 E	1 0	.05	0.20		OLINE- R3 E10		*	*	*		*	0.0	09	0.020		



GENERAL MOTORS LLC.

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MGMXR01103AA	MGMXR01103AA-LK1	*	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL	YEAR: VE	ODELS INF	ORMATION	

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CADILLAC	CT5	PC	3.0	SA10	MGMXR01103AA	1	F
CADILLAC	CT5 AWD	PC	3.0	SA10	MGMXR01103AA	1	F
CADILLAC	CT5 V	PC	3.0	SA10	MGMXR01103AA	1	F
CADILLAC	CT5 V AWD	PC	3.0	SA10	MGMXR01103AA	1	F