

BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0514

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP II	VFO	RMATION	I					
MODE		EST GROUP		VEHIC	LE CLASS(LE CLASS(ES) FUEL			JEL CATEGORY			FUEL TYPE		
2021	1 MBMXV03.0H58 PC						PLUG-IN HYBRID ELECTRIC VEHICLE				GASOLINE			
USEFUL LIFE (miles)				VEHICLE EMISSION CATEGORY				T	INTERIM / INTERMEDIATE IN-USE STD					
EXH/ORVR EVAP				FTP S			SFTP	TP FTP			SFTP			
15	0000	150000		LEV3	ULEV125	25 LEV 3 COMPOSIT			E	*		PM		
SPE	CIAL FE	ATURES & EXI	IAUST		ON CONTRO	OL	OBD S			STATUS		ENGINE DISPLACEMENT		
1	T	WC, WR-HO2S,	HO2S	, DFI,	TC, CAC			FULL		*				
*			*					PARTIAL		*		3.0		
*			* PARTIAL WIT FINES						TH	ALL MODELS				
		EV	APOR	ATIVE &	REFUELING	G (EVA	P/C	RVR) FAM	VILY	INFORMATION	1			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORICAL						GORY	'	EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES		
M	BMXR01	40G3H	LEV	7 3 OPT	ON2 WITH FEL PO			PC		*				
				I	EMISSION C	REDIT	IN!	FORMATIC	ON					
ALLOWANCE FOR TEST GROUP TZEV NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					IT FOR	NMOG CREDIT FOR NON-PZEV ZERO- EVAP			- 1 9	NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
* N						N			N		N			
				NMOG	AND FLEE	TAVE	RA	GE INFORI	MA'	TION				
NMOG RAF	CH4 RAF	MINROY 2/MINNEY DC 1 11 11 27 27 27 27 27							MDV (10,001-14,000					
*	*	1.10		*		0.058				0.065	T	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0514

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC. LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have five (5) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of seventy five dollars (\$75) per vehicle for the third through fifth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 5th day of May 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-

TIER3 E10

MBMXR0140G3H

0.20

0.01

BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0514

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	LATIA		A STATE OF THE PARTY OF THE PAR	-								(FTP, HW)				
	FUE	≣L TY	n a 0	nonoxi djustm DRVR	de; No nent fa [g HC	Ox: oxid actor; 2[/gallon (les of nitr DHS/3DH dispensed	ogen; H S [g HC d]: on-bo	CHO: (test]: pard re	formale 2/3 day	dehyde; f ys diurna i vapor re	rbon; NMH PM: particu I+hot-soak covery; g: lure; SFTF	ulate ; RL gran	matter; [g HC/m n; mg: m	RAF: ni]: ru nilligra	reactive inning learn; mi:	vity oss:				
					NMOG+NOx (g/mi)		CO (g/mi)				NOx g/mi)		HCH (mg/r		T	PM (g/mi)					
				CERT STD		CERT	ST	D	CERT	CERT STD		CERT :		STD CER		STD					
FTP@5		*		*		*	*	*		*	*	* *		* *		*	*				
FTP@I	11 1	R3 E	,	0.04	5 (0.125	0.3	2.	1	*	* *			4	0	.001	0.003				
50°F @	ARCI	OLIN		0.084	4 (250	0.4	2.	1	*	*	*		16							
					EII	EL TVD	E			N	MOG+N	Ox (g/mi)		CO (g/mi)							
				FUEL TYPE			E			CI	CERT		STD CE		RT STD		STD				
HWFE.	T @ 50K					*					*										
HWFE	T@UL			GAS	SOLIN	E-TIE	R3 E10			0.010		0.125	0.125								
20°F	@ 50K	CC	DLD CO	E10	REGU	LAR G	ASOLINE	(TIEF	:R3)			0.		7 10.0							
			S	FTP E	XHAU	JST EM	ISSION S	STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	.s							
		FUEL TYPE		US06							SC03			C	OMP	OMPOSITE					
	FUEL T			NMOG+NOx (g/mi)		CO PN (g/mi) (mg/				G+NOx /mi)	CO (g/mi)	1			CO (g/mi)	PM (mg/mi					
@ 4K	*		CERT		*		*				*	* *									
					*		*				*	*									
		CER		RT *		*	* 2			*	*		0.029		0.7	*					
@ UL						ASOLINE- IER3 E10 STD			*		*	(5		*	*	(0.077		4.2	*
				1							0.120										
		WH	OLE V	EHICL	E EV	APORA	TIVE EM	ISSION	STAI	NDARD	S AND	ERTIFIC	ATIO	N LEVE	LS						
						WI	HOLE VE	HICLE	EVAP	ORATI	VE TEST	ING									
	ORATIVE MILY	1 1-1		TYPE 3DHS (g		DHS (g	/test) @ UL			2DH	2DHS (g/test) @ U		R		RL (g/mi) @ UL						
				CERT		RT S	TD FEL		CE	RT	STD	STD FEI		CER			STD				
MBMXF	0140G3I	2	ASOLI IER3		0.1	91 0	.300	0.300	0.1	.30	0.300	0.30	00	0.0	00		0.05				
(ORVR / F	UEL (ONLY /	CANIS	STER	BLEEC	EVAPO	RATIVE	EMIS	SSION	STANDA	RDS AND	CE	RTIFICA	TION	I LEVE	LS				
							FUEL ONLY EVAP & CANISTER BLEED														
	ORATIVE		ORVR	(g/gall	lon) @	UL	FUEL	TYPE		HS RIC g/test)	@ UL	2DHS (g/tes			BLEED CANISTE TEST (g/test) @ 4						
		FUEL T		PE C	ERT	STD		CE			STD	CERT	T	STD	CE	RT	STD				



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0514

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MBMXR0140G3H	MBMXR0140G3H-001	0.00	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine: HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH; fuel fired heater; F/P/\$; full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	BMW	745E XDRIVE	PC	3.0	SA8	MBMXR0140G3H	1	\$

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	AY (MILES)	ZEV	
NUMBER	PHEVITPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	*	22.30	22.60	*	24.28	24.53	0.00	