

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

										-			
					TEST GRO	DUP IN	NFOR	MATION					
MODE	- 1 - 11	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2021	MF	AFMXT03.33U3 LDT2, LDT3						FLEX-FUEL VEHICLE (FFV)			85% ETHANOL, GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISS						SSION CATEGORY			INTERIM / IN	ITE	ERMEDIATE IN-USE STD		
EXH	EXH/ORVR EVAP			FTP SI			SF	FTP FTP			SFTP		
15	150000 150000 LEV3 ULEV70 LEV 3 COMPOSITE *				PM								
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	T	ENGINE DISPLACEMENT		
1	21	NC (2), 2HO2S	,2WR-	HO2S,SFI	, DFI , EGR			FULL	ALL MODELS				
*	*							ARTIAL	*	1	3.3		
*			*	* PARTIAL WITH * FINES									
and the state of the		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
M	IFMXR01	70NDF	L	EV 3 OPTI	CON2 WITH	FEL	LDT2				HCT		
M	IFMXR01	70NDG	L	EV 3 OPTI	ION2 WITH	FEL		LI	DT3	HCT			
				l	EMISSION CI	REDIT	INFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N		N				N		
			1	NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO (GASOLINE		HCHO/NMHC RATIO (GASOLINE) NMOG+NOX FLI PC+LDT (0-375 (g/mi)							NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.058		0.065			*		
										-	Central Sustama Dhaga		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this  $\underline{1974}$  day of June 2020.

Allen Jons, Chief Emissions Certification and Compliance Division



FUEL TYPE

FORD MOTOR COMPANY Executive Order: A-010-2257 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		UEL	IYPE													
					)G+NOx g/mi)		CO (g/mi)			lOx /mi)		HCH (mg/r			'M 'mi)	
				CERT	ST	CER	T ST	D	CERT	STD	CER	T	STD	CERT	STD	
FTP@5	0K	*		*	*	*	*		*	*	*		*	*	*	
FTP@L	TP@UL (GASOLINE TIER3 E10		LINE-	0.043 (0.030					* (*)	* 1. (*) (1			4 (4)	0.000 (0.000)	0.003 (0.003)	
50°F @	4K	*		*	*	*	*	-	*	*	*		*	d <u>(1997) - 1997</u> (1997) - 1997 (1997)		
									N	MOG+N	Ox (g/mi)			CO (g/mi	)	
					FUEL TYPE				CE	CERT STI				r STD		
HWFE	T @ 50	0K			*					*	*					
HWFE	T @ U	IL		(GAS	E85-1 OLINE-1	EPA IER3 El	0)			0.019 0.070 (0.009) (0.070						
20°F	@ 50k					GASOLII 30% EPA NE))	•						2.0 (2.7)		12.5 12.5)	
				SFTP EX	HAUST	EMISSIO	N STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	.s			
					US06				SC03			COMPOSITE				
	FUE	FUEL TYPE			G+NOx	co	-	M		G+NOx	CO		OG+NOx	СО	PM	
				(	g/mi)	(g/mi)	) (mg	g/mi)	(g/	/mi)	(g/mi)		(g/mi)	(g/mi)	(mg/mi)	
@ 4K	4K *		CER	т	*	*				*	*					
				2	*	*			*		*					
			-EPA STD		*	*				*		0.037		1.3	*	
@ UL	E85	E85-EPA			*	*		6		*	*		0.077	4.2	+	
			BIN		*	*		3	*		*		0.025	1.0	*	
@ UL			LINE- STD *		*	*		6		*		0.077		4.2	*	
				1					1				0.070			
		V	VHOLE	VEHICLI	EVAPO	RATIVE	EMISSION	N STA	NDARD	S AND C	ERTIFIC	ATIO	N LEVEL	S		
						WHOLE	VEHICLE	EVAP	PORATI	VE TEST	TING					
EVAPORATIVE					YPE 3DHS (g/test) @ UL				2DHS (g/test)		@ UL		RL (g/mi)		@ UL	
				CERT		STD	FEL	CE	RT STD		FE	L	CER	r	STD	
MFMXF	R0170	NDF	GASOI TIER3		0.228	0.400	0.400	0.:	172	0.400	0.4	00 0.00			0.05	
MFMXF	R0170	NDG	GASOI TIER3		0.228	0.500	0.500	0.:	172	0.500	0.5	00	0.00		0.05	

A	FORD MOTOR COMPANY			M	Executive Order: A-010-2257 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
		FUEL ONLY EVAP & CANISTER BLEED											
EVAPORATIVE FAMILY	ORVR (	g/gallon) @	UL	FUEL TYPE					HS RIG TEST		BLEED CANISTER		
	FUEL TYP	PE CERT STD		FUEL	IYPE	CERT	STD	CER	/test) @ UL RT STD		CERT	est) @ 4K	
MFMXR0170NDG	E10-EPA		0.20	GASOLINE- TIER3 E10		*	*	*		*	0.009	STD 0.020	
MFMXR0170NDF	E10-EPA 0.04 0		0.20	GASOLINE- TIER3 E10		*	*	*		*	0.009	0.020	
E	FFECTIV	E LEAK D	IAMETE	ER STA	NDARI	D AND CE	RTIFICAT		EVI	EL (INCH	ES)		
EVAPORATIVE FAMILY LEAK FAMI											STD		
MFMXR0170NDG MFMXR0170NDG				-001 *							0.02		
MFMXR0170	NDF	MFMXR0:	170NDF-	-001 *					0.02				
MFMXR0170NDF MFMXR0170NDF-001 * 0.02   *: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT-6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AlR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/S: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: comp													

# 2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	EXPLORER FFV AWD	LDT2	3.3	SA10	MFMXR0170NDF	1	F
FORD	POLICE INTERCEPTOR UTILITY FFV	LDT3	3.3	A10	MFMXR0170NDG	1	F