

FORD MOTOR COMPANY

Executive Order: A-010-2258

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	IFOI	RMATION						
MODE YEAR		EST GROUP		VEHIC	LE CLASS(I	ES)		FUEL CATEGORY			FUEL TYPE			
2021	MF	MXT03.03P1	3P1 LDT4					PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSIO							CATEGORY INTERIM / INT					ERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP			FTP SFTP			FTP	FTP			SFTP		
15	150000 150000 LEV			LEV3	SULEV30	LEV	3 (COMPOSITE	11	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD :	OBD STATUS			ENGINE DISPLACEMENT (L)		
1	TWC,DFI,WR-HO2S,HO2S,TC,CAC							FULL	T	ALL MODELS				
*	*							PARTIAL	T	*	3.0			
*		*						RTIAL WITH	1	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION ST VEHICLE CLASS									SPECIAL FEATURES					
N	IFMXR01	65LDG	LEV	V 3 OPT	CON2 WITH	FEL	LDT4			r4	HCT			
					EMISSION C	REDIT	INF	ORMATION	1					
ALLOWANCE FOR TEST GROUP TZEV NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							OG CREDIT FOR N-PZEV ZERO- EVAP				OPTIONAL EXH. STD FOR WORK TRUCKS			
	ALL M	ODELS		N			N N			N	N			
NMOG AND FLEET AVERAGE INFORMATION														
NMOG RAF	E DAE NMOG/NMHC PATIO PC+LDI (U-			STATE OF THE STATE	Charles and the				NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)					
*	*	1.10		*	(0.058 0.065 *					*			
					=	-		. D: 1	_		-	1-10t Dh		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



FORD MOTOR COMPANY

Executive Order: A-010-2258

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 2474 day of June 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-TIER3 E10

MFMXR0165LDG

0.004

0.20

FORD MOTOR COMPANY

Executive Order: A-010-2258

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

	ATTACHMENT																	
EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
	EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																	
	FU	FUEL TYPE			CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
				NMOG+NOx (g/mi)				CO (g/mi)			NOx (g/mi)		HCHC (mg/m			PM (g/mi)		
				CER	RT	STD	CERT	STI	0	CERT	STD	CERT		STD	CE	RT	STD	
FTP@5	0K	*		*		*	*	*		*	*	*		*		k	*	
FTP@l	11 1	R3 E	accord.	0.02	21 (0.030	0.87	1.	0	*	*	0.2		4	0.1	002	0.003	
50°F @	4K	*		*		*	*	*		*	*	*		*				
					FU	EL TY	PE					Ox (g/mi)				g/mi		
										C	ERT	STD	\dashv	CEF	RT	_	STD	
HWFET @ 50K * * *																		
HWFE	T@UL			GZ	ASOLIN	E-TIE	R3 E10			0	.015	0.030						
20°F @ 50K COLD CO E10 REGULAR GA					ASOLIN	NE (TIER3)				0.7		78 12.5		12.5				
				SFTP	EXHA	JST EN	IISSION	STANDA	ARDS	AND	CERTIFIC	ATION LE	VEL					
							US06			SC03				COMPOSITE				
	FUEL 1	YPE		NI	NMOG+NOx (g/mi)		CO (g/mi)			NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)			CO J/mi)	PM (mg/mi)	
@ 4K	*	CE		г	*		*				*	*						
			STD		*		*				*	*						
			CER	Г	*		*	4	l		*	*	0	.0285	0	.87	*	
@ UL		SOLINE- ER3 E10		S		*	* 6			*	*	0.077		4	1.2	*		
		BI											(0.040				
		Wh	HOLE \	/EHIC	LE EV	-						CERTIFICA	ATIO	N LEVE	LS			
	0 m 4 mm /					W	HOLE V	EHICLE	EVAP	ORAT	IVE TES	ring			DI /ale	ni\ @		
	ORATIV	- F	FUEL T	YPE			g/test) @			2DHS (g/test) @ UL				III) (<u>u</u>) @ UL	
		_			CEF	TS.	STD	FEL	CE	RT	STD	FEL		CE	RT	_	STD	
	0165LD	3 7	GASOL:	E10	0.21		.500	0.500	*		0.500	0.50		0.0				
	DRVR / F	UEL	ONLY	CAN	IISTER	BLEE	EVAPO	DRATIVE				RDS AND	_			LEVI	ELS	
FVAP	ORATIV	_	ORVR	VR (g/gallon) @ UL SUBSTER BLEED SUBSTER BLEED SUBSTER BLEED					D C	ANISTER								
	MILY			10.0	, e		FUE	TYPE	(g/test)	@ UL	(g/tes	-				est) @ 4K	
		FL	JEL TY	PE	CERT	STD	-		CE	RT	STD	CERT	+	STD	CEF	RT	STD	



FORD MOTOR COMPANY

Executive Order: A-010-2258

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MFMXR0165LDG	MFMXR0165LDG-001	*	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV; super ULEV; ZEV; zero-emission vehicle; TZEV; transitional ZEV; TWC/OC; 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor: WR-HO2S or AFS; wide range/linear/heated air-fuel ratio sensor; NOXS; NOx sensor; PMS; PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR: EGRC: EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR: SFI/MFI: sequential/multiport fuel injection; DFI/IFI; direct/indirect fuel injection; TC/SC; turbo/super charger; CAC; charge air cooler; FFH; fuel fired heater; F/P/\$; full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	LINCOLN	AVIATOR AWD PHEV	LDT4	3.0	SA10	MFMXR0165LDG	1	F

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	DUEV TVDE	UDDS AER	UDDS EAER US06 AER		HIGHW	ZEV		
NUMBER	PHEV TYPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	TZEV	23.3	25.5	0	24.0	24.0	0.56	