

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	DUP IN	FOR	MATION					
MODE		TEST GROUP VEHICLE CLASS(ES)				S)		FUEL CATEGORY			FUEL TYPE		
2021	MFMXT03.03U2 LDT3, LDT4							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
ļ	USEFUL	. LIFE (miles)		VEF	ICLE EMISS						TERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
15	0000	150000)	LEV3	ULEV70	LEV	3 C	MPOSITE	*		PM		
SPE	CIAL FE	ATURES & EX	HAUS Stems		ON CONTRO	L		OBD S	TATUS	I	ENGINE DISPLACEMENT (L)		
1	21	WC(2),DFI,2W	R-HO	2S,2HO2S	, 2TC , CAC			FULL	ALL MODELS				
*			*				P	ARTIAL	*		3.0		
*	*							RTIAL WITH FINES					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
M	IFMXR01	85NDG	LE	V 3 OPTI	CON2 WITH	ON2 WITH FEL			ЭТЗ		НСТ		
M	IFMXR01	70NDG	LE	V 3 OPTI	CON2 WITH	DN2 WITH FEL LDT3)ТЗ	нст			
				I	EMISSION C	REDIT	INFC	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV				R OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N								N		N		
				NMOG	AND FLEE	T AVE	RAGI		TION				
NMOG RAF	CH4 FTP RAF NMOG/NMHC RATIO HCHO/NMHC RATIO (g/mi)				0-375								
*	* 1.10 * 0.05					.058		0.065 *					
See the	o Attach	mont for Vohi		adole Evr	anorativo Ea	mily	Engir	Displace	mont Emissio		ontrol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-010-2259 dated June 10, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>30th</u> day of April 2021.

Allen lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NO: (g/mi)						Ox mi)		HCHO (mg/mi)		PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		OLINE- R3 E10	0.050	0.070	1.02	1.7	*	*	1	4	0.00	2 0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
				FUEL TYP	-		NN	IOG+N	Ox (g/mi)		CO (g/	/mi)
				FUELITP	E		CE	RT	STD	CEF	RT	STD
HWFET @) 50K			*			*		*			
HWFET (@ UL		GASO	LINE-TIEF	R3 E10		0.0	19	0.070			
20°F @	50K	COLD	CO E10 RI	EGULAR GA	ASOLINE	(TIER3)				0.8	7	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SI	- 1 P E)	THAUSI	EMISSION	ISTAND	ARDS A	AND	CERTIFIC	ATION	EVEL.	.5			
				US06					SC03			CON	IPOS	ITE		
	FUEL TY	PE			DG+NOx g/mi)	CO (g/mi)	-	PM g/mi)		DG+NOx g/mi)	CO (g/mi)		OG+NOx (g/mi)			PM (mg/mi)
@ 4K	*	CERT		*		* *				*	*					
-			STD		*	*				*	*				CO g/mi) 4.2 ni) @ l	
		CERT			*	*		2		*	*	0	0.044	0.	78	*
@ UL	UL GASOLINE- TIER3 E10		ISIDI		*	*		6		*	*	0.077		0.077 4.		*
			BIN									(0.070	(g/mi) 0.78 4.2 S (g/mi) @		
	1	WH	OLE VE	EHICLI	E EVAPO	ORATIVE E	MISSIO	N STAN	DAR	DS AND C	ERTIFIC	CATIO	N LEVELS	5		
						WHOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ING					
	ORATIVE	F	UEL TY	'PE	3DH	S (g/test) (DUL		2DH	IS (g/test)	@ UL		RL	(g/mi	0.78 4.2 g/mi) @ (JL
					CERT	STD	FEL	CER	RL	STD	FE	Ľ	CERT		S	STD
MFMXF	R0170NDG	_	ASOLIN IER3 E		0.2284	0.500	0.500	0.17	17	0.500	0.5	00	0.000		0	.05
MFMXF	R0185NDG		ASOLIN IER3 E		0.202	0.500	0.500	*		0.500	0.5	00	0.02		0	.05



ORVR / FUI		NISTER	BLEED	EVAPOR	RATIVE	EMISSION			CERTIFIC	TION LEV	FLS		
		EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS FUEL ONLY EVAP & CANISTER BLEED											
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL	TYPE		IG TEST) @ UL		lig test) @ UL	BLEED C TEST (g/t	-		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	D BLEED C TEST (g/t CERT 0.0030 0.003	STD		
MFMXR0170NDG	GASOLINE- TIER3 E10	0.044	0.20	GASOL TIER3		*	*	*	*	0.0030	0.020		
MFMXR0185NDG	E10-EPA	0.01	0.20	GASOL TIER3		*	*	*	*	0.003	0.020		
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE	EVAPORATIVE FAMILY LEAK FAMIL					Y CERT				STD			
MFMXR0170NDG MFMXR0170NDG			-001 *					0.02					
MFMXR0185	NDG	MFMXR0	185NDG	-001		ł	r			0.02			

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR;3751-5750#LVW; LDT3: LDT 6001-8500#GVWR;3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR;5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvoen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor: NH3S: ammonia sensor: EGR: exhaust gas recirculation: HP/LP EGR: High/Low Pressure EGR: EGRC: EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven): PAIR: pulsed AIR: SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" éthanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, = credits. S = credits for some/select models

	2021 MODEL Y	'EAR: VEI		ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	EXPLORER AWD 3.0L V6 GTDI	LDT3	3.0	SA10	MFMXR0170NDG	1	F
FORD	EXPLORER AWD 3.0L V6 GTDI	LDT3	3.0	SA10	MFMXR0185NDG	1	F
FORD	EXPLORER POLICE INTERCEPTOR UTILITY AWD 3L V6 GTDI	LDT3	3.0	A 10	MFMXR0170NDG	1	F
FORD	EXPLORER POLICE INTERCEPTOR UTILITY AWD 3L V6 GTDI	LDT3	3.0	A 10	MFMXR0185NDG	1	F
FORD	EXPLORER RWD 3.0L V6 GTDI	LDT3	3.0	SA10	MFMXR0170NDG	1	F
FORD	EXPLORER RWD 3.0L V6 GTDI	LDT3	3.0	SA10	MFMXR0185NDG	1	F
LINCOLN	AVIATOR AWD 3.0L V6 GTDI	LDT4	3.0	SA10	MFMXR0170NDG	1	F



2021 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD				
LINCOLN	AVIATOR RWD 3.0L V6 GTDI	LDT3	3.0	SA10	MFMXR0170NDG	1	F				