

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION															
MOD YEA		TE	ST GROUP		VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE			
202	1	MFM	XT03.51F1		LDT4					ELECTRIC HICLE		GASOLINE			
	USEF	UL I	LIFE (miles)		VEH	VEHICLE EMISSION CATEG				INTERIM / IN	ITE	FERMEDIATE IN-USE STD			
EX	H/ORV	/R	EVAF)		FTP S				FTP		SFTP			
1	50000)	15000	0	LEV3	ULEV70	LEV	3 CC	MPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS									OBD S	TATUS		ENGINE DISPLACEMENT (L)			
1	1 2TWC(2), DFI, SFI, EGR, EGRC, 2WR-HO2S, 2HO2S, 2TC, CAC								FULL	ALL MODELS		3.5			
*	*							P.	ARTIAL	*					
*	* *								RTIAL WITH *			1			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	AP / O	RVR	FAMILY	EVA	APORATIVE	E STD CATE	GORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	MFMXF	R029	5LDG	L	EV 3 OPTI	ON2 WITH	FEL		LDT4			HCT			
					E	EMISSION CI	REDIT	INFC	RMATION						
	REDIT	FOF	EFLEET AVE REXTENDED RANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
		1	N			N				N		N			
					NMOG	AND FLEE		RAGE	INFORMA	TION					
NMOG RAF					HO/NMHC RATIO	DCTINI /0_3750 IA									
*	*		1.10		*	0	.058			0.065		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>22nd</u> day of September 2020.

Allen/Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/i	i+NOx mi)	-	O mi)		Ox mi)					PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	STD CERT		STD	CEF	RT	STD
FTP@50K	*		*	*	*	*	*	*		*	*	*		*
FTP@UL	GASOLINE- TIER3 E10		0.059	0.070	0.4	1.7	*	*		0	4	0.0	01	0.003
50°F @4K		OLINE- R3 E10	0.051	0.140	0.2	1.7	*	*		0	16			
				FUEL TYP	E		N	NMOG+NOx (g/mi)				CO (g/mi)		
				FUEL ITP	E		CE	RT	κτ s ⁻		CERT		STD	
HWFET @ 50K				*			*	r	*					
HWFET @ UL			GASOI	LINE-TIEF	R3 E10		0.0	06	0	.070				
20°F @ 50K		COLD (CO E10 RE	GULAR G	ASOLINE	(TIER3)					1.0			12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFIP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																
						US06				SC03		C				
	FUEL TY	PE		NMOG+	NOx	со	P	м	NMC)G+NOx	со	NMOG+NC	x CC)	PM	
		_		(g/mi)	(g/mi)) (mg	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/n	ni)	(mg/mi)	
@ 4K	@ 4K *		CERT	*		*	*		*		*					
-			STD	*		*				*	*					
	@ UL GASOLINE- TIER3 E10		CERT		*		* 1		*		*	0.043	0.5		*	
@ UL			STD	*	*		* 6		*		*	0.077	4.	2	*	
			BIN									0.080				
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
					١	WHOLE	VEHICLE	EVAP	ORA	FIVE TEST	ING					
	ORATIVE	VE FUEL TY		E	3DHS (g/		g/test) @ UL			2DHS (g/test)		F	RL (g/mi) @) UL	
				CERT		STD	STD FEL CE		रा	T STD FEI		CE	RT	T STD		
MFMXF	R0295LDG		ASOLINE IER3 E1			0.	0.00		0.05							
0	DRVR / FUI	EL O	NLY / CA	NISTEF	R BLEI	ED EVA	PORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	TION LE	VE	LS	
								FL	JEL C	NLY EVA	P & CANIS	STER BLEE	D			
	ORATIVE	C)RVR (g/	g/gallon) @ UL		FUI			HS RIG TEST g/test) @ UL			RIG TEST t) @ UL			CANISTER (/test) @ 4K	
		FUE	EL TYPE	CERT	ST	5		CE	RT	STD	CERT	STD	CERT		STD	
MFMXF	R0295LDG		OLINE- R3 E10	0.01	0.2	0	*	,	r	*	*	*	*		*	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MFMXR0295LDG	MFMXR0295LDG-001	*	0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	F150 HEV 2WD	LDT4	3.5	SA10	MFMXR0295LDG	1	F
FORD	F150 HEV 4WD	LDT4	3.5	SA10	MFMXR0295LDG	1	F