AIR RESOURCES BOARD	A	CALIFORNIA AIR RESOURCES BOARD
---------------------	---	-----------------------------------

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
					IESI GRC		VFUR	MATION					
YEA	- I T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
2021	L MC	RXT03.25P0			LDT2			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATEGORY INTERIM / INTERMEDIATE IN-USE S					
EXH/ORVR EVAP FTP							SFTP FTP				SFTP		
1	150000 150000 LEV3 ULEV70 LEV						3 C	COMPOSITE *			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD STATUS			ENGINE DISPLACEMENT			
1		SFI, 2	TWC,	2HO2S (2)				FULL	*				
*			*						ALL MODELS		3.2		
*	*							TIAL WITH FINES	*				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
1	MCRXR01	18PP0	LF	IV 3 OPTI	ON2 WITH	FEL		LD	DT2		*		
				l	EMISSION CI	REDIT	INFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMAA COENITEAD AAD			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF						0-375		LVW) LDT (3751 LVW-8500 MDV (10,0			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.058			0.065		*		
-			Contraction of the local division of the loc					D' 1		-	Internet Disease		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this ZZND day of June 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



Executive Order: A-009-1530 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

					lOG+N (g/mi)	Ox		CO (g/mi)			NOx g/mi)		HCH mg/r				PM g/mi)		
			F	CER		STD	CER		D	CERT	STD		-	STD	CE		STD		
FTP@5	OK	*		*		*	*	*		*	*	*		*	1		*		
FTP@L		OLIN V3 E1		0.028	36 0	.070	0.4	3 1.	7	*	*	*		4	0.0	005	0.003		
50°F @	4K	*		*		*	*	*		*	*	*		*					
					CUIS		E			N	IMOG+N	Ox (g/mi)			CO (g/mi)				
					FUE		-6			C	ERT	STD		CER	STD				
HWFE	T @ 50K					*					*	*							
HWFE	T@UL			GA	SOLIN	IE-LE	73 E10			0.	0057	0.070							
20°F	@ 50K		GA	SOLIN	TE-COL	D CO	LOW O	CTANE						0.9	2		12.5		
			S	FTP E	XHAU	ST EN	IISSION	STAND	ARDS	AND C	CERTIFIC	ATION LE	EVEL	.S					
				US06						SC03				CC	OMPO	SITE			
	FUEL T	YPE		1	IOG+N (g/mi)	Ox	CO (g/mi)		PM g/mi)	1	G+NOx /mi)	CO (g/mi)		OG+NO (g/mi)		CO /mi)	PM (mg/mi)		
AK	+	* CI		CERT * *				* *											
@ 4K				1	*		*				*	*							
			CERT		*		*	0	. 4		*	*	0	.0313	0	0.72			
@ UL	GASOLI LEV3		STD		*		*		6		*	*		0.077	4	.2	*		
			BIN										-	0.070					
		WH	IOLE V	EHICI	E EVA	APOR/	ATIVE E	MISSIO	N STAI	NDARE	DS AND	CERTIFIC	ATIO	N LEVE	LS				
						W	HOLE	VEHICLE	EVAP	ORAT	IVE TEST	TING							
EVAPORATIVE FAMILY		FIFLIVPF JUMS (0/1			g/test) (@ UL		2DH	S (g/test) @ UL	@ UL		L (g/n	mi) @ UL					
					CER	T	STD	FEL	CE	RT	STD	FEL	FEL		RT	STD			
MCRXF	MCRXR0118PP0			NE- E10	0.25	03 0	. 400	0.375	0.2	.2623 0.400		0.37	0.375 0.00		08	0.05			
C	DRVR / F	UEL	ONLY	CAN	STER	BLEE	D EVAP	ORATIV	E EMIS	SSION	STANDA	RDS AND) CE	RTIFICA	TION	LEVE	LS		
		T										P & CAN							
	ORATIV	E ORVR (g/gall			llon) @	on) @ UL FUEL T					G TEST @ UL		2DHS RIG (g/test) @			EED CANISTER ST (g/test) @ 4M			
		FU	IEL TY	PEC	ERT	STD			CE		STD	CERT		STD	CER	RT	STD		
MCRXF	R0118PP		SOLIN EV3 E	10	.026	0.20		OLINE- V3 E10		*	*	*		*	0.01	44	0.020		

CALI AIR RESC	FORNIA DURCES BOARD		FCA US LLC.	Executive Order: A-009-1530 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	г	STD						
MCRXR0118PP0	MCRXR0118PP0-L	F1	*		0.02						
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines or prefix 2: parallel; (2) suffix: set device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MD ': heavy-duty vehicle; E0 vehicle weight rating; L' per ULEV; ZEV: zero-en AC: HC adsorbing cata : selective catalytic redu izer; DPF: diesel particu 402S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection direct fuel injection; TC h-board diagnostic; DOF eries; a hyphen (-) betwee coated DPF); CNG/LN E10: "10%" ethanol ("90 continuously variable tr ion; AMS: automated m V: plug-in hybrid electric	01-8500 0V 850 CS: em VW: loa nission lyst; W uction-I late filli e/linea nsor; E on (belt C/SC: tu C: corr 0%"gas cansmis cansmis cansmis cansmis cansmis	0#GVWR,3751-5750 1-10000#GVWR; ME nission control system aded vehicle weight; vehicle; TZEV: trans /U: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea c driven)/(electric drivu urbo/super charger; O ct ozone reducing; HO er treatment ECS ind npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectabl selectable transmissi	#ALVW; LDT4: I DV5: MDV 10001 n; CERT: certifica ALVW: adjusted itional ZEV; TW ; NAC: NOX ads DC: ammonia ox filter for spark-io o sensor; NOXS: circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon licates multiple f tural gas; LPG: atic (with lockup e continuously v on; OT: other tra	tidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; .P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi						

2021 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD					
JEEP	CHEROKEE 4X4	LDT2	3.2	A9	MCRXR0118PP0	1	P					
JEEP	CHEROKEE 4X4 ACTIVE DRIVE II	LDT2	3.2	A9	MCRXR0118PP0	1	P					
JEEP	CHEROKEE FWD	LDT2	3.2	A9	MCRXR0118PP0	1	P					
JEEP	CHEROKEE TRAILHAWK 4X4	LDT2	3.2	A9	MCRXR0118PP0	1	P					