

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE	-													
	г ти	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE				
2021	L MF	MXD03.57BG		MDV5 FLEX-FUEL VEHICLE (FFV)						85%	85% ETHANOL, GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION						ION C	ATEC	GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP			SFTP FTP			SFTP			
15	50000	150000		LEV3	ULEV400	(H (L2	ЮТ14 492),	ULEV 35 UC SC03, CYCLE)	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT (L)			
1	1 2TWC(2),DFI,SFI,2WR-H02S,2H02S,EGR							FULL	ALL MODELS	1				
*		*						PARTIAL *			3.5			
*			*					TIAL WITH FINES	*					
I		E\	APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL						
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
ľ	MFMXR02	15GDJ	LE.	V 3 OPTI	CON2 WITH	FEL		MDV5			HCT			
I	MFMXR01	.85NDJ	LE.	V 3 OPTI	CON2 WITH	FEL		MC	vv5	HCT				
					EMISSION CI	REDIT	INFC	RMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
N N									N		N			
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION					
NMOG RAF	IUG CH4 NMUG/NMHC RATIO DT (3751 I VW-8				VW-85	500 G	STD NMOG+NOX FLEET ST GVW) MDV (8501-10000 GVWF (g/mi)							
*	*	1.10		*		*			0.203		0.298			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-010-2267 dated September 3, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>4th</u> day of February 2021.

Allen yons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				-													
)G+NOx g/mi)		CO (g/mi)			IOx /mi)		HCHO (mg/mi)		PM (g/mi)		
				Γ	CERT	ST	CER	ат ѕт	D	CERT	STD	CER	Т	STD	CE	RT	STD
FTP@5	0K		*		*	*	*	*		*	*	*		*	*		*
FTP@L			0.1016					* (*)	* (*)	2.3 (1.6)		6 (6)	0.0 (0.0	026	0.010 (0.010)		
50°F @4	50°F @4K *		*		*	*	*	*		*	*	*		*			
	FUEL TYPE								NMOG+NOx (g/mi)				CO (g/mi)				
						FUEL	TPE			CE	CERT STD			CERT			STD
HWFE	т@:	50K				*					* *						
HWFE	т @	UL			(GAS	E85-1 OLINE-T	EPA Sier3 e1	-			0.0593 0.40 (0.0445) (0.40						
20°F (@ 50	ж			*									*		*	
				5	SFTP EX	HAUST	EMISSIO	N STAND	ARDS	AND C	ERTIFIC	ATION LI	EVEL	S			
		US06											CO	MPOSITE			
	FUEL TY		ГҮРЕ		NMC)G+NOx	со	P	PM		NMOG+NOx		NM	NMOG+NOx		co	PM
					()	g/mi)	(g/mi)	(g/mi) (mg/m		(g/mi)		(g/mi)		(g/mi)		/mi)	(mg/mi)
@ 4K		* CE		CER	г	*	*			*		*					
				STD		*	*				*	*					
		E85-EPA ST		CER	_	*		* *			*	*	0.0805		_	.14	1.3
@ UL	E8			STD	_	*	*	* *		*		*	0.550		6.0		7
						*	*		*		*	*		*		17	3.7
	GAS	CASOT THE												2.17			
@ UL		ER3 E		STD		*	*		*		*	*		0.550	e	5.0	7
				BIN										*			
			WHC	DLE V	EHICLE	E EVAPC	DRATIVE	EMISSION	N STAI	NDARD	S AND C	ERTIFIC	ATIO	N LEVEL	S		
						WHOLE VEHICLE EVAP					ORATIVE TESTING						
EVAPORATIVE FAMILY			FU	FUEL TYPE		3DH	@ UL	2DHS (g/test) (@ UL	@ UL		RL (g/mi) @		UL	
						CERT	STD	FEL	CE	RT	STD	FEL	-	CER	Т		STD
MFMXR	R018	5NDJ		SOLI ER3		0.2015	0.600	0.600	*	r	0.600	0.600		0.016		5 0.05	
MFMXR0215GDJ		5GDJ		SOLI ER3		0.2022	0.600	0.600	*	* 0.600 0.600		0.00	00		0.05		



ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
		FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS R (g/test		IS RIG TEST /test) @ UL		BLEED CANISTE TEST (g/test) @ 4				
	FUEL TYPE	CERT	STD				STD	CER	т	STD	CERT	STD
MFMXR0215GDJ	GASOLINE- TIER3 E10 PREM	0.009	0.20	GASOLINE- TIER3 E10		*	*	*		*	0.0015	0.030
MFMXR0185NDJ	GASOLINE- TIER3 E10 PREM	0.008	0.20	GASOL TIER3		*	*	*		*	0.0033	0.030
	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY LEAK FAMIL			Y CERT					STD				
MFMXR0185NDJ MFMXR0185NDJ			-001 *					0.02				
MFMXR0215GDJ MFMXR0215GDJ			-001 *					0.02				

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC: HAC: HC adsorbing catalyst: WU: warm-up catalyst: NAC: NOx adsorption catalyst: SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine: HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission: AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric rance: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	H CLASS ENGINE (L) TRANS TYPE		EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	TRANSIT T350 VAN 2WD FFV	MDV5	3.5	SA10	MFMXR0185NDJ	1	F
FORD	TRANSIT T350 VAN 2WD FFV	MDV5	3.5	SA10	MFMXR0215GDJ	1	Я
FORD	TRANSIT T350 WAGON 2WD FFV	MDV5	3.5	SA10	MFMXR0185NDJ	1	F
FORD	TRANSIT T350 WAGON 2WD FFV	MDV5	3.5	SA10	MFMXR0215GDJ	1	F