

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRC	UP II	NFOR	MATION						
MODE					VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
2021	L P	MFMX	V03.5VGT		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
	USEF	UL LI	IFE (miles)		VEHICLE EMISSION CATEGOR				GORY		INTERIM / INT	ERN	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP SF			TP FTP			SFTP				
150000 150000					LEV3	ULEV125 LEV 3 COMPOSITE			OMPOSITE	PM			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTR SYSTEMS							L		OBD S	BD STATUS		ENGINE DISPLACEMENT (L)			
1	2TWC, DFI, SFI, 2WR-HO2S, 2HO2S, 2TC, 2CAC								FULL		*				
*	*								PARTIAL		*	3.5			
*	* *								TIAL WITH		ALL MODELS				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION															
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATU			PECIAL FEATURES			
1	MFMXR0130NKE LE						V 2 PC				;	HCT			
					E	EMISSION CI	REDIT	r info	ORMATION		· · · · · ·				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N				N		
					NMOG	AND FLEET	AVE	RAG		TI	ON				
NMOG RAF						0-375		N) LDT (3751 LVW-8500 MDV (10,0			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*		1.10		* 0.058						0.065 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{9th}$ day of December 2020.

Allen Igons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			Γ	N	NMOG+NOx CO				NOx			нсно			РМ			
					(g/mi)	(g/mi) (g		(g/mi)	/mi)		(g/mi)		(mg/r			(g/mi)		
			ſ	CE	RT	STD	CER	т ѕт	D	CERT	STE	CERT		STD	CERT		STD	
FTP@5	0K	*		4	*	*	*	*		*	*	*		*	,	۲	*	
FTP@l	GASOLINE- P@UL TIER3 E10 PREM		E10	0.0	088 0	.125	0.7	2.	1	*	*	1		4		001	0.003	
50°F @	50°F @4K			ł	*	*	*	*		*	*	*		*				
									1	NMOG+NOx (g/mi)			CO (g/mi)					
					FU	EL TYF	<u>۲</u>			C	CERT)	CER	۲۲		STD	
HWFE	T @ 50k	ĸ				*					*		*					
HWFE	T @ UL	-		GAS	OLINE-	FIER3	E10 PREM		0	0.035		0.125						
20°F	@ 50K	c	OLD C	O E1	0 PREM	IUM G	ASOLIN	OLINE (TIER3)						6		10.0		
				SFTF	P EXHAU	JST EN	IISSION	I STAND	ARDS	SAND	CERTIFIC	CATION I	.EVE	LS				
							US06				SC03				COMPOSITE			
	FUEL	UEL TYPE		NMOG+NOx (g/mi)		CO PM (g/mi) (mg/mi)			NMOG+NOx (g/mi)		NN	NMOG+NOx (g/mi)		CO J/mi)	PM (mg/mi)			
		* CI		CERT *			*			k *								
@ 4K			STE	5	*		*				*		-					
				т	*		*		*		*	*		0.075	-).7	*	
@ UL	GASOLINE DUL TIER3 E1 PREM		IIO STD		*	*		* 6			*			0.077		1.2	*	
														0.130				
		W	HOLE	VEHI	CLE EV	APOR/	TIVE E	MISSION		NDAR		CERTIFIC		ON LEVE	LS			
						w	HOLE \	/EHICLE	EVA	PORAT	IVE TES	TING						
		/E	FUEL TYPE		YPE 3DHS (g/test) @ UL			2DH	2DHS (g/test) @ UL				RL (g/r	(g/mi) @ UL				
			·		CERT		STD	FEL C		RT	STD	FE	FEL		रा	STD		
MFMXR0130NKE			GASOLINE- TIER3 E10 PREM			13 ().50 * 0.		159	0.65	ł	*		0.00		0.05		
	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIV								E EMI	SSION	STAND	RDS AN	D CE	RTIFICA	TION	LEVE	LS	
									FUEL ONLY EVAP & CANISTER BLEED									
	EVAPORATIVE FAMILY										RIG TEST est) @ UL			BLEED CANISTER TEST (g/test) @ 4K				
		F	UEL T	YPE	CERT	STD	_ · · · · · · · · · ·		С	ERT	STD	CER		STD	CEF	RT	STD	
MFMXR0130NKE			ASOLI IER3 PREM	E10	0.009	0.20		*		*	*	*	* *		*		*	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD									
*	*	*	*									
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-od duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidiz	D#LVW; LDT3: LDT 6001-85 luty vehicle; MDV4: MDV 85 heavy-duty vehicle; ECS: e vehicle weight rating; LVW: I er ULEV; ZEV: zero-emissic AC: HC adsorbing catalyst; selective catalytic reduction zer; DPF: diesel particulate f	00#GVWR,3751-5750#ALVW; LI 01-10000#GVWR; MDV5: MDV mission control system; CERT: co oaded vehicle weight; ALVW: adj on vehicle; TZEV: transitional ZEV WU: warm-up catalyst; NAC: NO I-urea/ammonia; NH3OC: ammor ilter (active); GPF: PM filter for sp	nia oxidation catalyst; CTOX/PTOX:									

RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	FORD GT	PC	3.5	SA7	MFMXR0130NKE	1	\$