

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | | | TEST GRC | UP IN | FOR | MATION | | | | | |
|--|--|---------------|-------|----------|-------------------------|-------|--------------------------------------|--|------------|--|--|--|--|
| MODE YEAF | | TEST GROUP | | VEHIC | LE CLASS(E | S) | | FUEL CATEGORY | | | FUEL TYPE | | |
| 2021 | 2021 MBMXV01.5B36 PC | | | | | | | DEDICATED SINGLE FUEL VEHICLE | | | GASOLINE | | |
| USEFUL LIFE (miles) VEHICLE EMISSION | | | | | | | | TEGORY INTERIM / INTERMEDIATE IN-USE S | | | | | |
| EXH | I/ORVR | R EVAP | | FTP S | | | | SFTP FTP | | | SFTP | | |
| 15 | 50000 | 150000 | | LEV3 | SULEV30 LEV 3 COMPOSITE | | | | * | | PM | | |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS | | | | | | | | OBD S | BD STATUS | | ENGINE DISPLACEMENT (L) | | |
| 1 | WU-T | WC, TWC, WR-H | 02S, | HO2S, D | FI, TC, CA | C | | FULL | * | | Sec. A Sec. | | |
| * | | | * * | | | | Р | ARTIAL | * | the second second | 1.5 | | |
| * | * * | | | | | | | TIAL WITH FINES | ALL MODELS | $\frac{1}{2} \left[\frac{1}{2} \left$ | | | |
| | | E | /APOI | RATIVE & | REFUELING | (EVA | P/OR | VR) FAMIL | INFORMATIO | N | | | |
| EVA | P / OR | VR FAMILY | EVA | PORATIVE | STD CATE | GOR | Y EVAP EMISSION STD VEHICLE CLASS | | | - | SPECIAL FEATURES | | |
| 1 | MBMXRO | 0100F5X | LE | V 3 OPTI | ON2 WITH | FEL | | I | 2c | | * | | |
| | | | | I | EMISSION C | REDI | Γ INFO | RMATION | | 1 | | | |
| | NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY | | | | | | ZEV | EV NMOG CREDIT FOR DOR | | | OPTIONAL EXH. STD FOR WORK TRUCKS | | |
| | N N | | | | | | | | N | N | | | |
| | | | | NMOG | AND FLEE | Γ AVE | RAG | E INFORMA | TION | | | | |
| NMOG RAF | | | | | | 0-375 | | | | | NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) | | |
| * | * | 1.10 | | * | 0 | .058 | | | 0.065 | | * | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of February 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

BAYERISCHE MOTOREN WERKE AG Executive Order: A-008-0522 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

| | | | - | | | | | | | | | | | | | | | |
|--------------------------------|----------------------------|----------------------------|--------------------------|--------------------|------------|--------------|-------------------------------|--------------|---------------|--------------------|-----------------|--------------------------|---------------|-------------------|------------------------------|---|---------------|--|
| | | | NMOG+NOx (g/mi) | | | | | CO (g/mi) | | | NOx g/mi) | | HCHC (mg/m | | - | PM (g/mi) | | |
| | | | | CERT | г | STD | CER | T STC | | CERT | STD | CER | т | STD | CEF | RT | STD | |
| FTP@50 | ж | * | | * | | * | * | * | | * | * | * | | * | * | | * | |
| FTP@U | DUL GASOLINE- TIER3 E10 | | | 0.01 | 8 0 | .030 | 0.4 | 1.0 | | * | * | * | | 4 0.0 | | 01 | 0.003 | |
| 50°F@4K GASOLINE- TIER3 E10 | | | | 0.01 | 3 0 | .060 | 0.2 | 1.0 | | * | * | * - | | 8 | | | | |
| | | | | - | EU | EL TYPI | = | | 1. | 1 | MOG+NC | | CO (g/mi) | | | | | |
| | | | | | FUI | | - | | CERT | | STD | STD | | CERT | | STD | | |
| HWFET | @ 50k | < | | | | * | | | | * | | * | | | ere and Elabora | | | |
| HWFE | T @ UL | | | GAS | SOLIN | E-TIER | R3 E10 | | | 0 | 0.012 | | 0.030 | | e surge sour Station (See | n - Shi ya Ma Shi ya Hunan Qalaya Ta | | |
| 20°F (| @ 50K | C | COLD CC | E10 | REGU | LAR GA | SOLIN | E (TIER | .3) | | | | | 0.0 | 6 | | 10.0 | |
| | | | S | FTP E | EXHAL | JST EM | ISSION | STANDA | ARDS | AND | CERTIFIC | ATION LE | EVEL | .s | | | | |
| and the second | | | 行动的 | | US06 | | | | | SC03 | | | | | COMPOSITE | | | |
| | FUEL | TYPE | | NMOG+NOx (g/mi) | | | CO PM (g/mi) (mg/mi) | | | NMOG+NOx (g/mi) | | | | lOG+NOx (g/mi) | | :0 /mi) | PM (mg/mi) | |
| @ 4K | * | r | CERT | CERT | | * | | * | | * | | * | | | | | | |
| | | | STD | | * | | * | | | * | | * | | | | | | |
| | | GASOLINE- TIER3 E10 BIN | | | | | * | * 2 * 6 | | * | | * | 0.014 | | 0 | . 6 | * | |
| @ UL | | | | | | | * | | | | | * | | 0.077 | | .2 | * | |
| | | | | | | | | | | | | | 0.050 | | | | | |
| | | W | HOLE V | EHICL | E EV | APORA | TIVE E | MISSION | STAN | DAR | DS AND C | ERTIFIC | ATIO | N LEVE | LS | | | |
| | | | | | | WH | HOLE V | /EHICLE | EVAP | ORAT | IVE TEST | ING | | | | | | |
| | | RATIVE FUEL TYPE 3DHS | | | DHS (g | g/test) @ UL | | | 2DHS (g/test) | | @ UL | | RL (g/mi) @ | | ni) @ | ⊉ UL | | |
| | | | | CER | TS | TD | FEL | CEF | RT | STD | FEL | | CERT | | STD | | | |
| MBMXR0100F5X | | 5x | GASOLI LEV3 I PREN | E10 | 10 0.273 0 | | . 300 | 0.300 | 0.236 | | 0.300 | 0.300 | | 0.0 | .04 | | 0.05 | |
| 0 | RVR / | FUE | | | STER | BLEED | EVAP | | EMIS | SION | STANDA | |) CF | RTIFICA | TION | EVE | ELS. | |
| | | | | | <u></u> | | | | | | ONLY EVA | | | | | | | |
| EVAPORATIVE FAMILY | | /E | E ORVR (g/gallon) @ UL | | | | | 3D | | | IG TEST | 2DHS RIG T (g/test) @ | | TEST | ST BLEED C | | | |
| | | | | PEC | ERT | STD | | | | RT | STD | CERT | | STD | CERT | | STD | |
| MBMXR0100F5X | | 5 g | ASOLIN IER3 E | E- 0 | 0.04 | 0.20 | GASOLINE- LEV3 E10 PREM | | * | | * | * | | * | 0.009 | | 0.020 | |

| CALI AIR RESC | FORNIA DURCES BOARD | | BAYERISCHE OREN WERKE AG | | Executive Order: A-008-0522 ssenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4 |
|---|---|--|--|--|--|
| EFFECTI | /E LEAK DIAMETER | STAI | NDARD AND CER | TIFICATION L | EVEL (INCHES) |
| EVAPORATIVE FAMILY | | | CER | Г | STD |
| MBMXR0100F5X | MBMXR0100F5X-0 | 01 | 0.00 |) | 0.02 |
| 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/ii full/partial/partial with fines or prefix 2: parallel; (2) suffix: set device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss | duty vehicle; MDV4: MD 2 heavy-duty vehicle; EC vehicle weight rating; L' per ULEV; ZEV: zero-en IAC: HC adsorbing cata 3: selective catalytic redu izer; DPF: diesel particul 102S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection ndirect fuel injection; TC n-board diagnostic; DOF eries; a hyphen (-) betwee R coated DPF); CNG/LN E10: "10%" ethanol ("90 continuously variable tr ion; AMS: automated m V: plug-in hybrid electric | 0V 850 CS: em VW: loa nission lyst; V uction-u late filt ge/linea ensor; E on (belt C/SC: tu C: direc een aft G: com 0%"ga: ransmis anual- | 1-10000#GVWR; MI hission control system aded vehicle weight; vehicle; TZEV: trans /U: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas re c driven)/(electric driv urbo/super charger; 0 ct ozone reducing; Ho er treatment ECS inco npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectab selectable transmiss | DV5: MDV 10001 n; CERT: certifica ALVW: adjusted sitional ZEV; TW ; NAC: NOX ads DC: ammonia ox 1 filter for spark-i o sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon dicates multiple f atural gas; LPG: natic (with lockup le continuously v ion; OT: other tra | idation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi |

| | 2021 MODEL Y | EAR: VE | HICLE MO | ODELS INF | ORMATION | | |
|------|-------------------------------|-----------|------------|------------|-----------------------|------------|-----|
| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBD |
| MINI | MINI COOPER CONVERTIBLE | PC | 1.5 | AMS7,M6 | MBMXR0100F5X | 1 | \$ |
| MINI | MINI COOPER HARDTOP 2 DOOR | PC | 1.5 | AMS7,M6 | MBMXR0100F5X | 1 | \$ |
| MINI | MINI COOPER HARDTOP 4 DOOR | PC | 1.5 | AMS7,M6 | MBMXR0100F5X | 1 | \$ |