

FCA US LLC.

Executive Order: A-009-1537

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE		EST GROUP	VEHIC	HICLE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2021	MCRXV03.65P3 PC							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	. LIFE (miles)		VEH	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	TERM	MEDIATE IN-USE STD		
EXH	I/ORVR	EVAP			FTP SF			TP	FTP		SFTP		
15	50000	150000		LEV3	ULEV125 LEV 3 COMPC			MPOSITE	*		PM		
SPE	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1		2HO2S (2	2), 5	SFI, 2TWO	3			FULL	*				
*	*							ARTIAL	ALL MODELS		3.6		
*	*							TIAL WITH *		1			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	MCRXR0168PP0 LEV 3 OPTION2							F	PC	HCT			
				I	EMISSION CI	REDIT	r INF	ORMATION					
CREDIT FOR EXTENDED						T FOR NON-PZEV RO-EVAP NMOG CREDIT FOR I				OPTIONAL EXH. STD FOR WORK TRUCKS			
N N									N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	-1 NMOG/NMHC DC+1 DT (0-37)				0-375		N) LDT (3751 LVW-8500 MDV (10,001			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



FCA US LLC.

Executive Order: A-009-1537

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).


Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>13th</u> day of August 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division





ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																			
EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																			
	FUI	≣L TY	r a (CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
						NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		1	HCH (mg/i		PM (g/mi)		
				CER	т 📗	STD	CERT	r ST	D	CERT	STD	CER	CERT		CEF	₹T	STD		
FTP@5	OK	*		*		*	*	*		*	*	*		* *			*		
FTP@L	JL GASOLINE- LEV3 E10			0.09	26 0	125	0.83	2.	1	*	*	*	*		0.0008		0.003		
50°F @4	4K	K *				*	*	*		*	*	*	*						
				FUEL TYPE						NMOG+NOx (g/mi)				CO (g/mi					
						FUEL TIPE				CI	ERT	STD		CERT			STD		
HWFE	Г @ 50K					*					*								
HWFET @ UL				G	ASOLI	NE-LEV	V3 E10			0.0	0.0050 0.1		i						
20°F @ 50K			GA	GASOLINE-COLD CO LOW OCTANE										1.03 10.0			10.0		
			s	FTP	EXHAL			STAND	ARDS	AND C		CATION LI	EVEL						
				US06							SC03			COMPOSITE					
	FUEL TYF		YPE N				CO (g/mi)				G+NOx /mi)	CO (g/mi)		IOG+NO: (g/mi)		mi)	PM (mg/mi)		
@ 4K	K *		CERT		RT *		*				*	*							
		ST		*		*				*	*								
		GASOLINE- LEV3 E10 ST		T *		* 1		. 5	*		*	C	0.0763	0.	92	*			
@ UL					*		*	(6		*	*		0.077 4.2		. 2	*		
			BIN											0.120					
		WH	IOLE V	EHIC	LE EV							CERTIFIC	ATIC	N LEVE	LS				
 EVAPORATIVE		/E						IOLE VEHICLE EVAP			ORATIVE TESTING 2DHS (g/test) @ UL						(g/mi) @ UL		
FA	FAMILY		FUEL TYPE		3DHS (g/test) @			CE		STD	 		CERT		T STD				
MCRXR0168PP0		(1	SASOLI	DLINE- 0 1932			.300 FEL		0.2		0.300		0.300		00	0.05			
)RVR / F				 STFR	BLFF) FVΔP	ORATIVI	E EMIS	SSION	STAND	RDS AND) CF	 RTIFICA	TION I	FVF	ıs		
		<u> </u>	/								SSION STANDARDS AND CERTIFICATION LEVELS UEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY		· ·		VR (g/gallon) @ UL				L TYPE	30	3DHS RIG TE (g/test) @ U		2DHS	2DHS RIG (g/test) @		BLEE	BLEED CANISTER FEST (g/test) @ 4P			
		FL	FUEL TYPE C			STD	""	LITE	-	RT	STD	CERT		STD	CER		STD		
MCRXR0168PP0		GZ	SOLIN	F-		0.20	GASO	GASOLINE- LEV3 E10		*	*		*		0.009	\dashv	0.020		
MCRXR	0168PP		EV3 E	ιοΙς	0.028	0.20	LEV	3 E10		^	•	*		^ I	0.00	²⁰	0.020		



FCA US LLC.

Executive Order: A-009-1537

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MCRXR0168PP0	MCRXR0168PP0-LF1	*	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3; LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4; LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	MODEL VEH CLASS ENGINE (L) TRANS TYPE		EVAPORATIVE FAMILY	EXH ECS	OBD	
CHRYSLER	300	PC	3.6	A8	MCRXR0168PP0	1	P
CHRYSLER	300 AWD	PC	3.6	A8	MCRXR0168PP0	1	P
DODGE	CHALLENGER	PC	3.6	A8	MCRXR0168PP0	1	P
DODGE	CHALLENGER AWD	PC	3.6	8 A	MCRXR0168PP0	1	P
DODGE	CHARGER	PC	3.6	A8	MCRXR0168PP0	1	P
DODGE	CHARGER AWD	PC	3.6	A 8	MCRXR0168PP0	1	P