

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1075

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			-										
1405					TEST GRO	OUP II	NFOR	MATION					
MODE		EST GROUP		VEHICLE CLASS(ES)			FUEL C	CATEGORY		FUEL TYPE			
2021	L M	TYXT02.5P3M	-20	LDT2					ELECTRIC		GASOLINE		
	USEFU	L LIFE (miles)		VE	VEHICLE EMISSION CATEGOR				INTERIM / I	NTER	ERMEDIATE IN-USE STD		
EXI	I/ORVR	EVAP			FTP SFTP			TP	FTP		SFTP		
15	50000	150000)	LEV3	SULEV30 LEV 3 COMP			OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	E	ENGINE DISPLACEMENT		
1 SFI, EGR, EGRC, WR-HO2S, TWC(2), HO2S								FULL	ALL MODELS				
*	* *							ARTIAL	*		2.5		
*	* *							TIAL WITH	*				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
Þ	TYXR01	.30A82		LEV 3	OPTION2	PTION2			T2		HCT		
				ı	EMISSION CF	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NO ZERO-EVAP						ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N N					
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		O/NMHC RATIO	DC41 DT (D-275						IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0	.006	0	. 058			0.065		*		
_						-							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1075

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this _____ day of July 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-

TIER3 E10

0.018 0.20

MTYXR0130A82

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1075

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

		EVI	LALICT	FRAIC	201011	07444					11007	שוור	OLIVI	11 11	SAIIC	IN LE	VEL	.5		
		EXI	HAUST	EMIS	SION	STANE	ARDS AN	ID CE	RTIFIC	ATIO	N LEVE	LS (FTP, HV	VFE"	Γ, 50°F,	20°F)				
FU		EL TY		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP																
				NI	MOG+	NOx	T	СО			NOx		T	НСНО			DM			
							(g/m	i)	(g/mi)		1		(g/mi)		(mg/					PM /mi)
				CERT ST		STD	CERT	S	rD	CERT		TD	CER		STD	-	ERT	STD		
FTP@5	OK	*		*		*	*	١,	At	*		*	*		*	+	*	*		
FTP@UL GASOLINE- LEV3 E10			0.01	94	0.030	0.16	1.	. 0	*		*	*		4	+	*	0.003			
50°F @	4K	*		*	\neg	*	*	,		*	_	*	*		*	+-				
						NMOG+NOx (g						(a/mi)		CO (g			i\			
F					FU	JEL TY	YPE						STD			CERT		STD		
	T @ 50K			*							*		*							
HWFE	HWFET @ UL GA				ASOLI	SOLINE-LEV3 E10					.0087	0.030								
20°F	@ 50K	CC	OLD CO	E10	REG	ULAR G	ASOLINE (TIER3)						0.88			12.5				
			S	FTP	EXHA		IISSION S	TAND	ARDS	AND	CERTIF	ICA	TION LE	VEL	.S					
						US06					SC03				COMPOSITE					
FUEL T		YPE		NN	NMOG+NOx		CO			1	NMOG+NOx		CO	NMOG+NO				PM		
				(g/mi)		(g/mi)	(mg	g/mi)	(9			g/mi)		(g/mi) (g/mi)	(mg/mi)			
@ 4K	*	STE				*				*		*								
					*		*				*		*							
	63.60T T	ASOLINE- EV3 E10 STE		*		*	* *			*		*	0.0252		0.31		*			
@ UL					*		*		6		* * 0.077		0.077		4.2	*				
			BIN												0.040					
		WH	OLE V	EHICL	LE EV		TIVE EMI			-	The second secon	-		TIO	N LEVE	LS				
EVAD	DRATIVE				WHOLE VEHICLE EVAPO						DRATIVE TESTING									
	MILY	E FUEL TY		YPE 3DHS (g/			/test) @ UL			2DH	2DHS (g/test) @			@ UL		RL (g/mi) @ UL		UL		
					CEF	CERT STD		FEL	CERT		STD		FEL		CERT		STD			
MTYXR0130A82		GASOLINE- TIER3 E10 0.0740			40 0	.400 *		*	0.400		0	* 0.		0.05		0.05				
0	RVR / FL	JEL C	NLY /	CANI	STER	BLEED	EVAPOR	ATIVE	EMIS	SION	STAND	ARD	SAND	CER	RTIFICA	TION	LEVE	LS		
FUEL ONLY EVAP & CANISTER BLEED																				
EVAPORATIVE FAMILY		ORVR (g/gal		allon) @ UL		FUEL TYPE			DHS RIG TEST (g/test) @ UL			2DHS RIG T (g/test) @			BLEED CANIST TEST (g/test) @					
		FU	EL TYF	PE C	ERT	STD	CE		RT	STD		CERT	1	STD	CEF		STD			

GASOLINE-

LEV3 E10

*

*

*

0.0199

0.020



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1075

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MTYXR0130A82	MTYXR0130A82-001	*	0.02							
not applicable. My neural and My and All and A										

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD	
LEXUS	NX 300H AWD	LDT2	2.5	SCV6	MTYXR0130A82	1	F	