

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE		EST GROUP		VEHIC	EHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2021	MIN	ISXT02.5RPA		LI	DEDICA				SINGLE FUEL		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY INTERIM / INTERMEDIA							RMEDIATE IN-USE STD						
EXH	/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
15	0000	15000	C	LEV3	SULEV30	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS		ENGINE DISPLACEMENT		
1	TWC(2), HO2S, WR-HO2S, EGR, EGRC, DFI							FULL	ALL MODELS				
*			*				F	PARTIAL	*	-	2.5		
*	*							RTIAL WITH FINES	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAF	P / ORV	R FAMILY	EVA	PORATIVI	E STD CATEO	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
М	NSXR01	05PDA	LE	LEV 3 OPTION2 WITH FEL				LDT1			*		
М	NSXR01	05PEA	LF	LEV 3 OPTION2 WITH FEL				LDT2			*		
					EMISSION CR	REDIT	INFO	ORMATION					
CREDIT FOR EXTENDED					EDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N		N				N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF					-375							
1.00	*	1.10		*	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 1074 day of June 2020.

Allen Eyons, Chief Emissions Certification and Compliance Division



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0868 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUE	TYPE

	FU												
				S+NOx mi)		O mi)		Ox mi)		CHO g/mi)		PM /mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		SOLINE- V3 E10	0.015	0.030	0.2	1.0	*	*	*	4	0.001	0.003	
50°F @4K		SOLINE- V3 E10	0.018	0.060	0.2	1.0	*	*	*	8			
				FUEL TYP	E		NN	IOG+N	Ox (g/mi)	CO (g/mi)			
					L		CEI	RT	STD	CER	Т	STD	
HWFET @	HWFET @ 50K			*			*	*		*			
HWFET @	ET @ UL GASOLINE-LEV3 E10 0.007		07	0.030									
20°F@	50K	COLD C	0 E10 RE	GULAR GA	SOLINE	(TIER3)				0.4		10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	1		1	-					AND CENTIF	IOA HON L		3			
					US06				SC03			COMPOSITE			
FUEL TYP		PE		NM	OG+NO>	(CO	F	PM	NMOG+NO>	CO	NM	OG+NOx	CO	PM	
					(g/mi)	(g/mi)) (m	g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mg/mi)	
@ 4K	4K *		CERT		*	*			*	*					
			STD		*	*			*	*	+				
	@ UL GASOLINE- LEV3 E10		CERT		*	*		2	*	*	0.019		0.6	*	
@ UL			STD		*	*		6	*	*	0.077		4.2	*	
			BIN								0	.040			
		WH	OLE VE	HICL	E EVAP	ORATIVE E	MISSIO	N STAN	DARDS AND	CERTIFIC	ATIO	LEVELS			
						WHOLE	VEHICLE	EVAPO	RATIVE TES	STING					
	EVAPORATIVE FAMILY		UEL TYPE 3DHS			S (g/test) (@ UL		2DHS (g/test) @ UL			RL (g/mi) @ UL			
			[CERT	STD	FEL	CER	T STD	FEI	-	CERT		STD	
MNSXR	MNSXR0105PDA I		ASOLIN EV3 E		0.194	0.300	0.300	0.17	0 0.300	0.30	0.300 (C	.05	
MNSXR	0105PEA		ASOLIN LEV3 E:		0.194	0.400	0.400	0.17	0 0.400	0.40	00	0.000	0	.05	

A	CALI	FORI URCES B	NISSAN MOTOR COMPANY, LTD.			1	Executive Order: A-015-0868 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
FUEL ONLY EVAP & CANISTER BLEED												ELS		
EVAPORATIVE FAMILY		RVR (g/gallon) @ UL			3DHS RIG TYPE (g/test) @		IG TEST	TEST 2DHS		G TEST	BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYP		STD			CERT	STD	CERT		STD	CERT	STD		
MNSXR0105PDA	GASOLINE TIER3 E1	0.09	0.20	GASOLINE LEV3 E10		*	*	*		*	0.014	0.020		
MNSXR0105PEA	GASOLINE TIER3 E1	.0 0.09	0.20	GASOLINE- LEV3 E10		*	*	*		*	0.014	0.020		
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	FAMILY	LEAI	K FAMIL	Y		CERT			STD					
MNSXR0105	PDA	MNSXR0	105PDA-	-001 *				0.02						
MNSXR0105	PEA	MNSXR0	105PEA-	-001 *				0.02						
8500#ALVW; MDV: duty passenger veh emission limit; GVV ULEV: ultra LEV; S ADSTWC: adsorbir SCRC/SCR-N or S continuous/periodic heated/oxygen sen RDQS: reductant q EGRC: EGR cooler fuel injection; DFI/If full/partial/partial wi prefix 2: parallel; (2 device (ex. DPF-SC ethanol ("15%"gaso -automatic transmis automated manual	MNSXR0105PEA MNSXR0105PEA-001 * 0.02 *: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/S: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%"													

T

Γ

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

		1					
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MITSUBISHI MOTORS	OUTLANDER	LDT2	2.5	SCV8	MNSXR0105PEA	1	F
NISSAN	ROGUE AWD	LDT2	2.5	SCV8	MNSXR0105PEA	1	F
NISSAN	ROGUE AWD SV/SL/PLATINUM	LDT2	2.5	SCV8	MNSXR0105PEA	1	F
NISSAN	ROGUE FWD	LDT1	2.5	SCV8	MNSXR0105PDA	1	F
NISSAN	ROGUE FWD SV/SL/PLATINUM	LDT1	2.5	SCV8	MNSXR0105PDA	1	F
NISSAN	ROGUE FWD SV/SL/PLATINUM	LDT2	2.5	SCV8	MNSXR0105PEA	1	F