

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE YEAF		EST GROUP	VEHICLE CLASS(ES)					FUEL C	ATEGORY		FUEL TYPE		
2021	L MI	MXV05.0VKN			PC		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							ATE	GORY	INTERIM / IN	TERN	ERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP				FTP FTP			SFTP		
15	50000	150000		LEV3	ULEV125 LEV 3 CON			OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	ENGINE DISPLACEMENT			
1		2TWC (2), DFI,	SFI,2	WR-HO2S	,2HO2S			FULL	ALL MODELS				
*			*				P	PARTIAL *			5.0		
*							ARTIAL WITH * *			1			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	AP / OR	/R FAMILY	EVAI	PORATIVE	E STD CATE	GORY	Y EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES		
1	MFMXR0	125NDA		L	EV 2			E	PC		HCT		
				E	EMISSION CI	REDIT	INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						PZEV NMOG CREDIT FOR DOR				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEE	AVE	RAGE	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		CHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37 (g/mi)									
*	*	1.10		*	0.058 0.065						*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{900}$ day of December 2020.

Allen/Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx CO (g/mi) (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)				
			CERT	STD CERT STD		CERT	STD	STD CE		STD	CE	RT	STD	
FTP@50K	(*		*	*	*	*	*	*		*	*	* *		*
FTP@UL	GASOLINE- TIER3 E10		0.062	0.125	1.2	2.1	*	*		1	4	0.0	02	0.003
50°F @4K		*	*	*	*	*	*	*		*	*			
								NMOG+NOx (g/mi)			CO (g/mi)			
					FUEL TYPE					STD	CER	Т		STD
HWFET @) 50K	K *						r		*				
HWFET @ UI		GASOLINE-TIER3 E10)39		0.125				
20°F @ 50K		COLD C	CO E10 RE	GULAR GA					3.4	1		10.0		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFTF	PEXHAL	JST EM	ISSION	STAND	ARDS	AND	CERTIFIC	ATION LE	VELS				
					l	JS06				SC03			CO	MPOSIT	E	
	FUEL TYPE			NMOG+NOx		CO PN		М	NMC)G+NOx	со	NMOG+NOx		(CO	PM	
				(g/mi)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/	mi)	(g/mi) (mg/mi)	
@ 4K	*	СІ	ERT	*		*				*	*					
-		S	STD			*			*		*					
		CI	ERT	*		*	* 1			*	*	0.0	087	1.1	*	
@ UL	GASOLIN TIER3 E		STD	*		*	* 6			*	*	0.077		.077 4.2		
		E	BIN									0.110				
		WHOL	E VEHI	CLE EV	APORA	TIVE EI	MISSION	STAN	DAR	DS AND C	CERTIFICA		LEVEL	_S		
					W	HOLE V	EHICLE	EVAPO	ORA	TIVE TEST	ING					
	ORATIVE	FUEL TYPE		: 3	3DHS (g/		g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL			
					CERT S1		FEL	CEF	۲۲	STD	FEL		CER	T	STD	
MFMXR0125NDA		TIE	OLINE- R3 E10 PREM	E10 0.27		0.50 *		*		0.65	*		0.000		0.05	
C	DRVR / FUI	EL ONI	LY/CA	NISTER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERT	IFICAT	TION LE	/ELS	
								FU	EL C	NLY EVA	P & CANI	STER E	BLEED)		
	EVAPORATIVE FAMILY		ORVR (g/gallon) @ UL			FUEL TYPE			OHS RIG TEST g/test) @ UL		2DHS I (g/tes	RIG TE st) @ U			CANISTER test) @ 4K	
		FUEL	TYPE	CERT	STD			CEI	RT	STD	CERT	ST	D	CERT	STD	
MFMXR0125NDA		TIE	LINE - ER 2 EADED	0.038	0.20		* ;			*	*	*	,	*	*	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
*	*	*	*						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	MUSTANG	PC	5.0	M6, SA10	MFMXR0125NDA	1	F
FORD	MUSTANG CONVERTIBLE	PC	5.0	M6, SA10	MFMXR0125NDA	1	F
FORD	MUSTANG MACH 1	PC	5.0	M6, SA10	MFMXR0125NDA	1	F