

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1072

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE		ST GROUP	VEHICI	LE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2021		YXV05.0M5A			PC				SINGLE FUEL HICLE	GASOLINE			
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATE	GORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP SFT			TP	FTP		SFTP			
15	50000	15000)	LEV3	ULEV70 LEV 3 COMP			MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTRO SYSTEMS						L		OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1	DF	, SFI, 2WR	-но2	S, 2TWC(2), 2HO2S			FULL	ALL MODELS				
*	*							ARTIAL	*		5.0		
*	* * PARTIAL WITH * FINES												
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO								SSION STD E CLASS	SF	SPECIAL FEATURES		
1	MTYXR0180A72 LEV				3 OPTION2			PC			HCT		
					MISSION CI	REDIT	INFO	RMATION					
CDEDIT FOR EVTENDED					EDIT FOR NON-PZEV ZERO-EVAP			NMOG C	REDIT FOR DOI)	OPTIONAL EXH. STD FOR WORK TRUCKS		
N						N			N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	OG CH4 NMOG/NMHC HCHO/NMHC			PC+LDT (NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)			+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m					
*	*	1.10 0.012 0.058							0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1072 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance]. 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 25th day of March 2020.

Allen yons, Chief

Emissions Certification and Compliance Division



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1072 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

		EXH										(FTP, HW	-		_		
	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running los ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: n 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP											ty ss;					
			NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)			HCH (mg/n			PM (g/mi)		
				CERT	ST	D	CERT	ST	D	CERT	STD	CER	Т	STD CER		RT	STD
FTP@5	OK	*		*	*		*	*		*	*	*	* *		,	t I	*
FTP@U	L TIE	OLIN R3 E PREM		0.0222	0.0	70	0.08	1.	7	*	*	*		4	0.0003		0.003
50°F @4	4K LE	OLIN V3 E: PREM	10	0.029	0.1	40	0.18	1.	7	*	*	*		16			
				EUEL TVDE						NMOG+NOx (g/mi)				CO (g/mi)			
				FUEL TYPE					CERT STD		CERT		STD				
HWFET @ 50K				*					* *								
HWFET @ UL				GASOLINE-TIER3 E10 PREM					0.0022 0.070								
20°F @ 50K COLD		OLD C	CO E10 PREMIUM GASOLINE (TIER3)					R3)					1.4	7	:	10.0	
				SFTP E	KHAUST	EM	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	.S			
						Ĺ	US06				SC03	}		COMPOSITE			
	FUEL 1	YPE		NMOG+NOx (g/mi)			CO (g/mi)	PM (mg/mi)			G+NOx /mi)	CO (g/mi)	1	MOG+NOx (g/mi)		CO g/mi)	PM (mg/mi)
@ 4K		* C		CERT			*			*		*					
W 4K				*		+	*			*		*					
		ASOLINE- IER3 E10 S PREM E		₹T *			* 0.5		. 5	*		*	0	.0132	0	.53	*
@ UL	TIER3				*	* 6 * * 0		0.077 4.		4.2	*						
				1										0.080			
		WI	IOLE	VEHICL	E EVAP	ORA	TIVE E	MISSION	N STAI	NDARE	S AND	CERTIFIC	ATIO	N LEVE	LS		
	ORATIV	1 1-111-1					WHOLE VEHICLE EVAP				ORATIVE TESTING 2DHS (g/test) @ UL			RL (g/mi) @ UL			UL
F.P	MILY				CERT		STD	FEL			STD	FEI	L	CEF	RT	STD	
		-	GASOLINE-				-			-						<u> </u>	

0.300

0.007

0.05

0.1919 0.300

TIER3 E10 PREM

MTYXR0180A72



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1072

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
		FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g	ORVR (g/gallon) @ UL			FUEL TYPE		IG TEST) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	CERT STD		STD	
MTYXR0180A72	GASOLINE- TIER3 E10 PREM	1	0.20	GASOLINE- LEV3 E10 PREM		*	*	*	*	0.0067	0.020	
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY LEAK FAM			K FAMII	LY		CERT			STD			
MTYXR0180A72 MTYXR0180A72				-001 *					0.02			

to not applicable: #: pounds: UL; useful life; PC; passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit: GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV: ZEV: zero-emission vehicle: TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3; selective catalytic reduction-urea/ammonia; NH3OC; ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation: HP/LP EGR: High/Low Pressure EGR: EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION													
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD						
LEXUS	LC 500	PC	5.0	SA10	MTYXR0180A72	1	F						
LEXUS	LC 500 CONVERTIBLE	PC	5.0	SA10	MTYXR0180A72	1	F						