

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	DUP II	NFOR	MATION				9000 100 9 10 10 10 10 10 10 10 10 10 10 10 10 10		
MODI YEA	I T	EST GROUP		VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE			
202	1 M1	NSXVO3.0NHA		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSIO								SION CATEGORY INTERIM / INTERMED						
EX	H/ORVR	EVAP		FTP S				FTP FTP			SFTP			
1	50000	15000	0	LEV3	ULEV125 LEV 3 COMPOSI			OMPOSITE	re *			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS		ENGINE DISPLACEN			
1	2TWC (	2), 2HO2S, 2	, 2CAC, 2T	C		FULL	*		1					
*					P	ARTIAL ALL MODELS			3.0					
*					PAR	TIAL WITH	* 11							
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	AP / ORV	R FAMILY	E STD CATE	GORY	EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES					
1	MNSXR01	.59MCB	LE	V 3 OPTI	ION2 WITH I	FEL		P	C		*			
				I	EMISSION CH	REDIT	INFO	RMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N					
				NMOG	AND FLEET	AVE	RAGE	INFORMA	ΓΙΟΝ					
NMOG RAF	NBACIG/NBAHE				NMOG+NOX FLEET S PC+LDT (0-3750 LVV (g/mi)						MDV (10,001-14,000			
*	*	1.10		*	0	.058			0.065			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 3th day of July 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0871 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT
------------

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					9+NOx mi)	1	CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		Pl (g/r		
			Γ	CERT	STD	CERT	STD	CERT	STD	CER	T STI	5	CERT	STD	
FTP@5	OK	*		*	*	*	*	*	*	*	*	* *		*	
FTP@U		GASOLINE- LEV3 E10 PREM		0.046	0.125	0.5	2.1	*	* *		4		0.001	0.003	
50°F @4		ASOLIN EV3 E PREM	10	0.081	0.250	0.2	2.1	*	*	*	16				
	FUEL TYPE						NA	NMOG+NOx (g/mi)					CO (g/mi)		
					FUELIY	PE		CE	CERT STD		C	CERT		STD	
HWFET @ 50K				*			1	,	*						
HWFE	T @ UL	-		GASOLIN	IE-LEV3	E10 PREM	1	0.0	18	0.125	5				
20°F (	20°F@50K C		DLD CC	E10 PF	EMIUM	GASOLINE	(TIER3)					0.6		L0.0	
			S	FTP EXH	AUST E	MISSION S	TANDARD	S AND CE	RTIFIC	ATION LI	EVELS				
						US06			SC03	3	C		MPOSITE		
	FUEL	TYPE		NMOG (g/i		CO (g/mi)	PM (mg/mi)	NMOG (g/r		CO (g/mi)	NMOG+I (g/mi		CO (g/mi)	PM (mg/mi)	
@ 4K	1	ł	CERT			*		*		*					

@ 4h	~	L											
					*	*			*	*			
	@ UL GASOLINE- @ UL LEV3 E10 PREM		CERT	*		*		4	*	*	0.061	0.6	*
@ UL	QUL LEV3 E10		STD	*		*		6	*	*	0.077	4.2	*
			BIN								0.110		
		WHO	DLE VE	HICL	E EVAPO	ORATIVE E	MISSION	I STANDA	RDS AND C	ERTIFICA	TION LEVELS		
						WHOLE	/EHICLE	EVAPOR	ATIVE TEST	TING			
EVAPORATIVE FAMILY F		FUEL TYPE		3DHS (g/test) @ UL			2	DHS (g/test)	@ UL	RL (	RL (g/mi) @ UL		
					CERT	STD	FEL	CERT	STD	FEL	CERT		STD
MNSXR	0159MCB			10	0.233	0.300	0.300	0.211	0.300	0.300	0.000		0.05

A	CALI	FORN URCES B	<b>VIA</b> OARD	NISSAN MOTOR COMPANY, LTD.			1	Executive Order: A-015-0871 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
ORVR / FUI	EL ONLY /	CANISTER	BLEED	EVAPO	RATIVE	EMISSION	STANDA	RDS A	ND CERTIFIC		FLS			
				EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL	TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 41				
	FUEL TY	PE CERT	E CERT STD			CERT STD		CER	1	STD CERT				
MNSXR0159MCB	GASOLIN TIER3 E PREM		0.20	GASOL LEV3 PRE	E10	*	*	*	*	0.014	STD 0.020			
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)														
EVAPORATIVE		LEAI	LY CERT				STD							
MNSXR0159	MCB	MNSXR0	159MCB-	-001 *					0.02					
*: not applicable; # LDT<6000#GVWR 8500#ALVW; MDV duty passenger vel emission limit; GVV ULEV: ultra LEV; S ADSTWC: adsorbin SCRC/SCR-N or S continuous/periodid heated/oxygen sen RDQS: reductant q EGRC: EGR coolei fuel injection; DFI/I full/partial/partial wi prefix 2: parallel; (2 device (ex. DPF-SC ethanol ("15%"gasc -automatic transmis automated manual EAER: equivalent d	,3751-575( : medium-o hicle; HDV: WR: gross v ULEV: sup ng TWC; H. CRC-NH3: c trap oxidiz sor; WR-H uality sens r; AIR/AIRE F1: direct/in ith fines on c) suffix: sen CRC: SCR bline) fuel; I ssion; CV: o transmissio	D#LVW; LDT luty vehicle; heavy-duty vehicle weig er ULEV; ZE AC: HC ads selective ca zer; DPF: die O2S or AFS or; NH3S: a secondary direct fuel in -board diagr ries; a hyphe coated DPF E10: "10%" of continuously on; AMS: au	3: LDT 6 MDV4: N vehicle; ht rating; CV: zero- orbing ca atalytic re esel parti : wide rat mmonia air injec jection; T nostic; DC en (-) bet ); CNG/L ethanol (' variable tomated	001-850 ADV 850 ECS: em LVW: los emission atalyst; W duction-u culate filt nge/linea sensor; E tion (belt FC/SC: tu DR: direc ween afte NG: com '90%"gas transmis manual-s	0#GVW 1-10000 hission c aded ve vehicle /U: warr urea/am ter (activ tr/heated EGR: ex driven), urbo/sup to zone er treatm pressed soline) fi ssion; Si sselectab	R,3751-575 b#GVWR; M control syste hicle weight ; TZEV: trar n-up catalys monia; NH3 ve); GPF: P d air-fuel rat haust gas ro ((electric dri ber charger; reducing; F nent ECS in d/liquefied n uel; A: autor CV: selectal ble transmiss	0#ALVW; I IDV5: MDV m; CERT: t; ALVW: ac stitional ZE st; NAC: NO BOC: ammo M filter for cosensor; ecirculation ven); PAIR CAC: char ICT: hydroo dicates mu atural gas; matic (with oble continu sion; OT: of	LDT4: I ( 1000 certifica djusted V; TW Dx ads onia ox spark-ie NOXS: a; HP/L : pulse rge air carbon ultiple fi LPG: I lockup ously v ther tra	LDT 6001-8500 I-14000#GVWI ation; STD: sta LVW; LEV: lov C/OC: 3-way/o orption catalys idation catalys gnited engine; NOx sensor; F P EGR: High/L d AIR; SFI/MFI cooler; FFH: fu trap; BCAN: bl unctionalities o iquefied petrol- ); M: manual tr ariable transm nsmission; AE	#GVWR,57 R; MDPV: n ndard; FEL v emission xidizing cat ; SCR-U or t; CTOX/PT HO2S/O2S PMS: PM se ow Pressur : sequential el fired hea eed carbon f the after tr eum gas; E ansmission ssion; AM: R: all-electr	751- nedium- : family vehicle; alyst; OX: : ensor; re EGR; l/multiport ter; F/P/\$: canister; reatment 85: "85%" ; SA: semi ic range;			

EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
INFINITI	Q50	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q50 AWD	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q50 AWD RED SPORT	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q50 RED SPORT	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q60	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q60 AWD	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q60 AWD RED SPORT	PC	3.0	SA7	MNSXR0159MCB	1	P
INFINITI	Q60 RED SPORT	PC	3.0	SA7	MNSXR0159MCB	1	P