

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE YEAF	- I T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
2021	. <u>M</u>	NSXV01.6RNA			PC		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								GORY	IEDIATE IN-USE STD				
EXH	I/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
15	50000	150000	)	LEV3	SULEV30	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	BD STATUS		ENGINE DISPLACEMENT (L)		
1	TWC(2), HO2S, WR-HO2S, SFI							FULL	*				
*	*							PARTIAL	1.6				
*			*				PAR	RTIAL WITH *			1		
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							Y EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	MNSXR0	087PCA	LE	V 3 OPTI	CON2 WITH	FEL		E	PC		*		
				I	EMISSION CI	REDIT	r info	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY										OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEE	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		IO/NMHC RATIO	NMOG+NO PC+LDT ( (g								
*	*	1.10		*	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### **BE IT FURTHER RESOLVED:**

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-015-0872 dated July 24, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>2nd</u> day of November 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx CO (g/mi) (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PN (g/m			
			CERT	STD	CERT	STD	CERT	STD	CERT	- STD	CE	RT	STD
FTP@50K	*		*	*	*	*	*	*	*	*		*	*
FTP@UL	GASOLINE- LEV3 E10		0.017	0.030	0.4	1.0	*	*	*	4	0.0	001	0.003
50°F @4K		*	*	*	*	*	*	*	*	*			
			NN	NMOG+NOx (g/mi)			CO (g/mi)						
				FUEL TYP	E		CE	RT	STD	С	ERT		STD
HWFET @	) 50K	К *						r	*				
HWFET (	@ UL	L GASOLINE-LEV3 E10						005	0.030				
20°F @ 50K		COLD C	CO E10 RE	GULAR GA	ASOLINE				0	.7		10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SET	PEXHA	UST	EMIS	SSION	STANDA	ARDS	AND	CERTIFIC	ATION LE	=VEL	S			
				US06 SC03							C	OMP	OSITE				
	FUEL TY	L TYPE		NMOG+NOx			со		M NN		)G+NOx	CO NN		NMOG+NOx		СО	PM
				(g/mi)		(	(g/mi) (mg/		/mi)	(g/mi)		(g/mi)	) (g/mi)			(g/mi)	(mg/mi)
@ 4K *		С	CERT		*		*				*	*					
			STD	*			*				*	*					
		С	I SIN I		*		* 2		!	*		*	0.013		3 1.9		*
@ UL	@ UL GASOLIN				*		* 6		5		*	*	* 0			4.2	*
			BIN										0.040				
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																
						WH	OLE V	<b>EHICLE</b>	EVAP	ORAT	IVE TEST	ſING					
	ORATIVE	FUEL TY		E	3DHS (g/		(g/test) @ UL			2DF	IS (g/test)	@ UL		F	RL (g	/mi) @	UL
					CERT S		٢D	FEL	CEF	RT	STD	FEL	•	CE	RT		STD
MNSXF	MNSXR0087PCA		SOLINE V3 E10	10	233	0.3	300 0.300 0.		0.1	82	0.300	0.300		0.000		0.05	
<b>(</b>	DRVR / FUE	EL ON	ILY / CA	NISTE	R BLE	ED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	) CEF	RTIFICA		I LEVE	ELS
									FL	JEL C	NLY EVA	P & CANI	STEF	R BLEE	D		
	EVAPORATIVE FAMILY		ORVR (g/gallon) @ UL			· [	FUEL TYPE			OHS RIG TEST g/test) @ UL		2DHS RIG <sup>-</sup> (g/test) @					ANISTER est) @ 4K
		FUEL	L TYPE	CERT	ST	D			CE	RT	STD	CERT		STD	CE	RT	STD
MNSXF	R0087PCA		DLINE- R3 E10	0.03	0.:	20		OLINE- 3 E10	*		*	*		*	0.0	010	0.020



NISSAN MOTOR COMPANY, LTD.

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
LEAK FAMILY	CERT	STD								
MNSXR0087PCA-001	*	0.02								
	LEAK FAMILY	LEAK FAMILY CERT								

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	KICKS	PC	1.6	CV1	MNSXR0087PCA	1	P
NISSAN	VERSA	PC	1.6	CV1,M5	MNSXR0087PCA	1	P