

Executive Order: A-015-0881

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD	I T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
202	1 MN	SXV02.5RPB		PC DEDICATED SINGLE FUEL VEHICLE					GASOLINE				
	USEFUL	LIFE (miles)		VEH	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	NTERMEDIATE IN-USE STD			
EX	H/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
1	50000	150000		LEV3	SULEV30	LEV	3 C	OMPOSITE	*		PM		
SP	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS					OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)				
1	D	FI,WR-HO2S,H	02S,	TWC (2) ,E	GR,EGRC			FULL	*				
*			*				F	ARTIAL	TIAL ALL MODELS		2.5		
*	* *						PAF	TIAL WITH	*				
•		E\	/APC	RATIVE &	REFUELING	(EVA	P/OF	VR) FAMILY	/ INFORMATIO	v			
EV	AP / ORV	R FAMILY	EVA	APORATIVE	STD CATE	GORY	Y EVAP EMISSION STD VEHICLE CLASS			SF	PECIAL FEATURES		
	MNSXR01	.14PCB	L	EV 3 OPTI	ON2 WITH	FEL		PC			*		
				I	EMISSION C	REDIT	INF	ORMATION					
	REDIT FO	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG	INFORMA	TION				
NMOG RAF	NMOG/NMHC PC+1 DT /0-37/			0-375)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10		*	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-015-0881

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this ____21 st __ day of August 2020.

for Allen Lyons, Chief

Kunhely Pryor

Emissions Certification and Compliance Division

Executive Order: A-015-0881

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP. HWFET, 50°F, 20°F)

· · · · · · · · · · · · · · · · · · ·
CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon
monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity

adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

			G+NOx mi)		O mi)		Ox mi)		HCHO (mg/mi)		PM /mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	*	*	*	*	*	*	*	*	*	*	*	
	CASOLINE -											

FTP@UL GASOLINE-TIER3 E10 0.015 0.030 0.2 1.0 * * * 4 0.002 0.003 50°F@4K * * * * * * * * *

	FUEL TYPE	NMOG+N	Ox (g/mi)	co (g/mi)
	FUELTIFE	CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-TIER3 E10	0.006	0.030		
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			0.3	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	*	*	*	0.017	0.3	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	*	*	*	0.077	4.2	*
		BIN						0.040		
		CERT	*	*	2	*	*	*	*	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	6	*	*	*	*	*
		BIN						*		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \						
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (@ UL	2DI	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
MNSXR0114PCB	GASOLINE- LEV3 E10	0.146	0.300	0.300	0.236	0.300	0.300	0.000	0.05



Executive Order: A-015-0881

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
			FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE			IG TEST) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
MNSXR0114PCB	SXR0114PCB GASOLINE- TIER3 E10 0.03 0		0.20	GASOLINE- LEV3 E10		* *		*	*	0.011	0.020		
E	FFECTIVE	LEAK D	IAMET	ER STA	NDARI	D AND CE	RTIFICA	TION L	EVEL (INCH	IES)			
EVAPORATIVE FAMILY LEAK FAMIL			_Y CERT				STD						
MNSXR0114PCB MNSXR0114PCB			s-001 *					0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave, Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	ALTIMA	PC	2.5	CV1	MNSXR0114PCB	1	P
NISSAN	ALTIMA AWD	PC	2.5	CV1	MNSXR0114PCB	1	P
NISSAN	ALTIMA AWD SR/PLATINUM	PC	2.5	CV1	MNSXR0114PCB	1	P
NISSAN	ALTIMA SR	PC	2.5	CV1	MNSXR0114PCB	1	P
NISSAN	ALTIMA SV/SL	PC	2.5	CV1	MNSXR0114PCB	1	P