

CUMMINS INC.

Executive Order: A-021-0731

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	VFORM	MATION					
MOD		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	1 M	CEXD06.78WV	MDV5					SINGLE FUEL HICLE		DIESEL			
USEFUL LIFE (miles)				VEHICLE EMISSION CATEGOR				ORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP		SF	ГР	FTP		SFTP		
150000 *				LEV3	ULEV270 (HOT143 (LA92), FTP TEST			35 UC SC03,	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD STATUS			ENGINE DISPLACEMENT (L)			
1	TC, CAC, DFI, EGR, EGRC, OC, DPF, NH3OC, RDQS, NOXS(2), PMS							FULL	*				
*	*							PARTIAL *			6.7		
*	* *							RTIAL WITH ALL MODELS					
'	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVAP / ORVR FAMILY EVAPORATIVE STD CA						GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	*	,		*				*		*			
		•		1	EMISSION CI	REDIT	INFO	RMATION	•				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					MOG CREDIT FOR NON-PZEV ZERO-EVAP				REDIT FOR DO		OPTIONAL EXH. STD FOR WORK TRUCKS		
N N									N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMH0 RATIO					500 G\		MOG+NOX FLEET STD DV (8501-10000 GVWR (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	* * *						*			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



CUMMINS INC.

Executive Order: A-021-0731

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have four deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$75 per vehicle for the third through fourth deficiencies for vehicles in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board (CARB) reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2021 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall also be subject to enhanced manufacturer in-use verification testing requirements as described in the CARB letter CLC-2020-065.


Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 13th day of November 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division





ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																				
EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																				
	FUEL TYPE			m a O	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
						IC+NC g/mi)	Эx			CO /mi)		NOx (g/mi)		HCH (mg/				M mi)		
				CERT	ERT STD		CER	ERT STD		CERT	CERT STD		CERT		TD CE		STD			
	11 @301		*		*		*	*	4	,	*	*	*		*	*		*		
FTP@l		DIESEL-EPA		PA (2156	5 0.	. 270	0.18	3 4.	2	*	*	*		6	0.0	006	0.010		
50°F @	4K	*			*		*	*	4		*	*			*					
					FUEL TYPE						NMHC+NOx (g/m			•) (g/mi)			
											CE		STD CEI		₹T		STD			
HWFE	Г @ 50	K					*				*		*	*						
HWFE	T @ UI	L			DIESEL-EPA						0.0119 0			70	0					
20°F	@ 50K						*								*		*			
	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																			
					US06					SC03					COMPOSITE					
	FUEL TY		YPE			IC+NC	Ox	СО				NMHC+NOx			NMHC+NO		CO	PM		
					(!	(g/mi)		(g/mi) (mg/		g/mi)	(g/mi)		(g/mi)	_	(g/mi) (J/mi)	(mg/mi)		
@ 4K		* ST		CERT		*		*			*		*							
				STD		*		*				*								
		IESEL-EPA ST		CERT		*		*	*			*		_	0.0970	_	.07	1.0		
@ UL	DIESE			STD		*		*		*	,	*	*	+	0.550	- '	5.0	7		
			NA// 1/	BIN		- F\/A	DOD A	TIV/E E	MISSISI	LOTA	NDARR	S AND C	COTIC	CATIC		*				
		<u>`</u>	VV H (JLE V	ENICL	EVA					PORATI			CATIC	ON LEVE	LO				
	EVAPORATIV		EllEl		/PE	3DHS (g/test) @ U				LVA		(g/test)			RL (g/mi) @ UL			UL		
	MILY				ŀ	CERT S		STD	FEL	CE	RT STD		FEL		CERT			STD		
	*		*			*			*	+	*			* ,						
	RVR /	FUE	EL O	NLY /	CANIS	TER E	BLEED	EVAP	ORATIV	E EMI	SSION S	TANDA	RDS A	ND CE	RTIFICA	TION	LEVE	ELS		
										F	UEL ON	LY EVA	P & CA	NISTE	R BLEE	D				
1	EVAPORATIVE FAMILY		ORVR		(g/gallon) @ UL		UL	FUE	L TYPE			HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @				ED CANISTER T (g/test) @ 4K		
		F		EL TYPE C		RT STD				_	ERT			т	STD CE			STD		
	*	*		*		* *			*		* *		*			*		*		
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)																				
EVAF	EVAPORATIVE FAMILY LEAK FAMILY							CERT					STD							
*					*					*					*					



CUMMINS INC.

Executive Order: A-021-0731

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW: MDV: medium-duty vehicle: MDV4: MDV 8501-10000#GVWR: MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; JLEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE Family	EXH ECS	OBD
RAM	RAM 3500 4X2	MDV5	6.7	A6	*	1	\$
RAM	RAM 3500 4X4	MDV5	6.7	A6	*	1	\$