

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	IFOR	MATION						
MODE YEAR	- 1	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE			
2021	MT	KXV02.5FFA		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
l	USEFUL	. LIFE (miles)		VEF	ICLE EMISS		ATE	GORY	INTERIM / IN	TERMEDIATE IN-USE STD				
EXH	/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP			
15	0000	15000)	LEV3	ULEV125 LEV 3 C			MPOSITE	*		PM			
SPE	CIAL FE	ATURES & EX	HAUS		ON CONTRO	L		OBD S	TATUS		ENGINE DISPLACEMENT (L)			
1 T	WC, WU-:	IWC, HO2S, WR-	, DFI , CAC	,TC,EGR, E	GRC		FULL	*						
*			*				Р	ARTIAL	ALL MODELS		2.5			
*			*					RTIAL WITH *						
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							,		SSION STD E CLASS	SPECIAL FEATURES				
м	TKXR00	98ADP	LE	V 3 OPTI	ON2 WITH FEL			PC			НСТ			
м	TKXR01	20GAK		L	EV 2			PC			*			
				I	EMISSION C	REDIT	INFO	RMATION						
	EDIT FC	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR N ZERO-EVAP	ON-P				R OPTIONAL EXH. STD FOR WORK TRUCKS				
		N			N				N	N				
				NMOG	AND FLEE	T AVE	RAG	INFORMA	TION					
NMOG RAF	G CH4 FTP RAF NMOG/NMHC RATIO RATIO (g/mi)			0-375										
*	*	1.10		*	0	.058			0.065		*			
Soo th	o Attach	mont for Vohi		adole Ev	norativo Ea	mily	Engir	Displace	mont Emissio		ontrol Systems Phase-			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-016-0474 dated July 28, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>9th</u> day of October 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/i		CO (g/mi)			Ox mi)		:HO J/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD CER		STD	CER	T STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		SOLINE- V3 E10	0.064	0.125	0.8	2.1	*	*	*	4	0.00	2 0.003	
50°F @4K		SOLINE- V3 E10	0.031	0.250	0.3	2.1	*	*	*	16			
					-		NN	log+N	Ox (g/mi)		CO (g/mi)		
			FUEL TYPE						STD	CER	Т	STD	
HWFET @) 50K		*						· *				
HWFET @ UL			GASO	LINE-LEV	3 E10		0.0	38 0.125					
20°F @ 50K		COLD	CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.6	5	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06					SC03				COMPOSITE			
	FUEL TYP	PE		NM	OG+NOx	co l	P	M	NMC)G+NOx	СО	NMO	OG+NOx	CO		РМ
				((g/mi)	(g/mi)	(mg	j/mi)	(9	g/mi)	(g/mi)	(g/mi)	(g/m	i)	(mg/mi)
@ 4K	*		CERT		*	* *				* *						
0			STD		*	*			*		*					
	GASOLINE- LEV3 E10		CERT	RT *		*	:	3		*	*	0.057		1.0	0	*
@ UL			STD	*		*		6		*	*	0.077		4.2		*
			BIN									C	0.120			
	1	WH	OLE VE	HICL	E EVAP	ORATIVE E	MISSION		DAR	DS AND C	ERTIFIC	ΑΤΙΟ	N LEVELS	5		
						WHOLE \	/EHICLE	EVAPO	RAT	TIVE TEST	ING					
	ORATIVE	F	FUEL TYPE		3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL			JL
FAMILI					CERT	STD	FEL	CER	Т	STD	FEL	FEL			STD	
MTKXF	ROO98ADP		ASOLIN LEV3 E		0.208	0.300	0.300 * 0.300 0.300 0.00			0	. 05					
MTKXF	R0120GAK		ASOLIN LEV3 E		0.29	0.50	*	*		0.65	*		0.00		0	.05

A	CALIFORNIA AIR RESOURCES BOAR	4
MATT	AIR RESOURCES BOAR	D

MAZDA MOTOR CORPORATION

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
		FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g	/gallon) (DUL	FUEL TYPE		3DHS R (g/test	2DHS RIG TEST (g/test) @ UL			BLEED CANISTE TEST (g/test) @ 4		
	FUEL TYPE CERT STD				CERT	STD	CER	r	STD	CERT	STD	
MTKXR0098ADP	GASOLINE- TIER3 E10 0.00 0.20		GASOLINE- LEV3 E10		*	*	*		*	0.011	0.020	
MTKXR0120GAK	GASOLINE- TIER3 E10 0.00		0.20	*		*	*	*		*	*	*
E	EFFECTIVE	LEAK D	IAMET	ER STAI	NDARI	D AND CE	RTIFICA	TION L	EVE	EL (INCH	ES)	
EVAPORATIVE	LY		CE	ERT			STD					
MTKXR0098ADP MTKXR0098ADP			-001 *					0.02				
	*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2:											

LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle: HDV: heavy-duty vehicle: ECS: emission control system: CERT: certification: STD: standard: FEL: family emission limit: GVWR: gross vehicle weight rating: LVW: loaded vehicle weight: ALVW: adjusted LVW: LEV: low emission vehicle: ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER: PHEV: plug-in hybrid electric vehicle: NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits. Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MAZDA	CX-30	PC	2.5	SA6	MTKXR0098ADP	1	P
MAZDA	MAZDA3	PC	2.5	SA6	MTKXR0098ADP	1	P
MAZDA	MAZDA6	PC	2.5	SA6	MTKXR0120GAK	1	P