

HONDA MOTOR CO., LTD. Executive Order: A-023-0772 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFOR	MATION						
MODI	I TE	ST GROUP	LE CLASS(ES)			FUEL CATEGORY			FUEL TYPE					
202	1 MH	NXV01.5CEB			PC	PC 1			ELECTRIC HICLE		GASOLINE			
	USEFUL	LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY			ORY	INTERIM / IN	TE	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP			SF	ГР	FTP		SFTP			
150000 150000				LEV3	SULEV30	V30 LEV 3 CC		MPOSITE	SITE *		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	STATUS		ENGINE DISPLACEMENT (L)			
1	1 WU-TWC, TWC, WR-HO2S, HO2S, EGR, EGRC, SF							FULL	*	STORY SE				
*		*							ALL MODELS		1.5			
*	* *							TIAL WITH FINES	*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	MHNXR01	55VSA	LEV 3 OPTION2				PC			*				
		· · · · · · · · · · · · · · · · · · ·		E	EMISSION C	REDI [*]	TINFO	RMATION						
						EDIT FOR NON-PZEV ERO-EVAP			REDIT FOR DO	OPTIONAL EXH. STD FOR WORK TRUCKS				
	У И						N				N			
				NMOG	AND FLEE	TAVE	RAGE	INFORMA	TION					
NMO0 RAF	NMOG/NMHC:			HO/NMHC RATIO	PC+11)1/0-3/5011						D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		0.05	C	.058		0.065			*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HONDA MOTOR CO., LTD. Executive Order: A-023-0772

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1674 day of March 2020.

_ day of March 2020

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-TIER3 E10

0.02

0.20

MHNXR0155VSA

HONDA MOTOR CO., LTD.

Executive Order: A-023-0772

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

*

ATTACHMENT

	-													.S	
	EXHA	UST EMI	SSION S	STANDA	RDS A	ND CERT	IFICATIO	N LE	VELS (F	TP, HWF	ET,	50°F, 20)°F)		
FUE	FUEL TYPE		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP												
		N			(CO g/mi)								P M g/mi)	
	a.		RT	STD	CERT	STD	CEF	T	STD	CERT		STD	CERT	STD	
ок	*		*	*	*	*	*		*			*	*	*	
GASOLIN		1 0	013 (0.030	0.1	1.0	*		*	0		4	0.000	0.003	
ŧK	*		*	*	*	*	*		*	*		*			
			ELIEL TYPE					NMOG+NOx (g/mi)							
supercounts								CERT		STD		CER	T	STD	
HWFET @ 50K			*					*		*					
T@UL			GASOLINE-LEV3 E10					0.0	06	0.030					
20°F @ 50K COLD CO E10					REGULAR GASOLINE (TIER3)							0.3		10.0	
		SFTI	EXHA	UST EM	ISSION	STANDA	RDS ANI	CE	RTIFICA	TION LE	VEL:	S)	
			US06						SC03			COMPOSITE			
FUEL T	Aller Str. of China					CO PM (g/mi) (mg/m		NMOG+NOx (g/mi)		CO (g/mi)		Control of the Contro		PM i) (mg/mi)	
*	STE GASOLINE- LEV3 E10 STE		RT *		*			*		*					
			*		*			*		*					
			*		*	1		*		*	0.012		0.2	*	
			STD * * 6			*		*	0.077		4.2	*			
											0	.050			
	WH	OLE VEH	ICLE EV	APORA	TIVE E	MISSION	STANDA	RDS	AND CI	ERTIFICA	TIOI	N LEVE	LS		
				WI	HOLE V	EHICLE	EVAPOR	ATIV	E TESTI	NG		_			
EVAPORATIVE FAMILY		FUEL TYPE		PE 3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL			
				RT S	STD	FEL	CERT	T STD		FEL		CEF	RT	STD	
MHNXR0155VSA			1011010									0.0			
ORVR / FL	JEL C	ONLY / CA	NISTER	BLEED	EVAP	ORATIVE								VELS	
				o											
EVAPORATIVE FAMILY			,	FUEL TYPE			(g/te) UL	(g/test) @		UL TEST (g/tes			
	FU	EL TYPE	CERT	STD			CERT		STD	CERT	;	STD	CERT	STD	
	FUEL TY GASOLII LEV3 E GASOLII LEV3 E CRATIVE CORATIVE CORATIVE	FUEL TYPE T @ 50K T @ UL GASOLINE T @ UL GASOLINE LEV3 E10 WH ORATIVE MILY GROPH CONTRACTOR CO	FUEL TYPE FUEL TYPE ORV 1000 FUEL TYPE ORV 1000 CE OK * CE T @ 50K T @ UL @ 50K COLD CO E: SFTI FUEL TYPE * CERT STD CERT STD CERT STD GASOLINE- LEV3 E10 BIN WHOLE VEH ORATIVE ORVR / FUEL TYPE ORVR / GASOLINE- LEV3 E10 ORVR / GASOLINE- LEV3 E10	FUEL TYPE FUEL TYPE CH4: methan monoxide; No adjustment fa ORVR [g HC. 1000 miles; Feet of the monoxide] NMOG+N (g/mi) CERT OK * * * GASOLINE- 10.013 (Gen) FUEL TYPE FUEL TYPE FUEL TYPE SFTP EXHAUTE FUEL TYPE CERT * STD * GASOLINE- 10.000 miles; Feet on the monoxide; No adjustment factors of the monoxide; No adjust	### FUEL TYPE CANONING	CH4: methane; NMOG: non-omega and provided in the property of the provided in the provided i	FUEL TYPE	CH4: methane; NMOG: non-CH4 organic gas; Honoxide; NOx: oxides of nitrogen; HCHO: form adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 c ORVR [g HC/gallon dispensed]: on-board refueli 1000 miles; F: degrees Fahrenheit; FTP: federal 1000 miles; FTP: f	EXHAUST EMISSION STANDARDS AND CERTIFICATION LE	EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (it monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; Ph adjustment factor; 2DHS/3DHS (g HCHO: fb); 2/3 days diurnal+ORVR [g HC/Gallon dispensed]: on-board refueling vapor record 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles; F: degrees Fahrenheit; FTP: federal test procedu 1000 miles;	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHd monoxide; NOx: oxides of introgen; HcHO-: formaldehyde; PM: particul adjustment factor; 2DHS/3DHS [g HC/test); 2/3 days diurnal+hot-soak; ORVR [g HC/gallon dispensed]; on-board refueling vapor recovery; g: g1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP:	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: no monoxide; NOx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NOx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides of nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCx: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCX: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCX: oxides or nitrogen, HCH0: formaldehyde; PM: particulate in monoxide; NCX: oxides or nitrogen, HCH0: formaldehyde	EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°C)	Monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: read- adjustment factor; 2DHS/SJDHS (g HC/Rest); 23/ days diurnal+hot-soak; RL (g HC/mi]; unning ORVR (g HC/gallon dispensed): on-board refueling vapor recovery; g; gram; mg; milligram; m 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP	



HONDA MOTOR CO.,

Executive Order: A-023-0772

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MHNXR0155VSA	MHNXR0155VSA-C00	*	0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR: EGRC: EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MAKE MODEL		ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	INSIGHT	PC	1.5	CV1	MHNXR0155VSA	1	P
HONDA	INSIGHT TOURING	PC	1.5	CV1	MHNXR0155VSA	1	P