

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE YEA		TES	T GROUP		VEHIC	LE CLASS(E	S)	FUEL CATEGORY				FUEL TYPE		
202:	21 MHNXV02.0AEC PC								DEDICATED VE	GASOLINE				
USEFUL LIFE (miles) VEHICLE EMIS							ION C	ATE	GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP				TP	FTP		SFTP		
1	50000		150000		LEV3	SULEV30	LEV	3 C	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							-		OBD S	TATUS	E	ENGINE DISPLACEMENT		
1		TWC	, WR-HO2S,	но2	S, DFI, '	TC, CAC			FULL	*	1			
*	* *							P	ARTIAL	ALL MODELS		2.0		
*	* *							PAR	TIAL WITH	*]			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							Y EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES		
	MHNXR	0149	VSA		LEV 3	OPTION2			E	PC D		*		
					E	EMISSION CI	REDIT	INFC	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P				R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		Y				N				N		N		
					NMOG	AND FLEET	AVE	RAGI		TION				
NMOG RAF	CH4 FTP RAF NMOG/NMHC RATIO HCHO/NMHC RATIO (g/mi)				0-375	50 LVW) LDT		MOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*		1.10		0.05	0	.058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>6th</u> day of August 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				6+NOx mi)	CO (g/mi)			NOx (g/mi)		HCI (mg/		-		PM (g/mi)	
		CERT STD CERT STD C		CERT	STD		CERT	STD CE		RT	STD				
FTP@50K	*		*	*	*	*	*	*		*	*	* *		*	
FTP@UL	GASOLINE- LEV3 E10		0.017	0.030	0.4	1.0	*	*		0	4	0.0	01	0.003	
50°F @4K		OLINE- V3 E10	0.030	0.060	0.5	1.0	*	*		1	8				
	FUEL TYPE					NN	NMOG+NOx (g/mi)				CO (g/mi)				
			CE	RT		STD	CER	т		STD					
HWFET @ 50K		*						* *							
HWFET @ UL			0.0	08	C	0.030									
20°F @ 50K		COLD	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)					0.8			10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFIP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS															
				US06						SC03		COMPOSITE			
	FUEL TY			NMOG+NOx		CO P		N	NMC	G+NOx	со	NMOG+NO	x CO	PM	
				(g/mi)		(g/mi)	(mg/	/mi)	(9	g/mi)	(g/mi)	(g/mi)	(g/m	i) (mg/mi)	
@ 4K	24K ★		ERT	*		*				*	*				
-		S	STD	*		*			*		*				
	UL GASOLINE- LEV3 E10		ERT	*	*		* 4		*		*	0.018	0.5	*	
@ UL						*	* 6		*		*	0.077	4.2	*	
		E	BIN									0.050			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
					W	HOLE \	/EHICLE	EVAPC	RAT	IVE TEST	ING				
	ORATIVE	···· FUEL TY		UEL TYPE 31		3DHS (g/test) @ L			2DHS (g/test) @ UL			RL (g/mi) @ UL			
				CERT		STD	FEL	CER	Т	STD	FEL	CE	RT	STD	
MHNXI	MHNXR0149VSA		OLINE- V3 E10	0.1	0.178 0		*	0.21	.5	0.300	*	0.0	00	0.05	
(ORVR / FUI	EL ONI	LY/CA	NISTER	BLEED) EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VELS	
								FU	EL O	NLY EVA	P & CANIS	TER BLEE	D		
	EVAPORATIVE FAMILY		ORVR (g/ga		on) @ UL				HS RIG TEST g/test) @ UL			2DHS RIG TEST (g/test) @ UL		CANISTER /test) @ 4K	
		FUEL	TYPE	CERT	STD]		CEF	хт	STD	CERT	STD	CERT	STD	
MHNXE	R0149VSA		LINE- 3 E10	0.01	0.20		OLINE- 73 E10	*		*	*	*	0.010	0.020	



HONDA MOTOR CO., LTD.

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MHNXR0149VSA	MHNXR0149VSA-A00	*	0.02							

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC; SCR coated DPF); CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORM	IATION
--	---------------

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ACURA	TLX AWD	PC	2.0	SA10	MHNXR0149VSA	1	P
ACURA	TLX AWD A-SPEC	PC	2.0	SA10	MHNXR0149VSA	1	P
ACURA	TLX FWD	PC	2.0	SA10	MHNXR0149VSA	1	P
ACURA	TLX FWD A-SPEC	PC	2.0	SA10	MHNXR0149VSA	1	P