

HONDA MOTOR CO., LTD. Executive Order: A-023-0785

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD YEA	I T	TEST GROUP			VEHICLE CLASS(ES)				ATEGORY		FUEL TYPE		
202	1 MH	NXV02.0CL3		PC DED.					SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								GORY	INTERIM / IN	TERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP				TP	FTP		SFTP		
1	50000	150000		LEV3	3 SULEV30 LEV 3 COM			OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1		TWC, WR-F	102S,	HO2S, S	3FI			FULL	*				
*	* PARTIAL								ALL MODELS	1	2.0		
*	* PARTIAL WITH * FINES												
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	MHNXR01	LEV 3	OPTION2				PC		*				
		·		I	EMISSION C	REDIT	[INF	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP							NMOG CREDIT FOR DOR				OPTIONAL EXH. STD FOR WORK TRUCKS		
Y N								N			И		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	I NMOG/NMHG I I I DC					EET S 0 LVV	V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m)	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	* 1.10 0.05 0.058 0.065 *						*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HONDA MOTOR CO., LTD.

Executive Order: A-023-0785

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 4th day of September 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



HONDA MOTOR CO., LTD.

Executive Order: A-023-0785 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

	ATTAOTIMENT																		
	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																			
	FUEL TYPE				CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP														
				NIV	IOG+N (g/mi)		(CO (g/mi)			NOx g/mi)	1	HCH mg/n	_	PM (g/mi				
			ļ		CER	т	STD	CERT	ST	D	CERT	STD	CER	т	STD		RT	STD	
FTP@5	FTP@50K		*		*		*	*	*	.	*	*	*		*	*		*	
FTP@L	I ETDMIII I		SOLINE- V3 E10		0.01	5 (0.030	0.1	1.	0	*	*	0	4		0.000		0.003	
50°F @	4K	*	*		*		*	*	*		*	*	*		*				
					FUEL TYPE								NOx (g/mi)		CO (g				
										C	ERT	STD *	_	CERT		STD			
HWFE		+				*													
	T @ UL	+			G2	GASOLINE-LEV3 E10					0	0.005							
20°F	@ 50K		CO					SASOLIN		-					0.4		:	10.0	
	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																		
	FUEL T		<u>, </u>		US06 NMOG+NOx CO PM						SC03 NMOG+NOx		СО	NMOG+NO		MPOSITE CO		PM	
			IFE		(g/mi)			(g/mi)	1 -	(mg/mi)		j/mi)	(g/mi)	(g/mi)			/mi)	(mg/mi)	
@ 4K	@ 4K *		STE				*			*		*							
					*			*				*							
	CAGO			CERT	*		*		1	*		*	0.014		0.1		*		
@ UL GASO		E10 ST		STD	*		*		6	*		*	0.077		4.2		*		
				BIN										0.050					
		<u>\</u>	NH (OLE V	EHIC	LE EV							ERTIFIC	ATIO	N LEVEL	_S			
	EVAPORATIVE			UEL T				VHOLE V g/test) @		EVAP		S (g/test				RL (g/mi)) @ UL	
	FAMILY				CE				FEL	CE		STD	FEL		CER	T		STD	
MHNXR0113VS		SA			SOLINE-				300 *		0.202 0.300		*					0.05	
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																			
	\Box											P & CANI							
EVAPORATIVE FAMILY		VE	E ORVI		R (g/gallon) @ UL			_ FUEL	_ TYPE			G TEST @ UL		2DHS RIG (g/test) @				NISTER st) @ 4K	
		-+	FUEL T		-	ERT	STD				RT STD		CERT		STD		RT	STD	
MHNXF	MHNXR0113VSA			SOLINI ER3 E		0.02	0.20	1 1	LINE- 3 E10		*	*	*		*	0.0	06	0.020	



HONDA

CIVIC SEDAN

HONDA MOTOR CO., LTD.

Executive Order: A-023-0785

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

MHNXR0113VSA

P

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MHNXR0113VSA	MHNXR0113VSA-A00	*	0.02							

the included in the control of the c .DT<6000#GVWR,3751-5750#LVW; LDT3; LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4; LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC; SCR coated DPF); CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION MAKE MODEL VEH CLASS ENGINE (L) TRANS TYPE EVAPORATIVE EXH ECS OBD

2.0

CV1,SCV7

PC