

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
YEA		TEST	GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2021 MHYXV01.6KC5					PC					SINGLE FUE	6	GASOLINE		
	and the second		E (miles)		VE	VEHICLE EMISSION CATEGO				INTERIM / II	NTER	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP				TP	FTP		SFTP		
150000 150000					LEV	V3 ULEV70 LEV 3 C			OMPOSITE *			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS									OBD S	OBD STATUS		ENGINE DISPLACEMENT		
1	DFI,	WR-H	102S, HO2	s, wu	J-TWC, 1	TWC, TC, CA		FULL	ALL MODELS					
*	*								ARTIAL	*	-11	1.6		
*	*								TIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								, EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
M	HYXR0)127KC	E		I	LEV 2			PC			*		
						EMISSION CR	EDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-F							ON-PZ	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N N				
					NMOG	AND FLEET	AVE	RAGE	INFORMAT	ION				
IMOG RAF	CH4 RAF	1	FTP DG/NMHC RATIO		ICHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)							NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*		1.10		*	0.	058			0.065		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

HYUNDAI MOTOR COMPANY Executive Order: A-254-0447 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				NMOG+NOx CO						NOx				НСНО			PM		
			g/mi)			(g/mi)			(g/mi)		(mg/mi)		/mi)	(g/m		j/mi)			
				CERT		-	CER	TS	TD	CERI	CERT STD		CER	CERT		CERT		STD	
FTP@50K *			*	*		*		*	*		*	*		*		*	*		
FTP@UL GASOLINI TIER3 E		E10	0.047	0.0	70	0.3	1	.7	*		*	*		4		0.001	0.003		
50°F @	50°F @4K GASOLINE TIER3 E1			0.046	0.1	40	0.2	1	.7	*		*	*	*					
						NMOG+NOx (g/mi)					CO (g/mi)								
		1			FUEL	1111	6			C	CERT		STD		CERT		STD		
HWFE	T @ 50M	<			*						*		*						
HWFE	T @ UL			GAS	OLINE-	TIER	CR3 E10			0	0.027		0.070						
20°F	@ 50K		COLD CO	O E10 1	REGULAI	R GA	ASOLINE (TIER3)							0		.4 1		10.0	
			5	SFTP E)	HAUST	EMI	SSION	STANE	ARDS	AND	CERTI	FICA	TION LI	EVE	S				
						U	US06				SC03				COMPO		POSITE	SITE	
	FUEL T				NMOG+NOx (g/mi)		CO (g/mi)	PM (mg/mi)		1	NMOG+NOx (g/mi)						CO (g/mi)	PM (mg/mi)	
@ 4K	*	*		т *			*				*		*						
					*		*				*	+	*	1		+			
		ASOLINE- EV3 E10 BI			*		*		1	1	*	1	*		0.047	1	0.4	*	
@ UL					*		*		6		*		*	0.077			4.2	*	
														1	0.070				
		WI	HOLE V	EHICLE	EVAPO	RAT	IVE EN	AISSION	N STA	NDARD	DS AND) CE	RTIFICA	TIO	N LEVE	ELS			
						WH	OLE VI	EHICLE	EVAP	ORAT	IVE TE	STIN	G						
	ORATIVE FUEL TYP		YPE	3DH	S (g/t	ı/test) @ UL			2DH	2DHS (g/test)) @ UL		RL (g/mi) @	UL		
					CERT	STD		FEL	CE	RT	T STD		FEL		CERT		STD		
MHYXR	MHYXR0127KCE		asolin A Phas	102510			.50 *		0.	28	8 0.65		*	* 0.02		02	0.05		
C	RVR / F	UEL	ONLY /	CANIST	ER BL	ED	EVAPO	RATIV	EEMIS	SION	STAN	DAR	S AND	CEF	RTIFICA	TIO	N LEVI	ELS	
													& CANIS			_			
	EVAPORATIVE FAMILY		ORVR (g/gallon) @ UL							HS RIG TEST /test) @ UL		-	2DHS RIG 1 (g/test) @					D CANISTER (g/test) @ 4K	
		FL	JEL TYI	PE CE	RT ST	D			CE	RT	STD		CERT		STD	С	ERT	STD	
MHYXR0127KCE		Ξ	SOLINE TIER 2 NLEADE	0.0	0.03 0.20		*		-	*	*		*		*		* *		

CALI AIR RESC	FORNIA DURCES BOARD	н	YUNDAI MOTOR COMPANY	Executive Order: A-254-0447 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
EFFECTIV	/E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	LEVEL (INCHES)						
EVAPORATIVE FAMILY			CERT		STD						
*	*		*		*						
8500#ALVW; MDV: medium-o duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi: heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRE fuel injection; DFI/IFI: direct/in full/partial/partial with fines on- prefix 2: parallel; (2) suffix: ser device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; I -automatic transmission; CV: o automated manual transmission	* * * * * * * * * * * * * * * * * * *										

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYUNDAI	KONA AWD	PC	1.6	AMS7	MHYXR0127KCE	1	F
HYUNDAI	KONA FWD	PC	1.6	AMS7	MHYXR0127KCE	1	F