

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FOR	MATION						
MODE	I T	EST GROUP	VEHIC	ES)	FUEL CATEGORY				FUEL TYPE				
2021	L MR	MXT03.3KJ5		LDT2		DEDICATED SINGLE FUEL VEHICLE				GASOLINE			
	USEFUL	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEC	GORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD			
EXH	I/ORVR	EVAP		FTP S			FTP FTP			SFTP			
15	50000	150000	LEV3	ULEV70	LEV	EV 3 COMPOSI		*		PM			
SPE	ECIAL FE		HAUST EMISSIO	ON CONTRO	OL		OBD S	TATUS	South States	ENGINE DISPLACEMENT (L)			
1 DFI, 2WR-HO2S, 2HO2S, 2WU-TWC, TWC							FULL	ALL MODELS	COMPANY.				
*			******		PARTIAL		*	3.3					
*					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	TIAL WITH FINES	*	South and the second					
		E\	APORATIVE &	REFUELIN	G (EVA	P/OR	VR) FAMIL	INFORMATION	1	i i			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY						EVAP EMISSION STD VEHICLE CLASS SPECIAL FEAT						
1	MKMXR0139KJG LEV 3 OPTION2						LD	т2	*				
				EMISSION (	CREDIT	INFC	RMATION		1				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMOG CI	OPTIONAL EXH. STD FOR WORK TRUCKS					
N N								N					
			· NMOG	AND FLEE	T AVE	RAGE	INFORMA	ΓΙΟΝ	-				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NOX FLEE PC+LDT (0-3750 L (g/mi)			) LDT	+NOX FLEET S⊺ (3751 LVW-8500 ₹) + MDPV (g/m		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10	*		0.058			0.065		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1674 day of March 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division

R7	R	) C	ALI R RES	FC	) R N Ses b	VIA oard			OTORS DRATIOI			E New Pass			_ight-D	uty Tr -Duty		
			-				A	ТТАС	HME	NT						-		
	EXH	HAUS	ST AN	DEV	APOF	RATIVE	EEMIS	SION	STAN	DAR	DS AN	D CERT	IFIC	ATION	LEV	ELS		
		EX	HAUST	EMIS	SION	TANDA	RDS A	ND CER	TIFICAT		LEVELS	(FTP, HV	VFET	, 50°F, 2	20°F)		1999	
	F	UEL T		CH4: methane; NMOG: non-CH4 organic gas; HC monoxide; NOx: oxides of nitrogen; HCHO: forma adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 da ORVR [g HC/gallon dispensed]: on-board refuelin 1000 miles; F: degrees Fahrenheit; FTP: federal t						ormalo /3 day ueling	dehyde; F /s diurna vapor re	PM: partic I+hot-soal covery; g:	ulate ; RL gran	matter; I [g HC/m n; mg: m	RAF: re i]: runn illigram	eactiv ning lo n; mi:	ity ss;	
		NN		/IOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCH (mg/n				PM (g/mi)				
				CERT		STD	CERT			ERT	STD			STD		RT	STD	
FTP@50	ĸ	*		*		*	*	*		*	*	*		*	*		*	
FTP@U	с т	GASOLINE- TIER3 E10		0.03	39 (	0.070	0.6	1.	7	*	*	*	* 4		0.002		0.003	
50°F @4	0°F @4K GASOLINE- TIER3 E10			0.05	59 (	0.140	0.5	1.	7	*	*	*		16				
					FU	EL TYP	E			NMOG+NOx					CO (g/mi)			
HWFET @ 50K				*					- 57 <u>1</u>		ERT *	STD *		CEF	CERT		STD	
				SOLIN	E-TIER	TIER3 E10			0.	018	.8 0.070							
20°F @ 50K			COLD C	O E10	REGI	ILAR GA	ASOLINE (TIER3)		83)		an a	MAR ANNA		1.4		1.1.57	L2.5	
-					1.53	And the state	And Instant And	1	18		FRTIEIC	ATION L	EVEL		1	- 14 - 14 - 14 - 14 - 14 - 14 - 14 - 14		
				·····			JS06				SC03				OMPO	SITE		
	FUEL	- TYPE	TYPE		/IOG+N (g/mi)		CO (g/mi)		PM g/mi)		G+NOx /mi)	CO (g/mi)		OG+NO (g/mi)		CO /mi)	PM (mg/mi	
@ 4K		*	CER	ERT *			*				*	*						
e			STD	)	*		*				*	*						
			CER	т	*		*		1		*	*		0.033	0	. 9	*	
@ UL		LINE- 3 E1(			*		*		6		*	* 0.077		0.077	4	.2	*	
		BI												0.070				
		W	HOLE	VEHIC	LE EV							CERTIFIC	ATIO	N LEVE	LS			
						Wł	HOLE V	EHICLE	EVAPO	RATI	VE TES	TING		ļ _				
EVAPORATIVE FAMILY		Y FUEL TYP		ГҮРЕ	PE 3DHS (g/test) @ UL			UL		2DHS (g/test		) @ UL		RL (g/mi) @		11) @	JOL	
					CEF	RT S	STD	FEL	CER	Т	STD	FE	L CER		RT		STD	
MKMXR0139KJG		(JG		LEV3 E10		400	0 * 0.2		4	0.400 *		0.01		01				
0	RVR /	FUEL	ONLY	/ CAN	ISTER	BLEED	EVAPO	ORATIVI				RDS ANI				LEVE	LS	
EVAPORATIVE FAMILY		VE	/E ORVR (g/gallon) @ UL					30			HS RIG TEST		AP & CANISTER			EST BLEED CAN		
		FUEL TY		YPE CERT STD		STD	FUEL TYPE		(g/ CER	g/test) @ UL ERT STD		(g/te CERT				EST (g/test) ( CERT S		
	KMXR0139KJG		ASOLI	TE-	0.03	0.20	GASOLINE- LEV3 E10		*		*			* 0.00			STD 0.020	

,

	FORNIA urces board	KIA MOTORS CORPORATION	Executive Order: A-314-0353 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTIV	E LEAK DIAMETER	STANDARD AND CER	TIFICATION L	EVEL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	r	STD		
MKMXR0139KJG	MKMXR0139KJG-Y	and the second sec	The second second second	0.02		
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-o duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRI fuel injection; DFI/IFI: direct/ir full/partial/partial with fines or prefix 2: parallel; (2) suffix: se device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV:	D#LVW; LDT3: LDT 600 duty vehicle; MDV4: ME heavy-duty vehicle; E0 vehicle weight rating; L ber ULEV; ZEV: zero-er IAC: HC adsorbing cata : selective catalytic reduced zer; DPF: diesel particulor (02S or AFS: wide range sor; NH3S: ammonia se E: secondary air injection; TO h-board diagnostic; DOI wries; a hyphen (-) betw coated DPF); CNG/LN E10: "10%" ethanol ("9 continuously variable t ion; AMS: automated m V: plug-in hybrid electric	01-8500#GVWR,3751-5750 01 8501-10000#GVWR; ME CS: emission control system VW: loaded vehicle weight; nission vehicle; TZEV: trans alyst; WU: warm-up catalyst uction-urea/ammonia; NH30 ulate filter (active); GPF: PM ge/linear/heated air-fuel rationation ge/linear/heated air-fuel rat	WALVW, LD14, I DV5: MDV 10001 n; CERT: certifica ALVW: adjusted sitional ZEV; TW ; NAC: NOx ads DC: ammonia ox 1 filter for spark-it o sensor; NOXS: circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon dicates multiple f atural gas; LPG: natic (with lockup le continuously v ion: OT: other tri-	gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi		

,

	2021 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD					
KIA	SEDONA	LDT2	3.3	SA8	MKMXR0139KJG	1	F					