

KIA MOTORS CORPORATION

Executive Order: A-314-0356

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP IN	IFOR	MATION					
MODE	TEST GROUP VEHICLE (LASSIES)					S)		FUEL CATEGORY			FUEL TYPE			
2021	MIK	MXT02.4HH5	LDT1, LDT2						DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL LIFE (miles) VEHICLE EMISSION (EGORY INTERIM / INTERMEDIATE IN-USE ST				
EXH	I/ORVR	EVAF)		FTP			SF	TP	FTP		SFTP		
15	0000	15000	0		LEV3	LEV3 ULEV70 LEV 3			COMPOSITE *			PM		
SPE	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1	D	FI, WR-HO2S	S, H	1025	, WU-TW	C, TWC			FULL	ALL MODELS				
*	* *							P	PARTIAL *			2.4		
*	* *							1	RTIAL WITH *					
		E	VAF	POR	ATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	V			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY							,	EVAP EMISSION STD VEHICLE CLASS SPEC			PECIAL FEATURES		
1	MKMXR01	33HHG			LEV 3	OPTION2			LDT1			HCT		
		<u>'</u>			E	MISSION CI	REDIT	INFO	ORMATION					
1	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-F						ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	n n								N			N		
NMOG AND FLEET AVERAGE INFORMATION														
NMOG CH4 RAF NMOG/NMHC RATIO HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37: (g/mi)						0-375		V) LDT (3751 LVW-8500 MDV (10,001-			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	* * 1.10 * 0.058							0.065 *						
									D: 1		- 0-	ntrol Systems Phase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



KIA MOTORS CORPORATION

Executive Order: A-314-0356

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of April 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-

TIER3 E10

MKMXR0133HHG

KIA MOTORS CORPORATION Executive Order: A-314-0356

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

0.011

0.020

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				-				and the second second second second second		STATE OF THE OWNER, TH		CERTI				LS	
		EXHA										FTP, HW					
	FUE	L TYI	mo ad Of 10	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: car monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivi adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running lo ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP										ty ss;			
					NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCH(mg/n			PM (g/mi)	
				CERT	!	STD	CERT	STD		CERT	STD	CER	Г	STD	CER	Т	STD
FTP@50	OK	*		*		*	*	*		*	*	*		*	*		*
FTP@U	GASOLINE- TIER3 E10 0.0			.031	0	.070	0.6	1.7		*	*	*		4	0.000		0.003
50°F @4		OLIN R3 E		.032	0	.140	0.3	1.7		*	*	*		16			
					FUE	I TYPI	=				MOG+NO		_		CO (g	_	
				FUEL TYPE						С	ERT	STD		CERT		STD	
HWFET	@ 50K			*							*	*					
HWFE	T@UL			GASOLINE-TIER3 E10						0.	016	0.070					
20°F (20°F @ 50K COLD CO E10 RE					GULAR GASOLINE (TIER3)										10.0	
			SF	TP EX	(HAU			STANDA	RDS	AND C		ATION LE	VEL				
				US06							SC03	COMPOSITE OG+NOx CO PM					
FUEL TYPE			NMOG+NOx (g/mi)		CO (g/mi)	PI (mg/		1	G+NOx /mi)	CO (g/mi)	100000000000000000000000000000000000000	NMOG+NOx (g/mi)		ni)	PM (mg/mi)		
@ 4K	*	* CEI		т *		*				*	*						
					*		*				*	*					
		<u> </u>		CERT		*		* 4		*		*	0.029		0.	7	*
@ UL	GASOLI TIER3		STD	*			* 6			*		*	0.077		4.	2	*
			BIN											0.070			
		WH	OLE VE	HICLE	E EV							ERTIFICA	ATIO	N LEVE	LS		
	EVAPORATIVE		FUEL TYPE			TYPE 3DHS (g/test) @ UL					S (g/test)		RL (g/mi) @ UL				
FAMILY		PUELTIPE		· -	CERT STD			FEL	CEI		STD	FEL		CERT		STD	
MKMXR0133HHG		- 1		SOLTNE-		0.248 0.				0.300		*	* 0.		01 0		0.05
	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVE									SION	STANDA	RDS AND	CEF	RTIFICA	TION L	EVE	LS
												P & CANI					
EVAP	ORATIVE	E	ORVR (g/gallo	on) @	UL	FUE	L TYPE			G TEST @ UL	2DHS (g/te			TEST	g/te	NISTER st) @ 4K
EVAP	ORATIVE		ORVR (on) @	UL STD	FUE	L TYPE	(st) @			g/te	

GASOLINE-

LEV3 E10

0.20

0.00



KIA MOTORS CORPORATION

Executive Order: A-314-0356

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MKMXR0133HHG	MKMXR0133HHG-QL1	0.00	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW: MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer: DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS; reductant quality sensor; NH3S; ammonia sensor; EGR; exhaust gas recirculation; HP/LP EGR; High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

1								
	MAKE MODEL		VEH CLASS ENGINE		TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
	KIA	SPORTAGE AWD	LDT2	2.4	SA6	MKMXR0133HHG	1	F
	KIA	SPORTAGE FWD	LDT1	2.4	SA6	MKMXR0133HHG	1	F