

KIA MOTORS CORPORATION

Executive Order: A-314-0359

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE YEAR	- I T	EST GROUP	VEHIC	CLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2021	MIK	MXT03.8ML5			LDT2	アルカン			SINGLE FUEI HICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEH	IICLE EMISS	E EMISSION CATEGORY INTERIM / INT					ERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP SFT			TP	FTP		SFTP			
15	0000	15000	LEV3	3 ULEV70 LEV 3 COMP			MPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ENGINE DISPLACEMEN			
1 DFI, 2WR-HO2S, 2HO2S, 2WU-TWC, TWO								FULL	ALL MODELS				
*	* *							ARTIAL	*		3.8		
*	* *							RTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS	PECIAL FEATURES			
1	LEV 3	OPTION2			LD	T2		*					
		***************************************		I	EMISSION CI	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR EXERO-EVALUATION						ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N N								N			N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	NMO(-/NMH() P(-+) 1) (0-5/					0-375		V) LDT					
*	*	1.10		*	0	.058			0.065 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



KIA MOTORS CORPORATION

Executive Order: A-314-0359 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations. (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seg. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this _57# day of June 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-

TIER3 E10

0.02

0.20

MKMXR0135MLG

KIA MOTORS CORPORATION Executive Order: A-314-0359

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

0.011

0.020

ATTACHMENT

		=VIII	MIC	TAN	D E14	ADO	D 4 = 11	VE											
			4U3	IAN	DEV	APC	RATI	VE EMIS	SION	STA	NDAR	DS AN	ID CERT	ΓIFΙ	CATIO	N LE	VELS	3	
	EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																		
	FUEL TYPE			CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP										vity					
			N		NI	VIOG+ (g/m		1	CO (g/mi)		NOx (g/mi)			HCHO (mg/mi)		PM (g/mi)			
				CERT STD		STD	CERT	CERT STD		CERT	RT STD		CERT		STD CERT		STD		
FTP@	50K		*		*		*	*	,	-	*	*	*			_	*	*	
FTP@	UL	TIE	SOLINE- ER3 E10		0.04	16	0.070	0.3	1.	7	*	*	*		4	0.	001	0.003	
50°F @			OLIN R3 E		0.03	30	0.140	0.1	1.	7	*	*	*	* 16					
						EI	JEL TY	DE	NMOG+NOx (g/mi)							CO (g/mi)			
						- ' '	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_			CE	ERT STO			CER			STD	
HWFE	HWFET @ 50K						*				,	*		*					
HWFE	HWFET @ UL GASOLINE-TIE					ER3 E10			0.070	0.070									
20°F	20°F @ 50K COLD CO E10 REGULAR GA						GASOLINE	SOLINE (TIER3)				0.9			12.5				
				,	SFTP I	EXHA	UST EI	VISSION S	TAND	ARDS	AND CE	RTIFIC	ATION L	EVEL	.s				
		FUEL TYI						US06				SC03		COMPOSITE					
	FU		FE		NN	NMOG+NOx (g/mi)		CO (g/mi)	1	M J/mi)	NMOG (g/r		CO (g/mi)	NMOG+NOx (g/mi)			CO J/mi)	PM (mg/mi)	
@ 4K		*		CERT	*		*			*		*							
				STD		*		*			*		*						
		ASOLINE- IER3 E10 BIN		CERT		*		*	* 3		*		*	0.039		(. 4	*	
@ UL				STD	*		*		6	*		*	0.077		4	1.2	*		
														0.070					
			WH	OLE V	EHICL	EEV		ATIVE EMI						ATIO	N LEVE	LS			
EVAPORATIV FAMILY			FUEL TYPE		-		g/test) @ L	OLE VEHICLE EVAPO			2DHS (g/test) @ UL			RL (g/mi) @ UL			UL		
		Y			CERT				FEL	CEI					CERT				
MKMXR0135ML		5MLG	GASOLINE- LEV3 E10		0.2		.400	*	0.2		0.400	FEL *	0.02						
C	RVF	R / FU	-			STER	BLEF	DEVAPOR	ATIVE	EMIS	SION ST	TANDA	RDS AND	CEF	RTIFICA	TION	EVE	S	
	-		T										P & CANIS				V I		
	EVAPORATIVE FAMILY		ALCOHOL COLORS		(g/gallon) @ UL			1			HS RIG						BLEED CANISTER EST (g/test) @ 4K		
			FUEL TY		PE C	ERT	STD			CE		STD	CERT	1	STD		ERT STD		

GASOLINE-

LEV3 E10



KIA MOTORS CORPORATION

Executive Order: A-314-0359

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MKMXR0135MLG	MKMXR0135MLG-ON1	0.00	0.02							

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MAKE MODEL		ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD
KIA	TELLURIDE AWD	LDT2	3.8	SA8	MKMXR0135MLG	1	F
KIA	TELLURIDE FWD	LDT2	3.8	SA8	MKMXR0135MLG	1	F