

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP II	NFOR	MATION					
MODE	- I T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE			
2021	M	GAJ03.0N7F		1	LDT2, PC				SINGLE FUEL HICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEI	HICLE EMISS	ION C	CATE	GORY	INTERIM / IN	T	ERMEDIATE IN-US	E STD	
EXH	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
15	50000	150000		LEVS	3 ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	T	ENGINE DISPLACEMENT		
1	WU-TWC, TWC, WR-HO2S, HO2S, DFI, TC, CAC							FULL	*				
*	*							PARTIAL	ALL MODELS	1	3.0		
*			×					TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	EVAI	PORATIVI	E STD CATE	GORY			SSION STD E CLASS		SPECIAL FEATU	RES	
N	WGAR01	40NCN	LE	V 3 OPT:	ION2 WITH I	FEL		LDT2			*		
M	NGAR01	40NCP	LE	LEV 3 OPTION2 WITH FEL				PC			*		
					EMISSION CR	REDIT	INFO	ORMATION					
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR NO	ON-P	ZEV NMOG CREDIT FOR DOP			२	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG	INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO			C NMOG+NOX FLEET PC+LDT (0-3750 LV (g/mi)						MDV (10,001-14,000		
*	*	1.10		*	0	.058			0.065		*		
								and the second second second second					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 29th day of May 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0189 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity

FUEL TYPE

adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)		1	Ox mi)	HCHO (mg/mi)		-	M mi)			
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K		*	*	*	*	*	*	*	*	*	*	*		
FTP@UL	TIE	SOLINE- R3 E10 PREM	0.0418	0.070	0.31	1.7	*	*	*	4	0.0010	0.003		
50°F @4K	TIE	OLINE- R3 E10 PREM	0.0283	0.140	0.35	1.7	*	*	*	16				
				FUEL TYP	E		NN	IOG+NOx	(g/mi)		CO (g/mi)			
	FUELTIPE						CE	RT	STD	CER	т	STD		
HWFET @	50K			*			*	* *						
HWFET @ UL			GASOLINI	E-TIER3 1	E10 PREM	1	0.0	169	0.070					
20°F @ 5	50K		GASOLINI	E-TIER3 1	E10 PREM	ſ				0.57	7	10.0		
			SFTP EXH	AUST EM	ISSION ST	ANDARD	S AND CE	RTIFICAT		15				

SETP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			51	TIPE	XHAUS I	EMISSIO	NSIANL	JARDS	AND (JER HEIC	ATION L	EVEL	.s		
				US06					SC03				COMPOSITE		
	FUEL TY	PE		NM	OG+NOx	CO		PM	NMO	G+NOx	CO	NM	OG+NOx	CO	PM
					(g/mi)	(g/mi)) (m	g/mi)	(g	j/mi)	(g/mi)		(g/mi)	(g/mi)	(mg/mi)
@ 4K	@4K *		CERT		*	*				*	*				
			STD		*	*				*	*				
	GASOLINE- UL TIER3 E10 PREM		CERT		*	*	5	5.0		*	* (.0293	0.41	*
@ UL					*	*		6	* * 0.077		0.077	4.2	*		
			BIN									0	0.050		
		WH	OLE VE	HICL	E EVAPO	ORATIVE E	MISSIO	N STAN	DARD	S AND C	ERTIFIC	ATIO	N LEVELS	;	
						WHOLE	VEHICLE	EVAPO	ORATI	VE TEST	ING				
1	ORATIVE			PE	3DH	S (g/test) (@ UL	2DHS (g/test) @ UL RL (g/mi) @					UL		
							CERT	STD	FEL	CER	т	STD	FEL		CERT
MVGAR	0140NCN		ASOLIN IER3 E		0.310	0.400	0.400	0.27	73	0.400	0.40	0	0.000		0.05
MVGAR	0140NCP		ASOLIN IER3 E PREM		0.254	0.300	0.300	0.24	13	0.300	0.30	0	0.000		0.05

A		ALIF RESOU	OR	
1111	MIR	RESUU	RUES	BUARD

VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0189 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

											ge i ei i	
ORVR / FU	EL ONLY /	CANISTER	BLEED	EVAPO	RATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	ELS	
									STER BLEE			
EVAPORATIVE FAMILY	(5.5			FUEL	TYPE		IG TEST) @ UL		RIG TEST		D CANISTER (g/test) @ 4K T STD .6 0.020 98 0.020 98 0.020 98 0.020 98 C.020 98 C.020 97 C.020 98 C.020 97 C.020	
	FUEL TYP	PE CERT	STD			CERT	STD	CERT	STD	CERT STE		
MVGAR0140NCN	GASOLINI TIER3 E:		0.20	GASOL TIER3		*	*	*	*	0.016		
MVGAR0140NCP	GASOLINI TIER3 E1 PREM	- 1	0.20	GASOLINE- TIER3 E10 PREM		*	*	*	*	0.008	0.020	
E	EFFECTIV	E LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION LE	EL (INCH	ES)		
EVAPORATIVE FAMILY LEAK FAMIL					Y CERT				STD			
MVGAR0140NCP MVGAR0140NCP			-001 *					0.02				
MVGAR0140	NCN	MVGAR0	140NCN	-001		*				0.02		
: not applicable; # .DT<6000#GVWR 3500#ALVW; MDV luty passenger vel emission limit; GVV JLEV: ultra LEV; S ADSTWC: adsorbin SCRC/SCR-N or S continuous/periodic leated/oxygen sen 2020: reductant q	,3751-5750 : medium-d hicle; HDV: WR: gross v SULEV: sup ng TWC; H/ CRC-NH3: c trap oxidiz sor; WR-H0)#LVW; LDT uty vehicle; heavy-duty vehicle weig er ULEV; ZE AC: HC ads selective ca cer; DPF: die O2S or AFS	3: LDT (MDV4: I vehicle; ht rating EV: zero- orbing ca talytic re esel part : wide ra	6001-850 MDV 850 ECS: em ; LVW: los emission atalyst; W eduction-u iculate filt	0#GVW 1-10000 aded ve vehicle /U: warr urea/am ter (activ ar/heated	R,3751-575 WGVWR; M control syste hicle weigh ; TZEV: trai n-up cataly: monia; NH: ve); GPF: P d air-fuel rai	50#ALVW; I IDV5: MDV em; CERT: t; ALVW: ad nsitional ZE st; NAC: NG 30C: ammo M filter for tio sensor	LDT4: LD / 10001-14 certificatio djusted LV EV; TWC/C Ox adsorp onia oxida spark-ignit NOXS: NO	F 6001-8500 4000#GVWI n; STD: sta W; LEV: low OC: 3-way/o tion catalysi tion catalysi eed engine; Dx sensor: F)#GVWR,57 R; MDPV: n ndard; FEL: v emission v xidizing cat. t; SCR-U or t; CTOX/PT HO2S/O2S	751- family vehicle; alyst; OX:	

EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits,

Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
AUDI	S4	PC	3.0	SA8	MVGAR0140NCP	1	P
AUDI	S5	PC	3.0	SA8	MVGAR0140NCP	1	P
AUDI	S5 CABRIOLET	PC	3.0	SA8	MVGAR0140NCP	1	P
AUDI	S5 SPORTBACK	PC	3.0	SA8	MVGAR0140NCP	1	P
AUDI	SQ5	LDT2	3.0	SA8	MVGAR0140NCN	1	P