

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE YEAR	- I TI	EST GROUP	VEHICLE CLASS(ES)				FUE	FUEL CATEGORY			FUEL TYPE			
2021	MH	PC			IN HYBRID IC VEHICLE			GASOLINE						
1	USEFUL	. LIFE (miles)		VEF	ICLE EMIS	SION	CAI	TEGORY		INTERIM / IN	RIM / INTERMEDIATE IN-USE STD			
EXH	/ORVR	EVAP			FTP			SFTP		FTP		SFTP		
15	0000	150000		LEV3	SULEV30	LEV	3	COMPOSIT	E	*		PM		
SPE	CIAL FE	ATURES & EXI SYS	IAUS TEMS			DL		OBI	D S'	TATUS		ENGINE DISPLACEMENT (L)		
1 1	DFI, WI	GRC		FULL		ALL MODELS								
*	*							PARTIAL		*	1	1.6		
*	*							ARTIAL WI ⁻ FINES	тн	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR									SSION STD E CLASS	SPECIAL FEATURES			
MHYXR0110P2G				LEV 3 OPTION2					P	PC D			HCT	
				I	EMISSION	CREDI	T IN	FORMATIC	ON					
GROUP							NMOG CREDIT I NON-PZEV ZEF EVAP		- I I	NMOG CREDIT FO		OR OPTIONAL EXH. STD FOR WORK TRUCKS		
ALL MODELS				N				N		N	N			
NMOG AND FLEET AVERAGE INFORMATION														
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	100200	O/NMHC ATIO	PC+LDT	NMOG+NOX FLEE PC+LDT (0-3750 (g/mi)					(3751 LVW-8500		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		*	0.058 0.065						*			
See the Attachment for Vehicle Models, Evanorative Family, Engine Displacement, Emission Control Systems, Phase-														

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 10th day of December 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
			CERT	STD	CERT	CERT STD C		STD	CER	г	STD	STD CER		STD
FTP@50K		*	*	*	*	*	*	*	* *		*			*
FTP@UL		SOLINE- R3 E10	0.016	0.030	0.2	1.0	*	*	*		4	0.0	02	0.003
50°F @4K		SOLINE- R3 E10	0.024	0.060	0.1	1.0	*	*	*		8			
			NN	NMOG+NOx (g/mi)				CO (g/mi)						
	FUEL TYPE						CE	CERT STD			CER	ERT		STD
HWFET @ 50K		*						r l	*					
HWFET @ UL			GASOI	0.0	09	0.030								
20°F @ 50K		COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)					0.3			10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			3611	- EVUA	JOI EN	1133101	I STANDA	ARD3 /	AND	CERTIFIC	ATION LE	VELƏ				
						US06				SC03		COMPOSITE				
	FUEL TYPE		NMOG+N		OG+NOx		CO PN		NMOG+NOx		со	NMOG+NC	x C)	PM	
				(g/m i)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/n	ni)	(mg/mi)	
@ 4K	@4K *		CERT	*		*	*		*		*					
			STD	*		*			*		*					
		C	ERT	*		*	* 1		*		*	0.013	0.	2	*	
@ UL	@ UL GASOLINE- TIER3 E10				*		6	5		*	*	0.077	4.	2	*	
			BIN									0.030				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																
					W	HOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ING					
	EVAPORATIVE FAMILY		EL TYPE	= 3	3DHS (g/		g/test) @ UL		2DHS (g/test) @ UL			F	RL (g/mi	(g/mi) @ UL		
				CEF	CERT S		FEL	CER	RT	STD	FEL	CE	RT	T STD		
I MHYXR0110P2C I			SOLINE- V3 E10	101	0.178 0.3		*	0.20	0.203 0.300		*	0.	0.00		0.05	
(ORVR / FU	EL ON	NLY / CA	NISTER	BLEE	D EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LI	EVE	LS	
								FU	EL C	NLY EVA	P & CANIS	STER BLEE	D			
	ORATIVE	O	ORVR (g/gallon) @		DUL	FUE				G TEST) @ UL		RIG TEST t) @ UL		LEED CANISTE EST (g/test) @ 4		
		FUEI	L TYPE	CERT	STD	7		CEF	RT	STD	CERT	STD	CERT		STD	
GASOLTNE-		0.03	0.20		*	*		*	*	*	*		*			



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
MHYXR0110P2G	MHYXR0110P2G-AEP	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD		
1	HYUNDAI	IONIQ PLUG-IN HYBRID	PC	1.6	AMS 6	MHYXR0110P2G	1	F		
ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION										

MODEL		UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV			
NUMBER		(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE		
1	TZEV	42.5	42.1	*	39.6	40.0	0.72		