

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FOR	MATION				
MODE		TEST GROUP VEHICLE CLASS(ES)						FUEL C	ATEGORY	FUEL TYPE		
2021	MP	MXV02.0BE3		PC				DEDICATED SINGLE FUEL GASOLINE GASOLINE				
1	USEFUI	LIFE (miles)		VEH	ICLE EMIS	SION C	ATE	GORY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP	-		FTP		SF	TP	FTP	SFTP		
150000 150000 LEV3 SUL						LEV	3 CC	OMPOSITE	*	PM		
SPE		EATURES & EX	HAUST		ON CONTRO	DL		OBD S	TATUS	ENGINE DISPLACEMENT (L)		
1 SFI, WR-HO2S, HO2S, WU-TWC, TWC								FULL	ALL MODELS			
*	* *							PARTIAL *		2.0		
*	* *							TIAL WITH	*			
		E	APOR	ATIVE &	REFUELING	G (EVA	P/OR	VR) FAMIL	INFORMATION			
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	E STD CATE	GORY			SSION STD E CLASS	SPECIAL FEATURES		
M	KMXR01	14BEG		LEV 3	OPTION2			E	PC .	HCT		
				1	EMISSION C	REDIT	INFO	RMATION				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMOG C	REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N		
				NMOG	AND FLEE	TAVE	RAGE	E INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-375 (g/mi)			(0-375		V) LDT	+NOX FLEET ST (3751 LVW-8500 ₹) + MDPV (g/mi)	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	(0.058			0.065	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



KIA MOTORS CORPORATION

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 4774 day of February 2020.

Allen Kyons, Chief Emissions Certification and Compliance Division



KIA MOTORS CORPORATION Executive Order: A-314-0351 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

10000023.96			1									
		NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
1. Dent			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	* GASOLINE- TIER3 E10		LINE- 0.012	* 0.030	* 0.1	* 1.0	*	*	*	*	*	*
FTP@UL								*	* *		0.000	0.003
50°F @4K		OLINE- R3 E10	1 0 016 1		0.2	1.0	*	*	*	8	國語論	
1.00	1100				-		NN	IOG+NO>	c (g/mi)	-	CO (g/mi)
		FUEL TYPE						RT	STD	CER	۲۲ T	STD
HWFET @ 50K		K *							*		19 M S 2	Spilling 1
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.0	0.006 0.030				
20°F @ 50K		COLD	CO E10 RE	GULAR GI	SOLINE	(TIER3)			1. 1. 1. A.	0.4		10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

De est			11100	US06						SC03		C	COMPOSITE			
	FUEL TY	PE		NMOG+I (g/mi		CO (g/mi)	Pl (mg/			OG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)		PM (mg/mi		
@ 4K	*		CERT	*		*				*	*	27250				
e			STD			*	*		*		*	W/ASIN'N	N Y Th			
	GASOLINE- TIER3 E10		CERT	*		* 2		1	*		*	0.012	1.0	*		
@ UL			STD *		*		* 6			*	*	0.077	4.2	*		
			BIN	- 6 P.	bies!		1. (A. 1.)		1812	1122	de mar	0.030	Solar I	8 6152		
		WH	OLE VEH	ICLE EV	APOR	ATIVE E	MISSION	STAN	IDAR	DS AND C	ERTIFIC	ATION LEVE	LS			
					N	HOLE	/EHICLE	EVAP	ORA	TIVE TEST	ING					
	ORATIVE			ELIEL TYDE		E	3DHS (g/		j/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @ U	
				CER		STD	FEL	CERT		STD	FEL	. CEI	CERT			
MEMXR0114BEG			ASOLINE LEV3 E10	101	97 0	. 300	. *	0.2	47	0.300	*	0.01 0.05				
C	DRVR / FUI	EL C	DNLY/CA	NISTER	BLEE	D EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LEVI	ELS		
								FU	JEL C	NLY EVA	P & CANI	STER BLEE	D			
EVAPORATIVE FAMILY		ORVR (g/gal		gallon) (IG TEST)@UL		RIG TEST st) @ UL				
		FU	EL TYPE	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD		
MKMXF	RO114BEG		SOLINE- ER3 E10	0.04	0.20		OLINE- 73 E10			*	*	*	0.004	0.020		

A	CALIFORNIA AIR RESOURCES BOARD
ATT	AIR RESOURCES BOARD

KIA MOTORS CORPORATION Executive Order: A-314-0351 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
MKMXR0114BEG	MKMKR0114BEG-SK3	0.00	0.02							
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-d duty passenger vehicle; HDV: emission limit; GVWR: gross v ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidiz heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRE fuel injection; DFI/IFI: direct/in full/partial/partial with fines on orefix 2: parallel; (2) suffix: sen device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; I automatic transmission; CV: o automated manual transmission	D#LVW; LDT3: LDT 6001-8500#GN luty vehicle; MDV4: MDV 8501-100 heavy-duty vehicle; ECS: emissio vehicle weight rating; LVW: loaded er ULEV; ZEV: zero-emission vehi AC: HC adsorbing catalyst; WU: w selective catalytic reduction-urea/ zer; DPF: diesel particulate filter (a 02S or AFS: wide range/linear/hea or; NH3S: ammonia sensor; EGR: E: secondary air injection (belt drive direct fuel injection; TC/SC: turbo/ -board diagnostic; DOR: direct ozo ries; a hyphen (-) between after tre coated DPF); CNG/LNG: compress E10: "10%" ethanol ("90%"gasoline continuously variable transmission on; AMS: automated manual-select / plug-in hybrid electric vehicle; NI	WR,3751-5750#ALVW; LDT- 000#GVWR; MDV5: MDV 100 n control system; CERT: certi vehicle weight; ALVW: adjust cle; TZEV: transitional ZEV; T arm-up catalyst; NAC: NOx a ammonia; NH3OC: ammonia ctive); GPF: PM filter for spar ated air-fuel ratio sensor; NO> exhaust gas recirculation; HF en)/(electric driven); PAIR: pul super charger; CAC: charge a une reducing; HCT: hydrocarb atment ECS indicates multipl sed/liquefied natural gas; LPC b) fuel; A: automatic (with lock c; SCV: selectable continuousl table transmission; OT: other	001-14000#GVWR; MDPV: medium- fication; STD: standard; FEL: family ted LVW; LEV: low emission vehicle; fWC/OC: 3-way/oxidizing catalyst; udsorption catalyst; SCR-U or oxidation catalyst; CTOX/PTOX: tk-ignited engine; HO2S/O2S: KS: NOx sensor; PMS: PM sensor; P/LP EGR: High/Low Pressure EGR; Ised AIR; SFI/MFI: sequential/multipor air cooler; FFH: fuel fired heater; F/P/\$ ton trap; BCAN: bleed carbon canister; le functionalities of the after treatment G: liquefied petroleum gas; E85: "85% kup); M: manual transmission; SA: sen							

2021 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	SOUL	PC	2.0	SCV1	MKMXR0114BEG	1	F
KIA	SOUL ECO-DYNAMICS	PC	2.0	SCV1	MKMXR0114BEG	1	F