

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				Contraction of Contra											
					TEST G	BROL	JP IN	NFOR	MATION						
YEAR	- 1 7	TEST GROUP		V	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
2021	М	KMXV01.6CC5		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE				
	USEFU	L LIFE (miles)		VEHICLE EMISSION CATEGORY				GORY	T	INTERIM / INT	ERN	ERMEDIATE IN-USE STD			
EXH	I/ORVR	EVA		FTP			SF	SFTP FTP			SFTP				
150000 150000					LEV3 ULEV70	3 ULEV70 LEV 3 C			COMPOSITE *			PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD			BD STATUS		ENGINE DISPLACEMENT		
1	1 DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC								FULL	1	ALL MODELS				
*	*							F	ARTIAL	* 1.			1.6		
*	*								TIAL WITH		*				
			EVA	PORATI	VE & REFUELI	NG (EVA	P/OR	VR) FAMILY	YI	FORMATION				
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						ORY		AP EMISSION STD VEHICLE CLASS		SF	SPECIAL FEATURES			
b	KMXR0	125CCE			LEV 2			PC				*			
					EMISSION		EDIT	INFO	ORMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						N-P2	PZEV NMOG CREDIT FOR DOR				OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N N				N		
				N	MOG AND FLE	EET /	AVE	RAG	E INFORMA	TIC	DN				
NMOG RAF					IHC PC+ID	NMOG+NOX FLEET S PC+LDT (0-3750 LVV (g/mi)			the start protocol protocol of the sector of						
*	*	1.10		* 0.058					0.065				*		
						-		-				-	hal Customa Dhasa		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this and day of July 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

						OG+N (g/mi)			CO (g/mi)			NOx g/mi)		HCH (mg/			P (g/i		
					CERT		STD	CER		TD	CERT	STE		-	STD	c	ERT	STD	
FTP@5	TP@50K *			*	+	*	*		*	*	*	*	+	*		*	*		
FTP@l		GASOLINE TIER3 E1			0.042		0.070	0.0	6 1	. 7	*	*	*	* 4		0.	001	0.003	
50°F @4K GASOLINE- TIER3 E10			0.03	0.033 0.140		0.5 1.7		.7	*	* *		*							
					FU	EL TY				N	NMOG+NOx (g/mi				CO	CO (g/mi)			
											CI	CERT		STD		RT	-	STD	
HWFE	T @ 5	50K					*					*	*						
HWFE	T @ I	UL			GAS	SOLIN	E-TIE	R3 E10		0.	0.027		0.070						
20°F	@ 50	к	CO	LD CO	E10	REGU	LAR G	ASOLIN	NE (TIE	R3)					0.	8		10.0	
				SI	FTP E	XHAL	JST EN	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION LI	EVEL	S				
					US06							SC03			COM		IPOSITE		
	FUE	JEL TYPE				OG+N (g/mi)				PM g/mi)	1	G+NOx /mi)	CO (g/mi)	1			CO g/mi)	PM (mg/mi)	
@4K *		*	CERT		*		*				*	*							
		ST		STD		*		*			*		*						
			CERT			*		*		1		*	*		0.044		0.7	*	
@ UL		GASOLINE- TIER3 E10		STD	*			*	* 6		*		*		0.077		4.2	*	
				BIN									Non-the Owner of the Owner of t		0.070				
			WHO	OLE VE	HICL	EEV							CERTIFIC	ATIO	N LEVE	LS			
							W	HOLE	VEHICLE	EVAP	PORATI	VE TES	FING		4 _				
EVAP	ORAT	2 - C (C (C)	FUEL TYPE		3DHS (g/test) @ UL					2DHS) @ UL	UL		RL (g/mi) @ UL		UL			
CAMILI				CER	T	STD	FEL	CE	RT	STD	FEL		CERT		T STD				
MKMXR0125CCE		1	SOLIN PHAS		0.20		0.50	*	* 0.4		0.65	*		0.00			0.05		
(ORVR	/ FU	EL O	NLY /	CANI	STER	BLEE	DEVAP	ORATIV	EEMI	SSION	STANDA	RDS AND	CE	RTIFICA	TION	LEVE	LS	
													P & CAN						
EVAP FA	ORAT		ORVR (g/gallo			lon) @	on) @ UL FUEL T					HS RIG TEST g/test) @ UL		2DHS RIG 1 (g/test) @				ED CANISTER (g/test) @ 4K	
			FUI	EL TYP	EC	ERT	STD			CI	ERT	STD	CERT		STD	CERT		STD	
MKMXF	R0125	SCCE	T	OLINE IER 2 LEADE	0	.02	0.20		*		* *		*		*	5	*	*	

A	CALIFORNIA AIR RESOURCES BOARD

Executive Order: A-314-0361 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

				Fage 4 01 4						
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	г	STD						
*	*	*		*						
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-od duty passenger vehicle; HDV: emission limit; GVWR: gross v ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi; heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRE fuel injection; DFI/IFI: direct/in full/partial/partial with fines on- prefix 2: parallel; (2) suffix: sen device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; I -automatic transmission; CV: of automated manual transmission; EAER: equivalent AER; PHEV Y = credits, S = credits for som	0#LVW; LDT3: LDT 6001-85 duty vehicle; MDV4: MDV 85 heavy-duty vehicle; ECS: evehicle weight rating; LVW: ber ULEV; ZEV: zero-emission AC: HC adsorbing catalyst; selective catalytic reduction zer; DPF: diesel particulate O2S or AFS: wide range/line for; NH3S: ammonia sensor E: secondary air injection (be idirect fuel injection; TC/SC: -board diagnostic; DOR: dir rise; a hyphen (-) between a coated DPF); CNG/LNG: co E10: "10%" ethanol ("90%"g continuously variable transmon; AMS: automated manua /: plug-in hybrid electric vehi ne/select models	00#GVWR,3751-5750; 01-10000#GVWR; MD mission control system oaded vehicle weight; / on vehicle; TZEV: trans WU: warm-up catalyst; n-urea/ammonia; NH3C filter (active); GPF: PM ear/heated air-fuel ratio EGR: exhaust gas rec elt driven)/(electric drive turbo/super charger; C ect ozone reducing; HC fter treatment ECS indi impressed/liquefied nat asoline) fuel; A: automa ission; SCV: selectable I-selectable transmissio cle; NMOG + NOx Flee	#ALVW; LDT4: I V5: MDV 1000 a; CERT: certifica ALVW: adjusted itional ZEV; TW NAC: NOX ads OC: ammonia ox filter for spark-in sensor; NOXS: circulation; HP/L en); PAIR: pulse AC: charge air CT: hydrocarbon icates multiple fit tural gas; LPG: I atic (with lockup e continuously v on; OT: other tra- et Ave. Credit for	kidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$ trap; BCAN: bleed carbon canister; unctionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: sem variable transmission; AM: ansmission; AER: all-electric range; r Extended Warranty: N = no credits						
2021	MODEL YEAR: V	EHICLE MODE	ELS INFO	RMATION						

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	FORTE	PC	1.6	мб	MKMXR0125CCE	1	F
KIA	FORTE	PC	1.6	AMS7	MKMXR0125CCE	1	F
KIA	FORTE 5	PC	1.6	M6	MKMXR0125CCE	1	F
KIA	FORTE 5	PC	1.6	AMS7	MKMXR0125CCE	1	F