

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		IEOP	MATION					
MODE	1				IESI GRC	JUP IN	TOR	MATION		-			
YEAR		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2021	LMP	MXV03.3EK6		PC				SINGLE FUEL HICLE		GASOLINE			
	USEFUI	LIFE (miles)		VEH	ICLE EMISS	ION C	GORY	INTERIM / IN	MEDIATE IN-USE STD				
EXH	I/ORVR	EVAF		FTP S				FTP		SFTP			
15	50000	15000	LEV3	ULEV125 LEV 3 COM			OMPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	D STATUS		ENGINE DISPLACEMENT (L)		
1 DFI, 2WR-HO2S, 2HO2S, 2WU-TWC, 2TWC, 2TC, CAC								FULL	ALL MODELS				
*	* *							ARTIAL	*	1	3.3		
*	* *							TIAL WITH	*				
		E	VAPO	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	INFORMATION	1			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
P	MKMXR01	40EKE		L	EV 2	V 2			PC D		*		
					EMISSION CR	REDIT	INFO	ORMATION					
CDEDIT FOD EVTENDED						EDIT FOR NON-PZEV ZERO-EVAP			REDIT FOR DOI	2	OPTIONAL EXH. STD FOR WORK TRUCKS		
N N								N N					
NMOG AND FLEET AVERAGE INFORMATION													
					PC+LDT (AOG+NOX FLEET STI C+LDT (0-3750 LVW) (g/mi)			+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m				
*	* * 1.10 * 0.058						0.065 *						
		the second s						D: 1		-	test Queteres Dhees		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 28th day of July 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

KIA MOTORS CORPORATION Executive Order: A-314-0364 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			N			NMOG+NOx (g/mi)			CO (g/mi)			1	HCHO (mg/mi)		PM (g/mi)			
				CERT	r	STD	CER	TS	TD	CERT	STD	CER	T	STD	C	ERT	STD	
FTP@5	OK	*		*		*	*		*	*	*	*	*			*	*	
FTP@I	@UL GASOLINE- TIER3 E10			0.02	6 0	.125	0.2	2 2	.1	*	*	*		4		001	0.003	
50°F @4K GASOLINE- TIER3 E10				0.03	5 0	.250	0.3	3 2	.1	*	*	*	*					
					FU		F			NMOG+NOx (g/mi)				CO (g/mi)				
							-			CE	CERT		STD		CERT		STD	
HWFE	T @ 50M	<				*			*		*	*						
HWFE	T @ UL			GAS	SOLIN	E-TIE	R3 E10		0.	0.012 0.12		5						
20°F	@ 50K	C	OLD CO	E10	REGU	LAR G	ASOLINE (TIER3)							0.	б	10.0		
			S	FTP E	XHAL	IST EN	ISSIO	STANE	ARDS	AND C	ERTIFIC	ATION LE	VEL	.S				
							US06			SC03		3		COM		APOSITE		
	FUEL TYPE			1	IOG+NOx (g/mi)		CO (g/mi)			1	G+NOx /mi)	CO (g/mi)		OG+NO (g/mi)	Ox CO (g/mi)		PM (mg/mi)	
@ 4K	*	*			*		*	<i>i</i>			*	*						
			STD		*		*	*		*		*						
		ASOLINE- IER3 E10			*		*	* 1			*	*	(0.023		0.1	*	
@ UL					*		*		6	*		*	(0.077		4.2	*	
			BIN	•											0.130			
		WH	IOLE VI	EHICL	EEV							CERTIFICA	ATIO	N LEVE	LS			
						W	HOLE	/EHICLE	EVAP	ORATI	VE TEST	ring						
EVAPORATIVE FAMILY		FILE TYPE		3DHS (g/test) @ UL					2DHS (g/test) @ UL			RL		(g/	. (g/mi) @ UL			
					CER	T	STD	FEL	CE	RT	RT STD		FEL		RT	STD		
MKMXR0140EKE		CE C	ASOLIN A PHAS	E 2		0.35 0.		*	0.		0.65	*			0.02		0.05	
C	DRVR / I	FUEL (ONLY /	CANIS	STER	BLEE	EVAP	ORATIV				RDS AND				LEVE	LS	
EVAPORATIVE FAMILY											EL ONLY EVAP & CAN							
		E	ORVR (g/gal			(g/gallon) @ UL				HS RIG TEST g/test) @ UL		2DHS RIG T (g/test) @					/test) @ 4K	
TP.	VIAIS T	FL	JEL TYP	EC	ERT STD		FUE	FUEL TYPE		RT	STD	CERT			STD CER			
MKMXR0140EKE		GA	SOLINE TIER 2 NLEADE	- 0	.02	0.20		*		*	*	*			*		*	

CALI AIR RESC	FORNIA	KIA MOTORS CORPORATION		Executive Order: A-314-0364 New Passenger Cars, Light-Duty Trucks ar Medium-Duty Vehicle Page 4 of 4			
EFFECTIN	E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD		
*	*		*		*		
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRI fuel injection; DFI/IFI: direct/ir full/partial/partial with fines or prefix 2: parallel; (2) suffix: se device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MD : heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-em AC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu IO2S or AFS: wide rang for; NH3S: ammonia se E: secondary air injection direct fuel injection; TC i-board diagnostic; DOF ries; a hyphen (-) betwee coated DPF); CNG/LNG E10: "10%" ethanol ("90 continuously variable tra ion; AMS: automated ma /: plug-in hybrid electric	1-850 V 850 CS: en /W: lo hission lyst; W uction- late fil e/linea nsor; I n (belf /SC: tr C: direc een aft G: con 0%"ga ansmi anual-	0#GVWR,3751-5750 1-10000#GVWR; MD hission control system aded vehicle weight; A vehicle; TZEV: trans /U: warm-up catalyst; urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas red t driven)/(electric drive urbo/super charger; O ct ozone reducing; HO er treatment ECS ind npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectabl selectable transmissi	#ALVW; LDT4: I N/5: MDV 10001 n; CERT: certifica ALVW: adjusted itional ZEV; TW NAC: NOX ads OC: ammonia ox filter for spark-it sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon icates multiple fi tural gas; LPG: atic (with lockup e continuously v on; OT: other tra	idation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; unctionalities of the after treatment liquefied petroleum gas; E85: "85%" o); M: manual transmission; SA: semi		

2021 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD				
KIA	STINGER AWD	PC	3.3	SA8	MKMXR0140EKE	1	F				
KIA	STINGER RWD	PC	3.3	SA8	MKMXR0140EKE	1	F				