

### VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0186

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

|  | Or willon  | ocrimodion | 3.     |                   |                      |                                      |               |                                    |   |           |                                   |  |  |  |
|--|------------|------------|--------|-------------------|----------------------|--------------------------------------|---------------|------------------------------------|---|-----------|-----------------------------------|--|--|--|
|  |            |            |        |                   | TEST GRO             | UP IN                                | IFORI         | MATION                             |   |           |                                   |  |  |  |
| MODE   | _        - | ST GROUP   | VEHICL | VEHICLE CLASS(ES) |                      |                                      | FUEL CATEGORY |                                    |   | FUEL TYPE |                                   |  |  |  |
| 2021   | MV         | SAV02.9N7B |        | PC                |                      |                                      |               | DEDICATED SINGLE FUEL VEHICLE      |   |           | GASOLINE                          |  |  |  |
| USEFUL LIFE (miles) VEHICL   |            |            |        |                   |                      | CLE EMISSION CATEGORY INTERIM        |               |                                    |   |           | TERMEDIATE IN-USE STD             |  |  |  |
| EXH/ORVR EVAP  |            |            |        | F                 | FTP                  |                                      |               | SFTP FTP                           |   |           | SFTP                              |  |  |  |
|  | 0000       | 15000      | 0      | LEV3              | ULEV70 LEV 3 COMPOSI |                                      |               | MPOSITE                            | *   |           | PM                                |  |  |  |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS  |            |            |        |                   |                      | L                                    |               | OBD S                              | STATUS  |           | ENGINE DISPLACEMENT               |  |  |  |
| 2WU-TWC, 2TWC, 2WR-HO2S, 2HO2S, DFI, 2TC,  |            |            |        |                   |                      | c,                                   |               | FULL                               | *   |           |                                   |  |  |  |
| *  |            |            | ,      | *                 |                      |                                      | Р             | PARTIAL ALL MODELS                 |   | 2.9       |                                   |  |  |  |
| *  | *          |            |        |                   |                      |                                      | 1             | PARTIAL WITH *                     |   |           |                                   |  |  |  |
|  |            | E          | VAP    | ORATIVE &         | REFUELING            | (EVA                                 | P/OR          | VR) FAMIL                          | Y INFORMATIO                                      | V         |                                   |  |  |  |
| EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR   |            |            |        |                   |                      | GORY                                 | /             | EVAP EMISSION STD<br>VEHICLE CLASS |   |           | SPECIAL FEATURES                  |  |  |  |
| MVGAR0140NCP LEV 3 OPTION2 WITH  |            |            |        |                   |                      | FEL I                                |               |                                    | PC  |           | *                                 |  |  |  |
|  |            |            |        |                   | MISSION C            | REDI                                 | TINFO         | ORMATION                           |   |           |                                   |  |  |  |
| NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR NON ZERO-EVAP                                  |            |            |        |                   |                      |                                      |               |                                    |   | R         | OPTIONAL EXH. STD FOR WORK TRUCKS |  |  |  |
| N N  |            |            |        |                   |                      |                                      | N N           |                                    |   |           |                                   |  |  |  |
|  |            |            |        | NMOG              | AND FLEE             | TAVE                                 | RAG           | E INFORMA                          | TION  |           |                                   |  |  |  |
| NMOG CH4 NMOG/NMHC HCHO/NMHC PC+LDT  |            |            |        |                   | PC+LDT               | OX FLEET ST<br>(0-3750 LVW)<br>g/mi) |               | V) LDT                             | 6+NOX FLEET S<br>(3751 LVW-850<br>(R) + MDPV (g/m | 0         |                                   |  |  |  |
| *  | *          | 1.10       |        | 0.03 0.058 0.065  |                      |                                      |               |                                    | *   |           |                                   |  |  |  |
| See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase- |            |            |        |                   |                      |                                      |               |                                    |   |           |                                   |  |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



#### VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0186

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 4774

day of May 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 



VOLKSWAGEN GROUP OF AMERICA, INC.

Executive Order: A-413-0186

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

# **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

|                     | EXH                        |                      |         |             |                              |                                     | IVE EMIS  |                                    | NAME OF TAXABLE PARTY.       |                               | And the Party of t |  |                          |  |                            | ELS                       |           |
|---------------------|----------------------------|----------------------|---------|-------------|------------------------------|-------------------------------------|---|------------------------------------|------------------------------|-------------------------------|--|--|--------------------------|--|----------------------------|---------------------------|-----------|
|                     |                            | EX                   | (HA     |             |                              |                                     | IDARDS A  |                                    | -                            |                               |  | The second secon |                          |  |                            |                           |           |
|                     | Fl                         | UEL 1                | TYP     | m<br>a<br>C | onoxide<br>djustme<br>RVR (a | e; NOx: o<br>ent factor<br>HC/galle | MOG: non-<br>oxides of ni<br>; 2DHS/3D<br>on dispense<br>grees Fahr | trogen; F<br>HS [g HC<br>ed]: on-b | ICHO:<br>C/test]:<br>oard re | formald<br>2/3 day<br>fueling | ehyde; P<br>s diurnal·<br>vapor red  | M: particu<br>+hot-soak<br>covery; g:  | late  <br>; RL  <br>gram | matter; R.<br>[g HC/mi]<br>n; mg: mill | AF: re<br>: runn<br>ligram | activi<br>ing lo<br>; mi: | ty<br>ss; |
|                     | A cause existing property. |                      |         |             |                              | G+NOx<br>J/mi)                      |   | CO<br>(g/mi)                       |                              | NOx<br>(g/mi)                 |  | 1  | HCHO<br>(mg/mi)          |  | PM<br>(g/mi                |                           | -         |
|                     |                            |                      |         | -           | CERT                         | STE                                 | CER   |                                    | D                            | CERT                          | STD  | CER  | Т                        | STD                                    | CEF                        | RT                        | STD       |
| FTP@50              | K                          | *                    |         | $\dashv$    | *                            | *                                   | *   | *                                  | _                            | *                             | *  | *  | $\neg$                   | *                                      | *                          |                           | *         |
| FTP@U               | G                          | ASOL<br>IER3<br>PRE  | E1      |             | 0.0386                       | 0.07                                | 0 0.3   | 5 1.                               | 7                            | *                             | *  | *  |                          | 4                                      | 4 0.0010                   |                           | 0.003     |
| 50°F @4             |                            | ASOL<br>IER3<br>PRE  | E1      |             | 0.0392                       | 0.14                                | 0.2   | 5 1.                               | 7                            | *                             | *  | 0.8  |                          | 16                                     | L6                         |                           |           |
|                     |                            |                      |         |             | FUEL TYPE                    |                                     |   |                                    |                              |                               | NMOG+NOx (g/n  |  |                          |  | CO (g/mi)                  |                           |           |
|                     |                            |                      |         |             |                              |                                     |   |                                    |                              |                               | CERT STD   |  |                          | CERT                                   |                            | STD                       |           |
| HWFET @ 50K         |                            |                      |         |             |                              | *                                   |   |                                    |                              | * *                           |  |  |                          |  |                            |                           |           |
| HWFET @ UL GASOLINI |                            |                      |         |             | NE-TIE                       | WE-TIER3 E10 PREM                   |   |                                    | 0.0                          | 162                           | 0.070  |  |                          |  |                            |                           |           |
| 20°F @ 50K GAS      |                            |                      |         | GASOLI      | OLINE-TIER3 E10 PREM         |                                     |   |                                    |                              |                               |  |  | 0.78                     |  | 10.0                       |                           |           |
|                     |                            |                      |         | S           | FTP E                        | (HAUST                              | EMISSION  | STAND                              | ARDS                         | AND C                         | ERTIFIC  | ATION LI   | EVEL                     | _S                                     |                            |                           |           |
|                     |                            |                      |         |             |                              |                                     | US06  |                                    |                              |                               | SC03   |  |                          |  | MPOSITE                    |                           |           |
|                     | FUEL TYPE                  |                      |         |             | G+NOx<br>g/mi)               | CO<br>(g/mi)                        | PM<br>(mg/mi)   |                                    |                              | G+NOx<br>/mi)                 | CO<br>(g/mi)   |  | OG+NOx<br>(g/mi)         |  | CO<br>/mi)                 | PM<br>(mg/mi)             |           |
| - 414               |                            | *                    |         | CERT        |                              | *                                   | *   |                                    |                              |                               | *  | *  |                          |  |                            |                           |           |
| @ 4K                |                            |                      |         |             |                              | *                                   | *   | *                                  |                              |                               | *  | *  |                          |  |                            |                           |           |
|                     |                            |                      |         | CERT        |                              | *                                   | *   | * 3.                               |                              | *                             |  | *  | * 0.0279                 |  | 0                          | . 32                      | *         |
| @ UL                | TIER                       | LINE<br>R3 E1<br>REM | E10 STD |             |                              | *                                   | *   | * 6                                |                              | *                             |  | *  | * 0.077                  |  | 4                          | .2                        | *         |
|                     | -                          | E                    |         | BIN         |                              |                                     |   |                                    |                              |                               |  |  |                          | 0.090                                  |                            |                           |           |
|                     |                            | 1                    | WH      | OLE V       | EHICL                        | E EVAP                              | DRATIVE I   |                                    |                              |                               |  |  | ATIC                     | N LEVE                                 | LS                         |                           |           |
|                     |                            |                      |         |             |                              |                                     | WHOLE   | VEHICLE                            | EVA                          | PORAT                         | IVE TES  | TING   |                          | -                                      | L (g/n                     | ai) 🙉                     | 111       |
|                     |                            | RATIVE FUE           |         | UEL T       | JEL TYPE 3DHS                |                                     | 3DHS (g/test) @ UL  |                                    |                              | 2DH                           | 2DHS (g/test) @  |  | D UL                     |  | - (g/II                    | ''', @                    | JL .      |
| F/                  | AIVII L. Y                 |                      |         |             |                              |                                     | STD   | FEL                                |                              | RT STD                        |  | FEL  |                          | CERT                                   |                            | STD                       |           |
| 1                   |                            | ASOLI<br>IER3<br>PRE | E10     | 0.254       | 0.300                        | 0.300                               | 0.  | 243 0.300                          |                              | 0.3                           | 0.300 0.0  |  | 00                       | 0.05                                   |                            |                           |           |



VOLKSWAGEN GROUP OF AMERICA, INC. Executive Order: A-413-0186

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

| ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS |                              |             |           |                                 |                                |      |                                |      |                                    |       |       |  |
|---|------------------------------|-------------|-----------|---------------------------------|--------------------------------|------|--------------------------------|------|------------------------------------|-------|-------|--|
|   |                              |             |           | FUEL ONLY EVAP & CANISTER BLEED |                                |      |                                |      |                                    |       |       |  |
| EVAPORATIVE FAMILY  | ORVR (                       | g/gallon) @ | FUEL TYPE |                                 | 3DHS RIG TEST<br>(g/test) @ UL |      | 2DHS RIG TEST<br>(g/test) @ UL |      | BLEED CANISTE<br>TEST (g/test) @ 4 |       |       |  |
|   | FUEL TYP                     | E CERT      | STD       |                                 |                                | CERT | STD                            | CERT | STD                                | CERT  | STD   |  |
| MVGAR0140NCP  | GASOLINE<br>TIER3 E1<br>PREM | 1           | 0.20      | GASOLINE-<br>TIER3 E10<br>PREM  |                                | *    | *                              | *    | *                                  | 0.008 | 0.020 |  |
| EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)                         |                              |             |           |                                 |                                |      |                                |      |                                    |       |       |  |
| EVAPORATIVE FAMILY LEAK FAMIL   |                              |             | Y CERT    |                                 |                                |      |                                | STD  |                                    |       |       |  |
| MVGAR0140NCP MVGAR0140NCP   |                              |             |           |                                 | -001 *                         |      |                                |      |                                    | 0.02  |       |  |

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits. S = credits for some/select models

| 2021 MODEL YEAR: VEHICLE MODELS INFORMATION |                |           |            |            |                       |            |     |  |  |  |  |  |
|---|----------------|-----------|------------|------------|-----------------------|------------|-----|--|--|--|--|--|
| MAKE  | MODEL          | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE<br>FAMILY | EXH<br>ECS | OBD |  |  |  |  |  |
| AUDI  | RS 5           | PC        | 2.9        | SA8        | MVGAR0140NCP          | 1          | P   |  |  |  |  |  |
| AUDI  | RS 5 SPORTBACK | PC        | 2.9        | SA8        | MVGAR0140NCP          | 1          | P   |  |  |  |  |  |