

Executive Order: A-003-0759

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODEL YEAR TEST GROUP				VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE		
2022 NMBXD03.0HD4				MDV5				DEDICATED SINGLE FUEL VEHICLE			DIESEL		
	USEFUL	. LIFE (miles)	VEHICLE EMISSION CATEGO				GORY	INTERIM / IN	ΓERM	RMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP			SF	TP	FTP		SFTP		
150000 *			LEV3	S SULEV230 (HOT1 (LA92)		HOT14 A92),	SULEV 135 UC , SC03, F CYCLE)	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTR SYSTEMS						L		OBD S	STATUS		ENGINE DISPLACEMENT (L)		
1	DFI, TC, CAC, EGR, EGRC, OC+DPF, SCRC, WR-HO2S, NOXS(2), PMS, RDQS, FFH							FULL	*				
*			*				Р	ARTIAL *		3.0			
*			*	PAI				TIAL WITH FINES	I AT.T. MODET.S				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVAP / ORVR FAMILY EVAPORATIV					E STD CATEGORY			EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	* *							*			*		
				ı	EMISSION CI	REDIT	INFO	ORMATION					
(REDITEOREXIENDED)					REDIT FOR N ZERO-EVAP	EDIT FOR NON-PZEV ERO-EVAP			REDIT FOR DOP	, ,	OPTIONAL EXH. STD FOR WORK TRUCKS		
N N									N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		CHO/NMHC RATIO NMOG+NOX FLEE LDT (3751 LVW-8500 + MDPV (g/mi				MMOG+NOX FLEET STD W) MDV (8501-10000 GVWR) (g/mi)			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	* * * 0.018 *							0.247					
Caa th	See the Attachment for Vehicle Medela Evenerative Family, Engine Displacement, Emission Central Systems, Phase												

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0759

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2022 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$40,725 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 18th day of January 2022.

Allen 🚧ons, Chief

Emissions Certification and Compliance Division

Executive Order: A-003-0759

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

	EXHA	\US1	ΓAND	EVA	POR	ATIV	E EMIS	SSION	STA	NDAR	DS AN	D CER	TIFIC	CATION	LEV	'ELS)	
		EXH	AUST E	MISSI	ON S	TAND	ARDS A	ND CE	RTIFIC	CATION	LEVELS	(FTP, F	IWFE1	Γ, 50°F, 2	0°F)			
	FUI	≣L TY	m a C	nonoxid djustmo RVR [g	MISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) H4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon onoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity djustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; RVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
				NMHC+NOx (g/mi)		Ox	CO (g/mi)				NOx (g/mi)		HCI (mg/	_		PM (g/mi)		
				CERT		STD	CER	ΓS	TD	CERT			RT	STD	CERT		STD	
FTP@5	0K	*		*		*	*		*	*	*		*			ł	*	
FTP@L		SEL-	EPA	0.142	0	.230	0.1	_	.2	*	*		.1	6	0.0	004	0.010	
50°F @	4K	*		*		*	*		*	*	*	*		*				
					FUE	EL TY	PE				MHC+N					g/mi)		
										CI	ERT	ST		CER	RT		STD	
HWFE	Г @ 50K	50K		*							*							
HWFE	T@UL				DIESEL-EPA					0.	020 0.2		30)				
20°F	@ 50K		*											*		*		
	SFTP EXHAUST EMISSION STANDARDS									AND CERTIFICATION LEVELS								
							US06				SC03 NMHC+NOx CO N				COMPOSITE			
	FUEL 1		ГҮРЕ		NMHC+NOx (g/mi)		CO (g/mi)	PM (mg/m			IHC+NOx (g/mi) (NMHC+NOx (g/mi)		CO J/mi)	PM (mg/mi)	
@ 4K	*		CERT				*			*		*						
		ST			*		*				*	*						
		CEF DIESEL-EPA STI BIN			*			* *			*			0.085		0.0	4	
@ UL	DIESEL				*		*		*		*	*		*	- '	1.0	7	
				EUICL	E E\//	N D O D	A TI\/E E	MISSIC	N CT/	MDADD	S AND	CEDTIE	CATIC	ON LEVE	1.6			
		77	IOLE V	ENICL	CCVA					PORATI			CATIC	JN LEVE	LJ			
	ORATIVI MILY						g/test) @ UL				2DHS (g/test) @ U			<u> </u>		RL (g/mi) @ UL		
						CERT S		FEL	С	ERT	T STD		EL	CERT			STD	
	*	*			*	+		*		*	*		* *		*			
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS											LS							
											JEL ONLY EVAP & CA							
	ORATIVI MILY			R (g/gallon) @ UL		UL	FUE	L TYPE		DHS RIC (g/test)		2DHS RIG (g/test) (_		D CANISTER (g/test) @ 4K		
		FUI				STD			С	ERT	STD	CEF	RT	STD CEF		RT STD		
	*			* *			*		*			*		*		*		
		EFF	ECTIV	E LE	AK D	IAME	TER ST	ANDA	RD A	ND CEF	RTIFICA	TION I	EVE	L (INCHI	ES)			
EVAF	PORATIV	E FA	MILY		LEAK	K FAM	IILY		CERT					STD				
*				*					*					*				



Executive Order: A-003-0759

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES-BENZ	SPRINTER 3500 XD 4X4	MDV5	3.0	A7	*	1	\$