

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP I	NFOR	MATION					
MODE YEA		EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2022	22 NFJXV02.4AJM PC						PC DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY INTERIM / INT							TERM	ERMEDIATE IN-USE STD					
EXI	H/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
1	50000	150000		LEV3	ULEV125	LEV	′3 C	OMPOSITE	*		PM		
SPI	ECIAL F	EATURES & EX SYS	HAUS TEMS		ON CONTRO	L		OBD S	TATUS	EN	ENGINE DISPLACEMENT		
1		TWC(2), WR-H	<b>028</b> , 1	HO2S, SE	FI, DFI			FULL	*				
*	*							PARTIAL	ALL MODELS		2.4		
*	* *							RTIAL WITH *			]		
		E	/APOF	RATIVE &	REFUELING	(EV	AP/OF	RVR) FAMIL'					
EVA	AP / OR	/R FAMILY	EVA	PORATIVE	E STD CATE	GOR	C EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	NFJXR0	1165AC	LE.	V 3 OPTI	ION2 WITH	FEL		I	?C	HCT			
				I	EMISSION CI	REDI	T INF	ORMATION					
		OX FLEET AVE. OR EXTENDED RRANTY	I		EDIT FOR N ZERO-EVAP	ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET		RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	1	O/NMHC RATIO	HC NMOG+NOX FLI PC+LDT (0-375 (g/mi)			N) LDT	NMOG+NOX FLEET STI LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0	.002	0	.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>29th</u> day of June 2021.

Allen Kons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

#### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- LEV3 E10 PREM	0.0280	0.125	0.75	2.1	*	*	0.0	4	0.0004	0.003	
50°F @4K	GASOLINE- LEV3 E10 PREM	0.0284	0.250	0.41	2.1	*	*	0.0	16			
· · · · ·												

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-LEV3 E10 PREM	0.0121	0.125			
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			0.96	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																
						US06			SC03				COMPOSITE				
	FUEL TYPE			NMOG+N	Юx	CO	P	M	NMO	G+NOx	со	NMO	OG+NOx	со	РМ		
				(g/mi)		(g/mi)	(mg	J/mi)	(g	J/mi)	(g/mi)	(	g/mi)	(g/mi)	(mg/mi)		
@ 4K	*		CERT	*	*		* *					*					
-			STD	*		*				*	*						
		C	CERT	*		*	0	0.6		*	*	0.0398		0.77	*		
@ UL	GASOLINE- UL LEV3 E10 PREM		STD	*		*		6		*	*	0.070		4.2	*		
			BIN										.110				
	I	WHO	DLE VE		APO	RATIVE E	MISSION	I STAN	DAR	S AND C	CERTIFIC	ATIO	N LEVELS	;			
						WHOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ING						
	ORATIVE			PE 3	3DHS (g/test) @ UL			2DHS (g/test) @ UL				RL (g/mi) @ UL		UL			
				CEF	R	STD	FEL	CER	RT	STD	FEI	EL CERT			STD		
NFJXR01165AC		-	SOLIN EV3 E: PREM		12	0.300	0.300	0.18	44	0.300	0.30	00 0.000			0.05		



ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS R (g/test	IG TEST ) @ UL		RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4K					
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
NFJXR01165AC	GASOLINE- TIER3 E10 PREM	0.010	0.20	GASOLINE- LEV3 E10 PREM		*	*	*	*	0.0048	0.020		
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY			K FAMII	Y		CE	RT		STD				
NFJXR0116	5AC	NFJXR0	1165AC	-5AC		×			0.02				

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
SUBARU	SUBARU BRZ	PC	2.4	M6, SA6	NFJXR01165AC	1	P
TOYOTA	TOYOTA GR 86	PC	2.4	M6, SA6	NFJXR01165AC	1	P