

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	NFOR	MATION					
MODE YEAI		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE			
2022	2 NE	MXT03.51F1			LDT4			HYBRID ELECTRIC VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	CATE	GORY	INTERIM / INTERMEDIATE IN-USE S				
EX	I/ORVR	EVAP			FTP		SF	FTP FTP			SFTP		
1!	50000	150000		LEV3	ULEV50	LEV	3 CC	MPOSITE	*	PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
1	1 2TWC(2), DFI, SFI, EGR, EGRC, 2WR- HO2S, 2HO2S, 2TC, CAC							FULL	*				
*			*				Р	ARTIAL	ALL MODELS		3.5		
*	*							TIAL WITH FINES	*				
		E	/APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATION				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	/	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	NFMXR02	95LDG	LE	V 3 OPTI	ION2 WITH	FEL		LDT4			HCT		
				I	EMISSION CI	REDIT	r info	ORMATION					
		DX FLEET AVE. DR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAGE		TION				
NIM()(=/NIM(H())				IO/NMHC RATIO	NMOG+NO PC+LDT ((g			/) LDT	+NOX FLEET S⊺ (3751 LVW-8500 R) + MDPV (g/mi				
*	*	1.10		*	0	.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>19th</u> day of September 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/	i+NOx mi)	-	O mi)		Ox mi)		CHO g/mi)	-		
			CERT	STD	CERT STD C		CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.046	0.050	0.4	1.7	*	*	0	4	0.002	2 0.003	
50°F @4K		SOLINE- R3 E10	0.056	0.100	0.4	1.7	*	*	1	16			
					F		NN	NMOG+NOx (g/mi)			CO (g/mi)		
			FUEL TYPE						STD	CER	Т	STD	
HWFET @ 50K				*			*	r	*				
HWFET @ UL		GASOLINE-TIER3 E10						002	0.050				
20°F @ 50K		COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.6	5	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		031 6	1113310	N STAND	4803	AND	CERTIFIC		VELO			
						US06				SC03		С	OMPOS	ITE	
	FUEL TY	PE		NMOG+		СО	Р			OG+NOx		NMOG+NC		-	РМ
				(g/mi)	(g/mi) (mg	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/ı	ni)	(mg/mi)
@ 4K	*		CERT	*		*				*	*				
-			STD			*				*	*				
			CERT	*		*	2	2		*	*	0.030	0.	4	*
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.070	4.	2	*
			BIN									0.060			
		WHC			'APOF	ATIVE	EMISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LEVE	ELS		
					١	VHOLE	VEHICLE	EVAP	ORA	TIVE TEST	ING				
	ORATIVE	FL	JEL TYP	E	3DHS	(g/test)	@ UL		2Dł	IS (g/test)	@ UL	1	RL (g/mi	//mi) (mg).4 /* 1.2 /*	UL
				CE	RT	STD	FEL	CEF	RT	STD	FEL	CE	RT		STD
NFMXF	R0295LDG	-	ASOLINE IER3 E1		18	0.500	0.500	0.1	67	0.500	0.500	0.	00	(0.05
C) DRVR / FUB	EL O	NLY / C	ANISTEF	R BLEE	D EVA	PORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFIC	ATION L	EVE	LS
								FU	JEL C	ONLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE	C	ORVR (g	gallon) (@ UL	FU	EL TYPE	_	-	IG TEST) @ UL	_	tig TEST			-
		FUE	EL TYPE	CERT	STE)		CE	RT	STD	CERT	STD	CERT	-	STD
NFMXF	R0295LDG		SOLINE- ER3 E10	0.01	0.2	D	*	*	r	*	*	*	*		*



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
NFMXR0295LDG	NFMXR0295LDG-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	F150 HEV 2WD	LDT4	3.5	SA10	NFMXR0295LDG	1	P
FORD	F150 HEV 4WD	LDT4	3.5	SA10	NFMXR0295LDG	1	P