

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION						
MODE YEAR		TEST GROUP VEHICLE CLA				E CLASS(ES) FUEL CAT			ATEGORY		FUEL TYPE			
2022	2 NFMXT02.31EM LDT2, LDT3					LDT3 DEDICATED SINGLE FUEL VEHICLE				GASOLINE				
l	USEFUL	LIFE (miles)		VEF	ICLE EMISS	ION C	ATE	GORY	INTERIM / IN	NTERMEDIATE IN-USE ST				
EXH	EXH/ORVR EVAP				FTP			SFTP FTP			SFTP			
15	0000	150000	)	LEV3	ULEV70	LEV	3 CC	OMPOSITE	*		PM			
SPE	CIAL FE	EATURES & EX			ON CONTRO	L		OBD S	TATUS	E	NGINE DISPLACEMENT (L)			
1	TWC	,DFI,WR-HO2S	, но2	S, CAC, TC	, EGR , EGRC			FULL	*					
*			*				P	ARTIAL	*		2.3			
*	*							TIAL WITH	AT.T. MODELS		1			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	Y EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES			
N	IFMXR01	40NDF	LE	EV 3 OPTION2 WITH FEL				LDT2			HCT			
N	IFMXR01	40NDG	LE	V 3 OPTION2 WITH FEL				LDT3			HCT			
				I	EMISSION CI	REDIT		ORMATION	L					
	EDIT FO	X FLEET AVE. DR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N		N			
			•	NMOG	AND FLEET	AVE	RAGI		TION					
NMOG RAF	CH4 RAF RATIO CH4 CH4 CH4 CH4 CH4 CH4 CH4 CH4 CH4 CH4				0-375									
*	*	1.10		*	0	.051		0.056 *						
0 41-							<b>-</b>				ntrol Systems Phase			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2022 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$40,725 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 30th day of October 2021.

Allen yyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCH (mg/I			PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CE	RT	STD	CERT		STD
FTP@50K		*	*	*	*	*	*	*	*		*	*		*
FTP@UL		SOLINE- R3 E10	0.057	0.070	0.6	1.7	*	*	0		4	0.00	01	0.003
50°F @4K		SOLINE- R3 E10	0.049	0.140	0.7	1.7	*	*	1		16			
				FUEL TYP	E		NN	10G+N	Ox (g/mi	)		CO (g	J/mi)	
			l	FUEL ITP	E		CE	RT	STE	)	CER	Т		STD
HWFET @	) 50K			*			*		*					
HWFET @	@ UL		GASOI	LINE-TIEF	R3 E10		0.0	38	0.07	0				
20°F @	50K	COLD (	CO E10 RE	GULAR G	ASOLINE	(TIER3)					1.1		1	L2.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			0.															
			US06					SC03				COMPOSITE						
	FUEL TYP	PE		NMO	OG+NOx	CO	P	M	NMO	G+NOx	со	NM	OG+NOx	C	C	РМ		
				(	(g/mi)	(g/mi)	(mg	g/mi)	(g	g/mi)	(g/mi)		(g/mi)	(g/r	ni)	(mg/mi)		
@ 4K	*		CERT		*	*				*	*							
-			STD		*	*				*	*				1.8			
			CERT		*	*		3		*	*	(	0.049	1.	8	*		
@ UL	GASOLINE- TIER3 E10		STD		*	*	* (		*		*	(	0.070		2	*		
			BIN									(	0.070					
		WH	OLE VE	HICL	E EVAPO	ORATIVE E	MISSION	N STAN	DARI	DS AND O	CERTIFI	CATIO	N LEVELS	5				
						WHOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ſING							
	ORATIVE MILY	F	FUEL TYPE		3DH	S (g/test) @	(g/test) @ UL			IS (g/test)	t) @ UL		RL (g/r		ni) @ UL			
					CERT	STD	FEL	CER	RL	STD	F	EL	CERT		ŝ	STD		
NFMXF	R0140NDF	-	ASOLIN IER3 E		0.373	0.400	0.400	0.33	38	0.400	0.	400	0.00		0.00		0	.05
NFMXF	R0140NDG		ASOLIN IER3 E		0.373	0.500	0.500	0.33	38	0.500	0.	500	0.00	0.00 0		.05		



ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
		FUEL ONLY EVAP & CANISTER BLEED												
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS R (g/test	IG TEST ) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4						
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD			
NFMXR0140NDF	GASOLINE- TIER3 E10	0.10	0.20	GASOL TIER3		* *		*	*	0.015	0.020			
NFMXR0140NDG	GASOLINE- TIER3 E10	0.10	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.015	0.020			
E	EFFECTIVE	LEAK D	IAMET	ER STA	NDARI	D AND CE	RTIFICA		VEL (INCH	ES)				
EVAPORATIVE	EVAPORATIVE FAMILY LEAK FAMIL				Y CERT					STD				
NFMXR0140	NFMXR0140NDF-001				*	7		0.02						
NFMXR0140	NDG	NFMXR0	140NDG	-001		*			0.02					

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	BRONCO 4WD	LDT2	2.3	м7	NFMXR0140NDF	1	\$
FORD	BRONCO 4WD	LDT2	2.3	SA10	NFMXR0140NDF	1	\$
FORD	BRONCO 4WD	LDT3	2.3	SA10	NFMXR0140NDG	1	\$
FORD	BRONCO 4WD	LDT3	2.3	М7	NFMXR0140NDG	1	\$
FORD	BRONCO BADLANDS 4WD	LDT2	2.3	SA10	NFMXR0140NDF	1	\$
FORD	BRONCO BADLANDS 4WD	LDT2	2.3	М7	NFMXR0140NDF	1	\$
FORD	BRONCO BADLANDS 4WD	LDT3	2.3	SA10	NFMXR0140NDG	1	\$
FORD	BRONCO BADLANDS 4WD	LDT3	2.3	м7	NFMXR0140NDG	1	\$
FORD	BRONCO BLACK DIAMOND 4WD	LDT2	2.3	SA10	NFMXR0140NDF	1	\$
FORD	BRONCO BLACK DIAMOND 4WD	LDT2	2.3	м7	NFMXR0140NDF	1	\$
FORD	BRONCO BLACK DIAMOND 4WD	LDT3	2.3	м7	NFMXR0140NDG	1	\$



## 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	BRONCO BLACK DIAMOND 4WD	LDT3	2.3	SA10	NFMXR0140NDG	1	\$
FORD	BRONCO SASQUATCH 4WD	LDT2	2.3	м7	NFMXR0140NDF	1	\$
FORD	BRONCO SASQUATCH 4WD	LDT2	2.3	SA10	NFMXR0140NDF	1	\$
FORD	BRONCO SASQUATCH 4WD	LDT3	2.3	SA10	NFMXR0140NDG	1	\$
FORD	BRONCO SASQUATCH 4WD	LDT3	2.3	М7	NFMXR0140NDG	1	\$